

**WEST 1/4 CORNER SECTION 23, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 439 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 23-15-12.
- 2) G. M WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 20 & 21 FOR THE SURVEY OF THE "SANTA FE ROAD" IN THE NORTHEASTERN PART OF BRECKENRIDGE COUNTY THAT COMMENCED ON JANUARY 11, 1859 AND WAS ESTABLISHED FEBRUARY 29, 1859 IN COMMISSIONER JOURNAL ON PAGE 47 [SEE PACKET 158 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE], SAID THAT **HE FOUND THE STONE WEST 1/4 POST** OF SECTION 23-15-12 ON THIS ROAD SURVEY. SEE THE ROAD SURVEY FOR THE ANGLE STONES THAT HE SET ALONG THE ROUTE.
- 3) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGES 15 & 16 AND DATED JANUARY 11, 1859 FOR A SURVEY OF PART OF THE SANTA FE ROAD IN BRECKENRIDGE COUNTY, SAID THAT **HE FOUND THE WEST 1/4 STONE POST** OF SECTION 23-15-12 ON THIS ROAD SURVEY.
- 4) MATTHEW BROWN, COUNTY SURVEYOR, IN A PLAT OF SURVEY OF SECTION 22-15-12, TO ESTABLISH THE LINES AND CORNERS OF THE NORTH 1/2 OF SECTION 22 MADE UNDER THE DIRECTION OF THE W. D. DEANS, COUNTY SURVEYOR OF WABAUNSEE COUNTY AND MATTHEW BROWN, COUNTY SURVEYOR OF LYON COUNTY ON JULY 18, 19 & 20, 1889 AT THE REQUEST OF S. HOLMES, AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PGE 528 AT THE REGISTER OF DEEDS OFFICE ON JULY 24, 1889, SAID THAT **HE RESET THE ORIGINAL GOVERNMENT STONE** THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 22-15-12 ON LINE AND EQUIDISTANT BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 22-15-12 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 22-15-12 ON THIS **PERMANENT SURVEY**.
- 5) MILES ENGINEERING [GREGORY ALAN MILES, L.S. 667] PLANS FOR BRIDGE 955.6-474.5 SHOWS A **1/2" REBAR** AT THE WEST 1/4 CORNER OF SECTION 23-15-12, BUT THERE ARE NO NOTES IN THE SURVEY TIE FILES SHOWING IF HE FOUND OR SET THIS REBAR. THE TIES BELOW ARE ON THE BRIDGE PLANS. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS REBAR MAY HAVE BEEN "HEELED-IN" FOR THIS BRIDGE SURVEY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) AT STATION 66 + 04.71
  - 2) 36.48' SW TO A NAIL IN A CORNER FENCE POST
  - 3) 41.58' NW TO A NAIL IN A CORNER FENCE POST
  - 4) 36.10' NE TO A NAIL IN A CORNER FENCE POST

WEST QUARTER CORNER 23-15-12