

**WEST 1/4 CORNER SECTION 26, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 438 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 10" X 15" X 3-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 27-15-12, FROM WHICH:
  - 1) A WALNUT TREE 15" IN DIAMETER BEARS S. 28° E. AT 215 LINKS DISTANCE
  - 2) AN ELM TREE 26" IN DIAMETER BEARS N. 25° E. AT 185 LINKS DISTANCE
  
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 14 RECORDED IN SURVEY BOOK "A" ON PAGE 111 DATED FEBRUARY 13, 1868 FOR A SURVEY OF J. BANNICK'S AND J. WILLIAMS LAND, BEING A DIVISION OF THE WEST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 26, AND THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 27-15-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 26-15-12 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

  - 1) 20 CHAINS, 7-1/2 LINKS SOUTH TO THE POST HE SET FOR THE WEST 1/2/4 CORNER OF THE SW1/4 OF SECTION 26-15-12
  - 2) 40 CHAINS, 15 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 26-15-12
  
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 30, 2013 FOR PROJECT NUMBER 13263-02, A SURVEY OF THE WEST LINE OF SECTION 26-15-12 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT 13-38 TO REPLACE BRIDGE NUMBER 957.0-476.4 WITH A 50 FOOT ALL-STEEL BRIDGE, SURVEY F26001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 26-15-12 BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **LOST**. HE RESET THE CORNER ON TRUE LINE AND HALFWAY BETWEEN THE NORTHWEST AND SOUTHWEST SECTION CORNERS. **HE SET A 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 26-15-12. THIS SECTION CORNER IS ALSO PROJECT P.O.T. STATION 0+00.00.
  - 1) 4.00' WEST TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "T" NORTH-SOUTH
  - 2) 114.15' NNW TO THE TOP CENTER OF THE SOUTH END OF A 32" CMP CULVERT
  - 3) 141.35' NNW TO THE TOP CENTER OF THE NORTH END OF A 32" CMP CULVERT
  - 4) 80.60' NNE TO A 40 D SPIKE IN THE WEST FACE OF A WEIGHT LIMIT SIGN POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 500.00' NORTH ON THE SECTION LINE TO THE 1/2" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET FOR P.O.T. STATION 5+00.00
  - 2) 2,643.61' NORTH ON THE SECTION LINE TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 26-15-12
  - 3) 2,643.61' SOUTH ON THE SECTION LINE TO THE 1" PIPE [OVER THE 1/2" IRON PIN] HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SEC. 26-15-12

WEST QUARTER CORNER 26-15-12