

**NORTHWEST CORNER SECTION 27, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 440 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 18" X 3"** FOR THE CORNER TO SECTIONS 21, 22, 27 & 2-15-12.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.55 CHAINS EAST TO THE 18" X 10" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 27-15-12
- 2) 79.10 CHAINS EAST TO THE 28" X 10" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTION S 22, 23, 26 & 27-15-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 118 DATED JULY 13, 1882 ORDERED BY A. T. OLIN TO ESTABLISH THE CORNERS TO THE NORTH 1/2 OF SECTION 28-15-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 28-15-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,645' SOUTH TO THE 14" X 12" X 2" STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 28-15-12
- 2) 5,290' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-15-12
- 3) 2,671-1/2' WEST TO THE 16" X 12" X 2" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 28-15-12
- 4) 5,343' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-15-12

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROD NUMBER 202 RECORDED IN ROAD RECORD BOOK ON PAGES 394 TO 396 PETITIONED BY A. J. OLIN AND OTHER FOR THE LOCATION AND VACATION OF A COUNTY ROAD IN SECTION 28-15-12 [PACKET 472 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON MARCH 31, 1883 AND WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON APRIL 13, 1883 AS NOTED BY J. E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 28-15-12 TO COMMENCE THIS ROAD SURVEY. THE ROAD **VACATED** WAS ALL THAT PART OF THE SANTA FE ROAD IN SECTION 28-15-12. **[NOTE: THE FIELD NOTES AT THE BOTTOM OF PAGE 394 ARE NOT FOR THE ROAD AS PETITIONED. SEE THE FIELD NOTES IN THE PACKET – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE NORTHWEST CORNER OF SECTION 28-15-12; THEN EXTENDS SOUTH ON THE SECTION LINES TO INTERSECT THE SANTA FE ROAD WHERE IT CROSSES THE WEST LINE OF SECTION 28-15-12 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A PLAT OF SURVEY OF SECTION 22-15-12, TO ESTABLISH THE LINES AND CORNERS OF THE NORTH 1/2 OF SECTION 22 MADE UNDER THE DIRECTION OF THE W. D. DEANS, COUNTY SURVEYOR OF WABAUNSEE COUNTY AND MATTHEW BROWN, COUNTY SURVEYOR OF LYON COUNTY ON JULY 18, 19 & 20, 1889 AT THE REQUEST OF S. HOLMES, AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PGE 528 AT THE REGISTER OF DEEDS OFFICE ON JULY 24, 1889, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 22-15-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 3

- 1) 10,609' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 15-15-12 IN WABAUNSEE COUNTY
  - 2) 5,236' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 22-15-12
- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 396 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 526 TO 528 PETITIONED BY W. W. WILSON AND OTHERS FOR TWO ROADS IN TOWNSHIP 15-12 [PACKETS 642 & 655 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 31, 1893, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON SEPTEMBER 11 & 12, 1893, WERE ESTABLISHED AS 40 FEET WIDE FOR THE EAST-WEST ROAD AND 50 FEET WIDE FOR THE NORTH-SOUTH ROAD ON OCTOBER 7, 1893, AS NOTED BY W. N. D. BIRD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 24, 1893 BY C. W. WILHITE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 22-15-12 ON THE SECOND ROAD ON THIS ROAD SURVEY AND THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY. HE NOTED THAT THE SECTION CORNERS WERE IN AND DECLARED TO BE THE CENTER OF SAID ROAD.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE FIRST ROAD EXTENDS EAST ON THE SECTION LINES AT 20 FEET EACH SIDE OF THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-15-12 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
  - 2) THE SECOND ROAD EXTENDS NORTH ON THE SECTION LINES AT 25 FEET EACH SIDE OF THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY
  - 3) THE SECOND ROAD EXTENDS SOUTH ON THE SECTION LINES AT 25 FEET EACH SIDE OF THE SECTION LINE FOR 1 MILE TO THE SECTION CORNER HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-15-12 TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY
- 6) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 60 BY NOTICE FROM JOHN MARTIN TO MAKE A SURVEY OF THE LAND OWNED BY HIM IN SECTION 21-15-12 ON MARCH 17, 1910. ON APRIL 4, 1910 ON THE DAY TO COMMENCE THE SURVEY, AN AGREEMENT WAS MADE BETWEEN JOHN MARTIN, OTTO WHEAT, C. H. WATERS, L. E. BUSH, AND JOHN D. ECHOLS TO HAVE THE ONE FORTH AND ONE EIGHTH CORNER STONES ESTABLISHED ON THE WEST LINE OF THE SECTION AND ON THE CENTER LINE OF THE SECTION RUNNING NORTH. **HE SET A STAKE** FOR THE SOUTHEAST CORNER OF SECTION 21-15-12 BY RUNNING A LINE FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-15-12 OVER THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 21-15-12 AND AT THE SAME DISTANCE BETWEEN THESE TWO FOUND STONES ON THIS **PERMANENT SURVEY**. HE SAID THAT THIS POINT "COINCIDED CLOSELY WITH THE OF THE ROAD RUNNING NORTH AND SOUTH ON THE EAST SIDE OF THE SECTION". THE SURVEY WAS MADE ON APRIL 4 & 5, 1910 AND WAS ENTERED ON MAY 5, 1910.
- HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,653' NORTH TO THE STONE HE FOUND IN PLACE AT THE EAST 1/4 CORNER OF SECTION 21-15-12
  - 2) 5,306' NORTH TO THE STAKE HE SET FOR THE NORTHEAST CORNER OF SECTION 21-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE

HIS INFORMATION IS CONTINUED ON PAGE 3

- 3) 2,670' WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/4 CORNER OF SECTION 21-15-12
  - 4) 5,340' WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 21-15-12
- 7) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGES 87 & 88 AT THE REQUEST OF W. D. BUCHANAN TO PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 28-15-12, SAID THAT **HE PLANTED A 24" X 7" X 6" LIMESTONE WITH THREE NOTCHES ON THE WEST SIDE AND TWO NOTCHES ON THE NORTH SIDE** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 28-15-12 ON THIS **PERMANENT SURVEY**. HE SET THIS CORNER ON A PROLONGATION OF THE LINE FROM THE STONE THAT HE PLANTED FOR THE PERMANENT NORTHWEST CORNER OF SECTION 28-15-12 OVER THE STONE THAT HE FOUND IN PLACE AT THE NORTH 1/4 CORNER OF SECTION 28-15-12 AND AT THE SAME DISTANCE THAT HE MEASURED BETWEEN THESE TWO STONES. THE FIELD SURVEY WAS ON SEPTEMBER 12 TO 15, 1911 AND ENTERED ON JANUARY 2, 1912. SEE ALSO PACKET "M 168" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,670' WEST TO THE STONE HE FOUND IN PLACE AT THE NORTH 1/4 CORNER OF SECTION 28-15-12
  - 2) 5,340' WEST TO THE 17" X 10" X 6" LIMESTONE MARKED WITH 4 NOTCHES ON THE WEST SIDE AND 2 NOTCHES ON THE NORTH SIDE HE PLANTED FOR THE PERMANENT NORTHWEST CORNER OF SECTION 28-15-12
  - 3) 2,643' SOUTH TO THE 18" X 9" X 6" LIMESTONE MARKED "1/4" ON THE WEST SIDE HE PLANTED FOR THE PERMANENT EAST 1/4 CORNER OF SEC. 28-15-12
  - 4) 5,286' SOUTH TO THE 18" X 10" X 6-1/2" LIMESTONE MARKED WITH 3 NOTCHES ON THE WEST SIDE AND ONE NOTCH ON THE NORTH SIDE HE PLANTED FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 28-15-12
- 8) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 63  
ON JULY 5, 1920 A PETITION SIGNED BY WILLIAM WYRICK AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 15-12 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON SEPTEMBER 6, 1920, AND THE FINAL ORDER WAS ISSUED ON SEPTEMBER 11, 1920 TO ACCEPT THE VIEWERS REPORT AS FOLLOWS:
- 1) ROAD PETITIONED: BEGINNING AT THE SOUTHWEST CORNER OF SECTION 22 AND THE NORTHWEST CORNER OF SECTION 27-15-12; FROM THENCE EAST ONE MILE BETWEEN SAID SECTIONS 22 AND 27 TO THE EAST LINE OF SAID SECTIONS, AND TERMINATING AT THAT POINT IN WATERLOO TOWNSHIP
  - 2) VIEWERS RECOMMENDED THAT THE EAST ONE-FOURTH MILE OF ROAD BE **VACATED** FOR THE REASON THAT THIS PART OF THE ROAD IS NOT TRAVELED AND WOULD NOT BENEFIT IF LEFT OPEN
  - 3) VIEWERS RECOMMENDED THAT THE WEST 3/4 MILE BE **NOT** VACATED AS THE ROAD IS NEEDED IN ORDER FOR THE OWNERS TO GET TO THE LAND LYING ON THE EAST SIDE OF THE CREEK
- 9) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 714 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 71 PETITIONED BY WILLIAM WYRICK AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 15-12 AS FOLLOWS: BEGINNING AT THE SOUTHWEST CORNER OF SECTION 22-15-12 AND THE NORTHWEST CORNER OF SECTION 27-15-12; FROM THENCE EAST ONE MILE BETWEEN SAID SECTIONS 22 AND 27 TO THE EAST LINE OF SAID SECTIONS AND TERMINATING THERE. THE ROAD WAS VIEWED BY THE

COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON AUGUST 9, 1920 AND THE VIEWERS RECOMMENDED THAT THE EAST 1/4 OF A MILE BE VACATED FOR THE REASON THAT THIS PART OF THE ROAD IS NOT TRAVELED AND WOULD NOT BE OF MUCH BENEFIT IF LEFT OPEN, AND THE WEST 3/4 OF A MILE BE **NOT** VACATED AS THE ROAD IS NEEDED FOR THE OWNER TO GET TO THE LAND LYING ON THE EAST SIDE OF THE CREEK. THE *RETURN OF SURVEY AND PLAT* SAID THAT THE ROAD WAS **VACATED** AS PETITIONED FOR.

- 10) **COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 147**  
ON APRIL 4, 1936 A PETITION SIGNED BY W. L. SMITH AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 15-12 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON APRIL 27, 1936, THAT **VACATED** THE FOLLOWING ROAD:
  - 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 27-15-12, FROM THENCE EAST ONE MILE TO THE NORTHEAST CORNER OF SAID SECTION 27 AND ENDING THERE.
  - 2) SAID ROAD SHOULD BE VACATED AS PETITIONED.
  - 3) THE ROAD IS IN BAD REPAIR AND PARTIALLY CLOSED BY FENCING.
  - 4) IT WOULD BE AN UNWARRANTED EXPENDITURE IF THE TOWNSHIP BOARD ATTEMPTED TO PUT THIS STRETCH OF ROAD IN A CONDITION SO IT WE BE OF PUBLIC UTILITY.
  - 5) ITS USAGE WOULD NOT JUSTIFY THE EXPENSE.
  
- 11) O. D. HENRY, COUNTY ENGINEER FROM 1929 TO 1944, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK 1 ON PAGE 27 FOR ROAD NUMBER 771 PETITIONED BY W. L. SMITH AND OTHERS TO **VACATE** A ROAD IN TOWNSHIP 15-12 THAT WAS VIEWED ON APRIL 27, 1936 AND ORDERED **VACATED** ON APRIL 27, 1934 AS RECORDED ON PAGE 147 OF BOOK "A" OF THE COMMISSIONERS JOURNAL AS ATTESTED BY TED NEWCOMER, COUNTY CLERK, THE VIEWERS RECOMMENDED THAT THE ROAD BE **VACATED** FOR THE FLOWING REASONS:
  - 1) ROAD IS IN BAD REPAIR AND PARTIALLY CLOSED BY FENCING
  - 2) IT WOULD BE AN UNWARRANTED EXPENDITURE IF THE TOWNSHIP BOARD ATTEMPTED TO PUT THIS STRETCH OF ROAD IN A CONDITION SO IT WOULD BE A PUBLIC UTILITY
  - 3) ITS USAGE WOULD NOT JUSTIFY THE EXPENSE
  - 4) THE FOLLOWING ROAD WAS **VACATED:** BEGINNING AT THE NORTHWEST CORNER OF SECTION 27-15-12; THENCE EAST 1 MILE TO THE NORTHEAST CORNER OF SAID SECTION 27 AND ENDING THERE
  
- 12) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 18, 1982, SAID THAT **HE FOUND A 6" X 7" LIMESTONE WITH A 12" SPIKE BENT OVER THE CENTER OF THE STONE** AT THE NORTHWEST CORNER OF SECTION 27-15-12. HE IDENTIFIED THIS STONE AS THE STONE THAT WAS SET BY J. MAX YINGLING IN PERMANENT SURVEY BOOK 1 ON PAGE 87 IN 1911.
  - 1) 15.7' EAST TO THE NEAR FACE OF A CORNER FENCE POST
  - 2) 19.0' EAST TO A LINE OF POWER POLES NORTH-SOUTH
  - 3) 32.5' WEST TO A LINE OF FENCE TO THE NORTH
  - 4) 20.0' NORTH TO A LINE OF FENCE TO THE WEST
  - 5) 1.0' SOUTH TO A LINE OF FENCE TO THE EAST
  - 6) 7.5' WEST TO THE TRAVELED WAY OF THE NORTH-SOUTH ROAD
  
- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 60 TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF SECTION 29-15-12 PETITIONED BY KEITH ROWLAND, OWNER OF THE NORTHEAST 1/4 AND AGENTS FOR THE NORTHWEST CORNER OF SECTION 29,

AND BY HAROLD AND RUSSELL YEAGER, AGENTS FOR THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 29 THAT BEGAN DECEMBER 9, 1982 AND CONTINUED UNTIL COMPLETION OF DECEMBER 15, 1982, SAID THAT **HE FOUND THE 6" X 7" NOTCHED LIMESTONE THAT WAS SET BY YINGLING [1911, PERMANENT SURVEY BOOK 1 ON PAGE 87] AT 3" DEEP WITH A #5 REBAR ON THE EAST SIDE OF THE STONE AT THE NORTHEAST CORNER OF SECTION 28-15-12 ON THIS PERMANENT SURVEY.** HE NOTED THAT HE HAD ORIGINALLY FOUND THIS STONE ON A ROAD SURVEY IN OCTOBER 1982.

- 1) 19.0' EAST TO A LINE OF POWER POLES NORTH-SOUTH
- 2) 15.7' EAST TO THE NEAR FACE OF A CORNER FENCE POST
- 3) 20.0' NORTH TO A LINE OF FENCE TO THE WEST EXTENDED
- 4) 32.5' WEST TO A LINE OF FENCE TO THE NORTH EXTENDED
- 5) 1.0' SOUTH TO A LINE OF FENCE TO THE WEST EXTENDED
- 6) 7.5' WEST TO THE TRAVELED WAY OF THE ROAD NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,670.10' WEST TO THE GLO STONE HE FOUND STANDING AT THE NORTH 1/4 CORNER OF SECTION 28-15-12, AND HE SET A #5 REBAR WITH A LYON COUNTY CAP ON THE SOUTH SIDE CENTER OF THE STONE
- 2) 5,340.20' WEST TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 28-15-12
- 3) 7,982.15' WEST TO THE 5" X 9" X 17" LIMESTONE WITH PIECES OF THE GLO STONE UNDER AND AROUND IT AS DESCRIBED BY EDMISTON IN SURVEY BOOK "E" ON PAGE 38 IN 1886 AT THE NORTH 1/4 CORNER OF SECTION 29-15-12, AND HE DROVE #5 REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE
- 4) 10,639.70' TO THE 3-1/2" X 18" LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-15-12 THAT WAS SET BY BROWN ON A ROAD SURVEY IN ROAD RECORD BOOK "C" ON PAGES 490 & 538 IN 1891, AND HE DROVE A #5 REBAR WITH A LYON COUNTY CAP ON THE SOUTH SIDE CENTER OF THE STONE
- 5) 5,284.25' SOUTH TO THE 6-1/2" X 10" X 18" NOTCHED LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-15-12 THAT WAS SET BY YINGLING IN PERMANENT SURVEY BOOK 1 ON PAGE 87 IN 1911, AND HE DROVE A #5 REBAR WITH A LYON COUNTY CAP BESIDE THE STONE

- 14) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT **HE FOUND THE 6" X 7" LIMESTONE WITH A 5/8" REBAR ON THE EAST SIDE OF THE STONE AT 3" DEEP** AT THE NORTHEAST CORNER OF SECTION 28-15-12 FROM RECORDED TIES BY STEVEN S. BROSEMER, L.S. 752, DATED DECEMBER 1982, IN PERMANENT SURVEY BOOK 2 ON PAGE 60. KDOT CORNER NUMBER 28505

- 1) 19.0' EAST TO A LINE OF POWER POLES NORTH-SOUTH
- 2) 15.7' EAST TO THE NEAR FACE OF A CORNER FENCE POST
- 3) 32.5' WEST TO A LINE OF FENCE TO THE NORTH EXTENDED
- 4) 20.0' NORTH TO A LINE OF FENCE TO THE WEST EXTENDED
- 5) 1.0' SOUTH TO A LINE OF FENCE TO THE WEST EXTENDED
- 6) 7.5' WEST TO THE TRAVELED WAY OF THE NORTH-SOUTH ROAD

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,284.11' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-15-12
- 2) 2,669.98' WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 28-15-12
- 3) 5,340.16' WEST TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-15-12

NORTHWEST CORNER 27-15-12