

NORTHWEST CORNER SECTION 31, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 27 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 13" X 4"** FOR THE CORNER TO SECTIONS 30 & 31-15-12 ON THE WEST TOWNSHIP BOUNDARY.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION

- 1) 39.89 CHAINS EAST TO THE 22" X 15" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-15-12
 - 2) 79.89 CHAINS EAST TO THE 20" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-12
 - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 27" X 8" X 5" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 31-15-12
 - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 42" X 12" X 7" LIMESTONE THEY SET ON A SLOPE TO THE EAST FOR THE CORNER TO TOWNSHIP 15, SOUTH, RANGES 11 & 12 EAST ON THE 3RD STANDARD PARALLEL
-
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 40 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 162 TO 164 PETITIONED BY L. M. HATCHER AND OTHERS FOR THE VACATION AND RELOCATION OF A PORTION OF THE SANTA FE STATE ROAD [PACKET 142 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 2, 1879, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON OCTOBER 6, 1879, AND WAS RECORDED ON OCTOBER 6, 1879, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-15-12 ON THE RANGE LINE ON THIS ROAD SURVEY. **[NOTE: THE OLD SANTA FE STATE ROAD WAS VACATED FROM THE POINT 500 FEET SOUTH OF THE WEST 1/4 CORNER OF SECTION 31-15-12 EXTENDING NORTHEASTERLY TO THE POINT 1,320' EAST OF THE NORTHEAST CORNER OF SECTION 31-15-12 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE TO A POINT 500' SOUTH OF THE WEST 1/4 CORNER OF SECTION 31-15-12 TO COMMENCE THIS ROAD SURVEY AT THE INTERSECTION OF THE OLD SANTA FE STATE ROAD
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO A POINT 1,320' EAST OF THE NORTHEAST CORNER OF SECTION 31-15-12 AT THE INTERSECTION OF THE OLD SANTA FE STATE ROAD AT THE TERMINUS OF THIS ROAD SURVEY
-
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 186 DATED SEPTEMBER 16, 1880, FOR A COUNTY ROAD IN TOWNSHIP 15-11, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-15-11 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ONE MILE ON THE SECTION LINE TO THE STONE THE FOUND AT THE NORTHWEST CORNER OF SECTION 36-15-11; THEN EXTENDS NORTH ON THE SECTION LINE FOR 900 FEET TO AN ANGLE TO THE NORTHWESTERLY DUE TO 142 MILE CREEK
-
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 78 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 314 TO 316 PETITIONED BY DILL A. AVERY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 15-11 [PACKET 215 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS SURVEYED ON SEPTEMBER 16, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 5, 1880, AND WAS RECORDED ON NOVEMBER 12, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-15-11 ON THE RANGE LINE TO COMMENCE THIS ROAD

SURVEY. [NOTE: A PENCILED NOTE UNDER THE DRAWING STATES: "THIS ROAD WAS DECIDED **ILLEGAL** FEBRUARY 15, 1884 IN THE CASE STATE OF KANSAS VS. A. H. PUTMAN AS PETITION STATED TOWNSHIP 18, RANGE 11 INSTEAD OF 15-11. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 5,280 FEET TO THE NORTHWEST CORNER OF SECTION 36-15-11; THEN EXTENDS NORTH ON THE SECTION LINE FOR 900 FEET TO A TURN TO THE NORTHWESTERLY DUE TO 142 MILE CREEK

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY OF SECTION 36-15-11 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE AND THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 36 SURVEYED MARCH 16, 1882 AND FILED IN MISCELLANEOUS VOLUME 13 ON PAGE 395 ON MARCH 27, 1882 IN THE REGISTER OF DEEDS OFFICE, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-15-11 ON THE RANGE LINE ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,635' WEST TO THE STONE **HE RESET** FOR THE NORTH 1/4 CORNER OF SECTION 36-15-11
 - 2) 5,270' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-15-11
 - 3) 2,643' SOUTH ON THE RANGE LINE TO THE STONE HE SET FOR THE EAST 1/4 CORNER OF SECTION 36-15-11
 - 4) 3,964-1/2' SOUTH ON THE RANGE LINE TO THE STONE HE SET FOR THE EAST 1/8TH CORNER OF THE SE1/4 OF SECTION 36-16-11
 - 5) 5,286' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-15-11 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL

- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 19 FOR A ROAD IN TOWNSHIPS 15 & 16, RANGE 11 FOR J. S. GRIMSLEY, PRINCIPAL PETITIONER, DATED AUGUST 8, 1882, APPARENTLY **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-15-12 ON THE RANGE LINE ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 1 MILE TO THE SOUTHWEST CORNER OF SECTION 31-15-12 ON THE 3RD STANDARD PARALLEL; THEN EXTENDS WEST ON THE 3RD STANDARD PARALLEL FOR 640 FEET TO THE TOWNSHIP CORNER BETWEEN RANGE 11 & RANGE 12; THENCE SOUTH ON THE RANGE LINE FOR 1 MILE TO THE SOUTHEAST CORNER OF SECTION 1-16-11; THEN WEST ON THE SECTION LINES FOR 350 FEET TO AN ANGLE POINT; THEN N. 80° W. FOR 300 FEET TO AN ANGLE POINT; THEN S. 70° W. FOR 300 FEET TO INTERSECT THE SECTION LINE ON THE SOUTH SIDE OF SECTION 1-16-11 AND CONTINUES WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 186 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 330 TO 332 PETITIONED BY J. S. GRIMSLEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-11 & 16-11 [PACKET 401 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 8, 1882, AND WAS

ESTABLISHED AS A 50 FOOT ROAD, **EXCEPT** FOR THE DISTANCE OF 80 RODS SOUTH OF THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 1-16-11 WHICH SHALL BE 35 FEET, ON OCTOBER 5, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 24, 1882 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-15-12 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 3) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
- 4) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 1 MILE TO THE SOUTHWEST CORNER OF SECTION 31-15-12 ON THE 3RD STANDARD PARALLEL; THEN EXTENDS WEST ON THE 3RD STANDARD PARALLEL FOR 640 FEET TO THE TOWNSHIP CORNER BETWEEN RANGE 11 & RANGE 12; THENCE SOUTH ON THE RANGE LINE FOR 1 MILE TO THE SOUTHEAST CORNER OF SECTION 1-16-11; THEN WEST ON THE SECTION LINES FOR 350 FEET TO AN ANGLE POINT; THEN N. 80° W. FOR 300 FEET TO AN ANGLE POINT; THEN S. 70° W. FOR 300 FEET TO INTERSECT THE SECTION LINE ON THE SOUTH SIDE OF SECTION 1-16-11 AND CONTINUES WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 8) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 138 DATED DECEMBER 19, 1882 THROUGH JANUARY 3, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 31 & 32 IN TOWNSHIP 15, RANGE 12, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-15-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 19.77 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 31-15-12
- 2) 39.97 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-15-12
- 3) 59.84 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 31-15-12
- 4) 79.91 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-15-12

NORTHWEST CORNER 31-15-12