

SOUTHWEST CORNER SECTION 31, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 6 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 42" X 12" X 7"** ON AN EAST SLOPE FOR THE CORNER TO TOWNSHIP 15 SOUTH, RANGES 11 & 12 EAST ON THE 3RD STANDARD PARALLEL ON OCTOBER 2, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 23" X 12" X 2-1/2" LIMESTONE THEY SET ON AN EAST SLOPE FOR THE SOUTH 1/4 CORNER OF SECTION 31-15-12
 - 2) 80.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 22" X 15" X 2-1/2" LIMESTONE THEY SET ON A GENTLE WEST SLOPE FOR THE CORNER TO SECTIONS 31 & 32-15-12
- 2) IN NOTES FOR THE STATE ROAD FROM DRAGON CREEK ON THE WYANDOTTE AND SANTA FE ROAD IN OSAGE COUNTY TO ALLEN IN BRECKENRIDGE COUNTY AS RECORDED IN ROAD RECORD BOOK "A" ON PAGE 36; THEY APPARENTLY **FOUND** THE SOUTHWEST CORNER OF SECTION 31-15-12 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY. THE ROAD WAS 66 FEET WIDE.
- THE SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL TO THE SOUTHEAST CORNER OF SECTION 34-15-13 AT THE CORNER WHERE THE COUNTY LINE BETWEEN BRECKENRIDGE AND OSAGE COUNTIES INTERSECS THE 3RD STANDARD PARALLEL

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY OF SECTION 36-15-11 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE AND THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 36 SURVEYED MARCH 16, 1882 AND FILED IN MISCELLANEOUS VOLUME 13 ON PAGE 395 ON MARCH 27, 1882 IN THE REGISTER OF DEEDS OFFICE, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 36-15-11 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,321-1/2' NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE EAST 1/8TH CORNER OF THE SE1/4 OF SECTION 36-15-11
 - 2) 2,643' NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE EAST 1/4 CORNER OF SECTION 36-15-11
 - 3) 5,286' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-15-11
 - 4) 2,640' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 36-15-11
 - 5) 3,964' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 36-15-11
 - 6) 5,284' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-15-11
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 19 FOR A ROAD IN TOWNSHIPS 15 & 16, RANGE 11 FOR J. S. GRIMSLEY, PRINCIPAL PETITIONER, DATED AUGUST 8, 1882, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 31-15-12 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL AT A TURN ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL FOR 640 FEET TO THE TOWNSHIP CORNER BETWEEN RANGE 11 & RANGE 12; THENCE SOUTH ON THE RANGE LINE FOR 1 MILE TO THE SOUTHEAST CORNER OF SECTION 1-16-11; THEN WEST ON THE SECTION LINES FOR 350 FEET TO AN ANGLE POINT; THEN N. 80° W. FOR 300 FEET TO AN ANGLE POINT; THEN S. 70° W. FOR 300 FEET TO INTERSECT THE SECTION LINE ON THE SOUTH SIDE OF SECTION 1-16-11 AND CONTINUES WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 186 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 330 TO 332 PETITIONED BY J. S. GRIMSLEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-11 & 16-11 [PACKET 401 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 8, 1882, AND WAS ESTABLISHED AS A 50 FOOT ROAD, **EXCEPT** FOR THE DISTANCE OF 80 RODS SOUTH OF THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 1-16-11 WHICH SHALL BE **35 FEET**, ON OCTOBER 5, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 24, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER AT THE SOUTHWEST CORNER OF SECTION 31-15-12 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 3) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
 - 4) THIS ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL FOR 640 FEET TO THE TOWNSHIP CORNER BETWEEN RANGE 11 & RANGE 12; THENCE SOUTH ON THE RANGE LINE FOR 1 MILE TO THE SOUTHEAST CORNER OF SECTION 1-16-11; THEN WEST ON THE SECTION LINES FOR 350 FEET TO AN ANGLE POINT; THEN N. 80° W. FOR 300 FEET TO AN ANGLE POINT; THEN S. 70° W. FOR 300 FEET TO INTERSECT THE SECTION LINE ON THE SOUTH SIDE OF SECTION 1-16-11 AND CONTINUES WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 113, RECORDED IN SURVEY BOOK "E" ON PAGE 113 DATED AUGUST 17-19, 1885, AND RECORDED IN VOLUME 41 ON PAGE 34 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SURVEYED PER THE ORDER OF THE **DISTRICT COURT OF LYON COUNTY** TO SURVEY AND SUBDIVIDE SECTION 6-16-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 31-15-12 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL ON THIS **DISTRICT COURT ORDERED SURVEY**. HIS SURVEY NOTES/DRAWINGS SHOWS THE FOLLOWING INFORMATION:
- 1) 600' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 6-16-12
 - 2) 528' EAST ON THE 3RD STANDARD PARALLEL TO THE 3" X 6" X 12" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 6-16-12
 - 3) 1,848' EAST ON THE 3RD STANDARD PARALLEL TO THE 3" X 8" X 14" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-16-12
 - 4) 2,640' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 31-15-12

HIS INFORMATION IS CONTINUED ON PAGE 3

- 5) 3,168' EAST ON THE 3RD STANDARD PARALLEL TO THE 3" X 6" X 12" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 6-16-12
 - 6) 4,488' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-16-12
 - 7) 5,280' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-15-12
 - 8) 7,131' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-16-12
 - 9) 7,920' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12
 - 10) 9,774.6' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 5-16-12
- 7) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 155 OF TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 78 & 79 DATED MARCH 4-6, 1909 AT THE ORDER OF LeMONT DeCAMP TO ESTABLISH THE CORNERS AND BOUNDARIES OF LOTS 3 & 4 OF SECTION 1-16-11 AND ANY OTHER CORNERS THAT MIGHT BE NECESSARY IN SAID SECTION TO ESTABLISH THE SAID CORNERS AND BOUNDARIES OF SAID LOTS, SAID THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER TO SECTIONS 35-15-11 AND **32-15-12** ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. [NOTE: THIS SHOULD BE THE SOUTHWEST CORNER OF SECTION 31-15-12 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR] HE USE THIS STONE AND THE STONE THAT HE FOUND AT THE CORNER TO SECTION 35 & 36-15-11 ON THE 3RD STANDARD PARALLEL TO SET A STONE FOR THE PERMANENT NORTHEAST CORNER OF SECTION 1-16-11.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 600.4' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 1-16-11
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 30, 2013, FOR PROJECT NUMBER 13262-02 TO LOCATE A CERTAIN BRIDGE IN THE SOUTHWEST 1/4 OF SECTION 36-15-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT 13-37, SURVEY F36004 IN THE SURVEY FILE FOR TOWNSHIP 15-11, SAID THAT HE DEEMED THAT THE TOWNSHIP CORNER AT THE SOUTHEAST CORNER OF SECTION 36-15-11 ON THE 3RD STANDARD PARALLEL WAS **LOST**. HE RESET THIS CORNER BY THE RETRACEMENT OF A PERMANENT SURVEY BY R. H. EDMISTON, COUNTY SURVEYOR, RECORDED IN SURVEY BOOK "E" ON PAGE 113 DATED AUGUST 17-19, 1885, AND RECORDED IN VOLUME 1 ON PAGE 34 IN THE LYON COUNTY REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887. **HE SET A 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP** FOR THE SOUTHEAST CORNER OF SECTION 36-15-11 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL.
- 1) 25.10' WSW TO A 40 D SPIKE IN THE TOP OF A BRACE POST
 - 2) 29.80' SW TO A 40 D SPIKE IN THE TOP OF A CORNER FENCE POST
 - 3) 3.00' NORTH OT THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 370 TO THE EAST
 - 4) 12.50' NORTH TO A LINE OF FENCE TO THE WEST EXTENDED
 - 5) 1.00' WEST TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "N" TO THE NORTH EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 526.77' EAST ON THE 3RD STANDARD PARALLEL TO THE 3" X 6" LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF LOT 3 ON THE NORTH LINE OF THE NW1/4 OF SECTION 6-16-12 FROM A SURVEY BY EDMISTON IN 1885

HIS INFORMATION IS CONTINUED ON PAGE 4

- 2) 600.40' WEST ON THE 3RD STANDARD PARALLEL TO THE 6" X 9" LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 6-16-12
- 3) 2,641.02' WEST ON THE 3RD STANDARD PARALLEL TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 36-15-11
- 4) 3,956.04' WEST ON THE 3RD STANDARD PARALLEL TO THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET FOR P. I. STATION 13+28.00 FOR AN ANGLE TO THE NORTHEASTERLY
- 5) 5,284.04' WEST ON THE 3RD STANDARD PARALLEL TO THE SQUARE 5/8" IRON PIN [AND STONE] HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-15-11 AT STATION 0+00.00

SOUTHWEST CORNER 31-15-12