

WEST 1/4 CORNER SECTION 31, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 27 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 27" X 8" X 5"** FOR THE WEST 1/4 CORNER OF SECTION 31-15-12 ON THE WEST TOWNSHIP BOUNDARY.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 16" X 13" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-15-12
- 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 42" X 12" X 7" LIMESTONE THEY SET ON A SLOPE TO THE EAST FOR THE CORNER TO TOWNSHIP 15 SOUTH, RANGES 11 & 12 EAST ON THE 3RD STANDARD PARALLEL

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 40 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 162 TO 164 PETITIONED BY L. M. HATCHER AND OTHERS FOR THE VACATION AND RELOCATION OF A PORTION OF THE SANTA FE STATE ROAD [PACKET 142 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 2, 1879, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON OCTOBER 6, 1879, AND WAS RECORDED ON OCTOBER 6, 1879, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 31-15-12 ON THE RANGE LINE ON THIS ROAD SURVEY.

[**NOTE:** THE OLD SANTA FE STATE ROAD WAS VACATED FROM THE POINT 500 FEET SOUTH OF THE WEST 1/4 CORNER OF SECTION 31-15-12 EXTENDING NORTHEASTERLY TO THE POINT 1,320' EAST OF THE NORTHEAST CORNER OF SECTION 31-15-12 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 500' TO THE POINT TO COMMENCE THIS ROAD SURVEY AT THE INTERSECTION OF THE OLD SANTA FE STATE ROAD
- 2) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE NORTHWEST CORNER OF SECTION 31-15-12 AT A TURN TO THE EAST; THEN CONTINUES EAST ON THE SECTION LINES TO A POINT 1,320' EAST OF THE NORTHEAST CORNER OF SECTION 31-15-12 AT THE TERMINUS OF THIS ROAD SURVEY AT THE INTERSECTION OF THE OLD SANTA FE STATE ROAD

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY OF SECTION 36-15-11 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE AND THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 36 SURVEYED MARCH 16, 1882 AND FILED IN MISCELLANEOUS VOLUME 13 ON PAGE 395 ON MARCH 27, 1882 IN THE REGISTER OF DEEDS OFFICE, SAID THAT **HE SET A STONE** FOR THE EAST 1/4 CORNER OF SECTION 36-15-11 ON THE RANGE LINE EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-15-11 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-15-11 ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,321-1/2' SOUTH ON THE RANGE LINE TO THE STONE HE SET FOR THE EAST 1/8TH CORNER OF THE SE1/4 OF SECTION 36-15-11
- 2) 2,643' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-15-11 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL
- 3) 2,643' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-15-11
- 4) 2,634' WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 36-15-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 5) 3,953-1/4 FEET WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE SW1/4 OF SECTION 36-15-11
 - 6) 5,272-1/2' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 36-15-11
- 4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 138 DATED DECEMBER 19, 1882 THROUGH JANUARY 3, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 31 & 32 IN TOWNSHIP 15, RANGE 12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 31-15-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 79.92 CHAINS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-15-12

WEST QUARTER CORNER 31-15-12