

**CENTER CORNER OF THE NORTHEAST QUARTER SECTION 32, TOWNSHIP 15 SOUTH,  
RANGE 12 EAST**

- 1) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 154, TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 75 DATED FEBRUARY 25-27, 1909 TO SUBDIVIDE SECTION 32-15-12, SAID THAT **HE PLANTED A 6" X 8" X 15" STONE** FOR THE PERMANENT CENTER CORNER OF THE NORTHEAST 1/4 OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,322.5' EAST TO THE STONE HE FOUND AT THE EAST 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 32-15-12
  - 2) 1,327.5' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE SW1/4 OF THE NE1/4 OF SECTION 32-15-12
  
- 2) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12 SAID THAT **HE FOUND A 5" X 6" X 12" LIMESTONE** AT THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 32. HE IDENTIFIED THIS STONE AS THE STONE THAT WAS SET BY J. MAX YINGLING ON A PERMANENT SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 75 DATED FEBRUARY 1909 IN THE COUNTY SURVEYORS OFFICE. **HE SET A 1/2" X 24" REBAR WITH A KDOT CAP AT 0.3 FEET WEST OF THE CENTERLINE OF THE STONE AT 1.5 FEET DEEP.** KDOT CORNER NUMBER 32055
  - 1) IN LINE WITH OLD HEDGE ROW REMNANTS NORTH-SOUTH
  - 2) IN LINE WITH AN OLD FENCE LINE TO THE EAST
  - 3) NO OTHER REFERENCES AVAILABLEHIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:
  - 1) 1,326.99' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/16<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 32-15-12

CENTER CORNER NORTHEAST QUARTER 32-15-12