

NORTH 1/4 CORNER SECTION 32, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 444 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-15-12.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.96 CHAINS WEST TO THE 20" X 14" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-12
- 2) 39.96 CHAINS EAST TO THE 16" X 8" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-15-12

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 138 DATED DECEMBER 19, 1882 THROUGH JANUARY 3, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 31 & 32 IN TOWNSHIP 15, RANGE 12, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-15-12 ON LINE AND MIDWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12 AND THE STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.08-1/2 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 32-15-12
- 2) 40.08-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12
- 3) 60.15-1/2 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 31-15-12
- 4) 80.22-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-15-12
- 5) 100.22-1/2 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 31-15-12
- 6) 119.99-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-15-12 ON THE RANGE LINE
- 7) 80.46 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 168 ORDERED BY J. E. LEEPER TO LOCATE THE NORTHWEST CORNER AND THE LINES AND CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 DATED MAY 5-7, 1887, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,642' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 196 DATED NOVEMBER 20, 1900 ORDERED BY MIKE ROBERTS TO PERMANENTLY ESTABLISH THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE LOCATED 20 FEET NORTH OF A FENCE** AT THE NORTH 1/4 CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 39.90 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-12
 - 2) 80.34-1/2 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-15-12
 - 3) 40.20 CHAINS WEST TO THE CENTER OF THE ROAD AT THE NORTHWEST CORNER OF SECTION 32-15-12 – **NO STONE FOUND**
- 5) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 154, TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK “D” ON PAGE 75 DATED FEBRUARY 25-27, 1909 TO SUBDIVIDE SECTION 32-15-12, SAID THAT **HE FOUND A STONE** AT 10 FEET EAST OF THE MIDWAY POINT BETWEEN THE NORTHEAST CORNER AND THE NORTHWEST SECTION CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**. HE DETERMINED THAT THE THIS STONE THAT HE FOUND **HAD BEEN MOVED**. **HE SET A STONE FOR THE TRUE NORTH 1/4 CORNER OF SECTION 32-15-12** ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12 AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,645’ WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12
 - 2) 10’ EAST TO THE STONE HE FOUND AND HE DETERMINED TO **NOT** BE THE 1/4 CORNER
 - 3) 2,645’ EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-12
- 6) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 44 AND DATED DECEMBER 1909 FOR A ROAD RECORDED IN ROAD RECORD BOOK “D” ON PAGE 437, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 60 TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF SECTION 29-15-12 PETITIONED BY KEITH ROWLAND, OWNER OF THE NORTHEAST 1/4 AND AGENTS FOR THE NORTHWEST CORNER OF SECTION 29, AND BY HAROLD AND RUSSELL YEAGER, AGENTS FOR THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 29 THAT BEGAN DECEMBER 9, 1982 AND CONTINUED UNTIL COMPLETION OF DECEMBER 15, 1982, SAID THAT **HE FOUND THE 4” X 16” X 18” LIMESTONE THAT WAS SET BY YINGLING [1909, SURVEY BOOK “D” ON PAGE 75] AT THE TRUE NORTH 1/4 CORNER** OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**. HE ALSO FOUND THE 5” X 7” LIMESTONE THAT YINGLING FOUND OF “UNKNOWN ORIGIN” AT 10 FEET EAST OF THE **TRUE CORNER STONE**. **HE PLACED A #5 REBAR WITH A LYON COUNTY CAP ON THE NORTH AND SOUTH SIDES AND AT THE CENTER OF THE TRUE CORNER STONE**.
- 1) **10.0’ EAST TO THE 5” X 7” LIMESTONE FOUND “ORIGIN UNKNOWN”**
 - 2) 22.5’ SOUTH TO A LINE OF FENCE EAST & WEST
 - 3) 37.5’ NORTH TO A LINE OF FENCE EAST & WEST
 - 4) 3.5’ EAST TO A LINE OF FENCE TO THE NORTH-EXTENDED
 - 5) 10.0’ EAST TO A LINE OF FENCE TO THE SOUTH-EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,645.15’ WEST TO THE 6” X 7” NOTCHED IRREGULAR LIMESTONE HE FOUND AT THE **TRUE SOUTHWEST CORNER** OF SECTION 29-15-12 WITH A MARKED 2” X 12”

X 12" ROAD STONE FROM 1891 HE FOUND ON THE WEST SIDE OF THE NOTCHED IRREGULAR LIMESTONE, AND HE DROVE A #5 REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE OF BOTH STONES

- 2) 2,645.15' EAST TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 29-15-12
 - 3) 5,298.90' EAST TO THE BROKEN REMAINS OF THE GLO STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 28-15-12 ,AND HE DROVE A #5 REBAR WITH A LYON COUNTY CAP IN THE CENTER OF THE MASS OF STONE PLACING PIECES OF THE BROKEN GLO STONE AROUND THE REBAR
 - 4) 7,965.80' EAST TO THE 6-1/2" X 10" X 18" NOTCHED LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-15-12 THAT WAS SET BY YINGLING IN PERMANENT SURVEY BOOK 1 ON PAGE 87 IN 1911
 - 5) 2,657.55' NORTH TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-15-12
 - 6) 5,310.20' NORTH TO THE 5" X 9" X 17" LIMESTONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 29-15-12, WITH PIECES OF THE GLO STONE UNDER AND AROUND THE STONE AS DESCRIBED BY EDMISTON IN SURVEY BOOK "E" ON PAGE 38 IN 1886, AND HE DROVE #5 REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE
- 8) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT **HE FOUND THE STONE AT 6" DEEP WITH 5/8" REBARS ON THE NORTH AND SOUTH SIDES OF THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 32-15-12 FROM RECORDED TIES BY STEVEN S. BROSEMER, L.S. 752, DATED DECEMBER 1982 IN PERMANENT SURVEY BOOK 2 ON PAGE 60. KDOT CORNER NUMBER 32405
- 1) 22.5' SOUTH TO A LINE OF FENCE EAST-WEST
 - 2) 37.5' NORTH TO A LINE OF FENCE TO EAST-WEST
 - 3) 3.5' EAST TO A LINE OF FENCE TO THE NORTH-EXTENDED
 - 4) 10.0' EAST TO A LINE OF FENCE TO THE SOUTH-EXTENDED
 - 5) 23.7' SSE TO THE CENTERLINE TOP OF A STEEL FENCE CORNER POST
 - 6) 21.9' SOUTH TO THE CENTERLINE OF A STEEL FENCE BRACE POST
 - 7) 40.0' NORTH TO A SET SPIKE & KDOT WASHER IN THE TOP OF A FENCE CORNER POST
 - 8) 8.0' NORTH TO THE TRAVEL WAY OF AN EAST-WEST GRAVEL ROAD
- HIS SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) 2,643.97' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12
 - 2) 5,307.28' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12
 - 3) 2,646.02' EAST TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-12

NORTH QUARTER CORNER 32-15-12