

**NORTHWEST CORNER SECTION 32, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 444 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 2-1/2"** FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-12.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION
  - 1) 39.96 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-15-12
  - 2) 79.92 CHAINS EAST TO THE 16" X 8" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-15-12
  
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 40 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 162 TO 164 PETITIONED BY L. M. HATCHER AND OTHERS FOR THE VACATION AND RELOCATION OF A PORTION OF THE SANTA FE STATE ROAD [PACKET 142 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 2, 1879, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON OCTOBER 6, 1879, AND WAS RECORDED ON OCTOBER 6, 1879, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 31-15-12 ON THIS ROAD SURVEY. [NOTE: THE OLD SANTA FE STATE ROAD WAS VACATED FROM THE POINT 500 FEET SOUTH OF THE WEST 1/4 CORNER OF SECTION 31-15-12 EXTENDING NORTHEASTERLY TO THE POINT 1,320' EAST OF THE NORTHEAST CORNER OF SECTION 31-15-12 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE NORTHWEST CORNER OF SECTION 31-15-12 ON THE RANGE LINE; THEN CONTINUES SOUTH ON THE RANGE LINE FOR 3,140' TO A POINT 500' SOUTH OF THE WEST 1/4 CORNER OF SECTION 31-15-12 TO THE INTERSECTION OF THE OLD SANTA FE ROAD TO COMMENCE THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO A POINT 1,320' EAST OF THE NORTHEAST CORNER OF SECTION 31-15-12 AT THE INTERSECTION OF THE OLD SANTA FE STATE ROAD FOR THE TERMINUS OF THIS ROAD SURVEY
  
- 3) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 138 DATED DECEMBER 19, 1882 THROUGH JANUARY 3, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 31 & 32 IN TOWNSHIP 15, RANGE 12, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 20.07 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 31-15-12
  - 2) 40.14 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-15-12
  - 3) 60.14 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 31-15-12
  - 4) 79.91 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-15-12 ON THE RANGE LINE
  - 5) 40.08-1/2 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-15-12
  - 6) 80.17 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 32-15-12
  
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 168 ORDERED BY J. E. LEEPER TO LOCATE THE NORTHWEST CORNER AND THE LINES AND CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 DATED MAY 5-7,

1887, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,642 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-12

- 5) ROAD NUMBER 353: RECORDED IN ROAD RECORD BOOK "C" ON PAGES 362 TO 363 [PACKET 596 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE]:

ON JULY 11, 1887 A PETITION BY J. E. LEEPER AND 12 OTHERS PRESENTED A PETITION FOR THE LOCATION OF A ROAD WITH OUT VIEW AND SURVEY COMMENCING AT THE NORTHWEST CORNER OF SECTION THIRTY-TWO (32), TOWNSHIP 15 OF RANGE 12, THENCE EAST ON THE SECTION LINE FOR 1 MILE TO THE NORTHEAST CORNER OF SECTION 32-15-12. THE LAND OWNERS ON WHICH THE ROAD IS TO BE LOCATED WAIVE ALL RIGHT TO DAMAGES AS THE ROAD IS FENCED OUT AND THE PUBLIC TRAVEL OVER IT AT THE PRESENT TIME.

WHEREAS, NO LEGAL OBJECTIONS HAVE BEEN MADE TO THE PETITION FOR A ROAD ON THE SECTION LINE, WITHOUT VIEW AND SURVEY, AND WHEREAS THE LAND OWNERS ADJOINING SAID PROPOSED ROAD HAVE RELEASED ALL CLAIMS FOR DAMAGES, AND WHEREAS WE ARE SATISFIED THE ROAD DESCRIBED IN SAID PETITION WILL BE A PUBLIC UTILITY: IT IS HEREBY ORDERED THAT THE WITHIN PETITION BE GRANTED WITHOUT VIEW AND SURVEY, AND SAID ROAD DECLARED LEGALLY ESTABLISHED FORTY FEET IN WIDTH. WITNESS THE BOARD OF COUNTY COMMISSIONERS OF SAID COUNTY AT EMPORIA THIS 11<sup>TH</sup> DAY OF JULY, 1887 BY T. E. McMILLAN, CHAIRMAN. THIS STATEMENT WAS ATTESTED BY ROLAND LAKIN, COUNTY CLERK. IT WAS NOTED THAT THE TRUSTEE WAS NOTIFIED ON SEPTEMBER 7, 1887.

- 6) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, , IN A ROAD SURVEY FOR ROAD NUMBER 386 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 490 TO 492 PETITIONED BY JOSEPH WYRICK AND OTHERS FOR A ROAD IN TOWNSHIP 15-12 THAT HE SURVEYED ON JUNE 16, 1891, WAS ESTABLISHED AS 40 FOOT WIDE ROADS ON APRIL 12, 1892 AS NOTED BY S. V. BITLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON APRIL 26, 1892 BY C. W. WILHITE, COUNTY CLERK, SAID THAT **HE SET A 12" X 12" X 2" ROAD STONE MARKED "R/1M"** FOR THE SOUTHEAST CORNER OF SECTION 30-15-12 AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE TO THE 23" X 18" X 3-1/2" ROAD STONE MARKED "R" HE SET FOR THE SOUTHEAST CORNER OF SECTION 19-15-12 TO BEGIN THIS ROAD SURVEY

- 7) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 399 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 538 TO 540 PETITION BY JOSEPH WYRICK AND OTHERS FOR A ROAD IN TOWNSHIP 15-12 [PACKET 641 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 16, 1891, 1894, WAS ESTABLISHED AS 40 FEET WIDE ROAD ON APRIL 12, 1892, AS NOTED BY S. V. BITLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 23, 1895 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE SET A 12" X 12" X 2" STONE MARKED "R/1M"** FOR THE SOUTHEAST CORNER OF SECTION 30-15-12 FOR THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE "BY GOVERNMENT SURVEY" TO THE 23" X 18" X 3-1/2" STONE MARKED "R" HE SET FOR THE SOUTHEAST CORNER OF SECTION 19-15-12 TO BEGIN THIS ROAD SURVEY

- 8) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 438 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 13 THROUGH 16 PETITION BY G. R. WAGNER AND OTHERS FOR A ROAD IN TOWNSHIP 15-12 [PACKET 677 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 10, 1898, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, LAYING THE ROAD 20 FEET EACH SIDE OF THE SECTION LINE, ON APRIL 9, 1898 AS NOTED BY J. A. MILLES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND ATTESTED TO BY M. Q. STARR, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 31-15-12 TO BEGIN THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY
- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 196 DATED NOVEMBER 20, 1900 ORDERED BY MIKE ROBERTS TO PERMANENTLY ESTABLISH THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT HE USED THE CENTER OF THE ROAD FOR THE NORTHWEST CORNER OF SECTION 32-15-12 AS HE DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 40.20 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-12
  - 2) 80.10 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12
  - 3) 120.54-1/2 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-15-12
- 10) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 154, TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 75 DATED FEBRUARY 25-27, 1909 TO SUBDIVIDE SECTION 32-15-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,645' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-15-12
  - 2) 2,655' EAST TO THE STONE HE FOUND AND HE DETERMINED TO **NOT** BE THE 1/4 CORNER STONE
  - 3) 5,290' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-12
- 11) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 100  
ON MAY 25, 1955 A PETITION SIGNED BY GROVER FEE AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 15-12 WAS PRESENTED TO VERNON E. GRIFFITH, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND W. D. KRETSINGER, COUNTY ENGINEER, ON JUNE 21, 1955 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON JUNE 21, 1955 **VACATED** THE FOLLOWING ROAD:
- 1) BEGINNING AT THE NORTHEAST CORNER OF SECTION 31-15-12, THENCE SOUTH ON SAID SECTION LINE, AND TERMINATING AT THE SOUTHEAST CORNER OF SAID SECTION 31-15-12.

- 12) IN A YELLOW FIELD BOOK LABELED "MISC. 1968-1971" IN THE VAULT IN THE COUNTY ENGINEERS OFFICE ON PAGE 74, IT SHOWS A **STONE** AT THE SOUTHWEST CORNER OF SECTION 29-15-12.
- 1) 39.75' SOUTH TO A SPIKE IN THE TOP OF A CORNER FENCE POST
  - 2) 33.9' SE TO A SPIKE IN THE TOP OF A CORNER FENCE POST
  - 3) 34.1' NE TO A SPIKE IN A TELEPHONE POLE
- 13) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-12 SHOWS A **STONE** AT THE "SW CORNER SECTION 29-15-12" ON NOVEMBER 12, 1971.
- 1) 39.75' SOUTH TO A SPIKE IN THE TOP OF A CORNER FENCE POST
  - 2) 33.9' SE TO A SPIKE IN THE TOP OF A CORNER FENCE POST
  - 3) 34.1' NE TO A SPIKE IN A TELEPHONE POLE
- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 60 TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF SECTION 29-15-12 PETITIONED BY KEITH ROWLAND, OWNER OF THE NORTHEAST 1/4 AND AGENTS FOR THE NORTHWEST CORNER OF SECTION 29, AND BY HAROLD AND RUSSELL YEAGER, AGENTS FOR THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 29 THAT BEGAN DECEMBER 9, 1982 AND CONTINUED UNTIL COMPLETION OF DECEMBER 15, 1982, SAID THAT **HE FOUND THE NOTCHED IRREGULAR LIMESTONE, BROKEN AT THE TOP 14" [APPROXIMATELY 6" X 7"] WITH A MARKED 2" X 12" X 12" LIMESTONE ON THE WEST SIDE [THE ROAD STONE FROM 1891],** WITH A #4 REBAR ON THE EAST SIDE AND BENT OVER THE TOP OF THE STONE, AT THE SOUTHWEST CORNER OF SECTION 29-15-12 ON THIS **PERMANENT SURVEY. HE PLACED A #5 REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE OF BOTH STONES. HE ACCEPTED THE NOTCHED STONE AS THE TRUE SOUTHWEST CORNER OF SECTION 29-15-12.**
- 1) 15.3' WEST TO A LINE OF HEDGE TO THE NORTH-EXTENDED
  - 2) 30.0' SOUTH TO A LINE OF FENCE TO THE WEST-EXTENDED
  - 3) 30.5' SOUTH TO A LINE OF FENCE TO THE EAST-EXTENDED
  - 4) 30.0' NORTH TO A LINE OF FENCE TO THE WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,656.55' NORTH TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-15-12
  - 2) 5,313.10' NORTH TO THE 3-1/2" X 18" LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-15-12 THAT WAS SET BY BROWN IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "C" ON PAGES 490 & 538 IN 1891. HE DROVE A #5 REBAR WITH A LYON COUNTY CAP ON THE SOUTH SIDE CENTER OF THE STONE
  - 3) 2,645.15' EAST TO THE 4" X 16" X 18" LIMESTONE HE FOUND AT THE **TRUE SOUTH 1/4 CORNER OF SECTION 29-15-12** THAT WAS SET BY YINGLING IN SURVEY BOOK "D" ON PAGE 75 IN 1909. HE DROVE #5 REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE **TRUE STONE**
  - 4) 2,655.15' EAST TO THE 5" X 7" LIMESTONE HE FOUND AT 10' EAST OF THE **TRUE CORNER** THAT WAS FOUND BY YINGLING AND **NOT ACCEPTED** IN SURVEY BOOK "D" ON PAGE 75 IN 1900
  - 5) 5,290.30' EAST TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 29-15-12
  - 6) 7,944.05' EAST TO THE BROKEN REMAINS OF THE GLO STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 28-15-12. HE DROVE A #5 REBAR WITH A LYON COUNTY CAP IN THE CENTER OF THE MASS OF STONE, PLACING BROKEN PIECES OF THE GLO STONE AROUND THE REBAR

HIS INFORMATION IS CONTINUED ON PAGE 5

- 7) 10,610.95' EAST TO THE 6-1/2" X 10" X 18" NOTCHED LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-15-12 THAT WAS SET BY YINGLING IN PERMANENT SURVEY BOOK 1 ON PAGE 87 IN 1911. HE DROVE A #5 REBAR WITH A LYON COUNTY CAP BESIDE THE STONE
- 15) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT **HE FOUND THE STONE WITH A 1/2" REBAR ON THE EAST SIDE OF THE STONE AND A 5/8" REBAR ON THE WEST SIDE OF THE STONE AT 6" DEEP** AT THE NORTHWEST CORNER OF SECTION 32-15-12 FROM RECORDED TIES BY STEVEN S. BROSEMER, L.S. 752, DATED DECEMBER 1982, IN PERMANENT SURVEY BOOK 2 ON PAGE 60. KDOT CORNER NUMBER 32305
- 1) 15.3' WEST TO A LINE OF HEDGE TO THE NORTH-EXTENDED
  - 2) 30.0' SOUTH TO A LINE OF FENCE TO THE WEST-EXTENDED
  - 3) 30.5' SOUTH TO A LINE OF FENCE TO THE EAST-EXTENDED
  - 4) 30.0' NORTH TO A LINE OF FENCE TO THE WEST AND TO THE EAST
  - 5) 40.0' NE TO A SET SPIKE & KDOT WASHER IN THE WEST FACE OF A POWER POLE
  - 6) 40.0' SE TO A FOUND SPIKE IN THE TOP OF A CORNER FENCE POST
  - 7) 35.5' NW TO THE NEAR FACE OF A 12" DIAMETER HEDGE CORNER POST
  - 8) 2.0' NORTH TO THE TRAVEL WAY OF THE EAST-WEST GRAVEL ROAD
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,313.31' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-15-12
  - 2) 2,643.97' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-12
  - 3) 5,289.99' EAST TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-12

NORTHWEST CORNER 32-15-12