

SOUTH 1/4 CORNER SECTION 32, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 7 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 15" X 3"** ON A NORTHEAST SLOPE FOR THE SOUTH 1/4 CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON OCTOBER 2, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE 22" X 15" X 2-1/2" LIMESTONE THEY SET ON A GENTLE WEST SLOPE FOR THE CORNER TO SECTIONS 31 & 32-15-12
- 2) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 28" X 10" X 2" LIMESTONE THEY SET ON A NORTHWEST SLOPE FOR THE CORNER TO SECTIONS 32 & 33-15-12

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 138 DATED DECEMBER 19, 1882 THROUGH JANUARY 3, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 31 & 32 IN TOWNSHIP 15, RANGE 12, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-12
- 2) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 32-15-12
- 3) 80.46 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-15-12

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 16 DATED MARCH 17-18, 1884 ORDERED BY JAMES JONES FOR A SURVEY TO ESTABLISH THE SOUTH 1/4 CORNER AND THE CENTER CORNER SECTION 5-16-12, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-12, RECORDED IN VOLUME 41 ON PAGE 13 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-12 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-12 TO SET THE PERMANENT NORTH 1/4 CORNER OF SECTION 5-16-12 AND THE PERMANENT NORTHEAST CORNER OF SECTION 5-16-12.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 11.95 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE 3" X 10" X 20" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 5-16-12
- 2) 40.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-12
- 3) 28.10 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 3" X 12" X 18" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 5-16-12
- 4) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-12

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 113, RECORDED IN SURVEY BOOK "E" ON PAGE 113 DATED AUGUST 17-19, 1885, AND RECORDED IN VOLUME 41 ON PAGE 34 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SURVEYED PER THE ORDER OF THE **DISTRICT COURT OF LYON COUNTY** TO SURVEY AND SUBDIVIDE SECTION 6-16-12, SHOWS ON HIS SURVEY DRAWING

THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **DISTRICT COURT ORDERED SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,854.6' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 5-16-12
- 2) 789' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-16-12
- 3) 2,640' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-15-12
- 4) 3,432' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-16-12
- 5) 4,752' WEST ON THE 3RD STANDARD PARALLEL TO THE 3" X 6" X 13" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 6-16-12
- 6) 5,280' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 31-15-12
- 7) 6,072' WEST ON THE 3RD STANDARD PARALLEL TO THE 3" X 8" X 14" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SEC. 6-16-12
- 8) 7,392' WEST ON THE 3RD STANDARD PARALLEL TO THE 3" X 6" X 12" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 6-16-12
- 9) 7,920' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-12
- 10) 8,520' WEST TO THE STONE HE FOUND AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-16-12

- 5) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT **HE FOUND A 3" X 9" X 11" LIMESTONE AT 1.4 FEET DEEP** AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL. **HE IDENTIFIED THIS STONE AS THE GLO STONE** USED BY RICE, COUNTY SURVEYOR, ON A RECORDED PERMANENT SURVEY DATED 1883. **HE SET A 5/8" X 24" REBAR WITH AN ALUMINUM KDOT CAP 0.2 FEET NORTH OF THE CENTERLINE OF THE STONE.** KDOT CORNER NUMBER 32805
- 1) 33.0' NW TO A SET SPIKE & KDOT WASHER IN THE EAST FACE OF A 10" ELM TREE
 - 2) 28.0' NORTH TO A SET SPIKE & KDOT WASHER IN THE EAST FACE OF A 12" HEDGE TREE
 - 3) IN LINE WITH A FENCE TO THE NORTH
 - 4) 29.0' NORTH TO A FENCE TO THE WEST
 - 5) 24.7' SOUTH TO AN EAST-WEST FENCE LINE
 - 6) 2.0' NORTH TO THE TRAVEL WAY OF THE EAST-WEST GRAVEL ROAD

HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:

- 1) 5,307.28' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-12
- 2) 2,649.68' EAST ON THE 3RD STANDARD PARALLEL TO THE 1/2" REBAR WITH A KDOT ALUMINUM CAP HE SET FOR THE SOUTHEAST CORNER OF SEC. 32-15-12

SOUTH QUARTER CORNER 32-15-12