

**NORTH 1/4 CORNER SECTION 33, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 442 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-15-12.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 39.55 CHAINS WEST TO THE 16" X 8" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-15-12
  - 2) 39.55 CHAINS EAST TO THE 22" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-15-12
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 13 RECORDED IN SURVEY BOOK "A" ON PAGE 109 DATED FEBRUARY 12, 1868 FOR A SURVEY OF MARION WEAVER'S LAND, BEING THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 33-15-12, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 33-15-12 ON THIS SURVEY.
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 168 ORDERED BY J. E. LEEPER TO LOCATE THE NORTHWEST CORNER AND THE LINES AND CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 DATED MAY 5-7, 1887, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 33-15-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,666' WEST TO THE 9" X 16" X 20" LIMESTONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 33-15-12
  - 2) 2,676' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-15-12
  - 3) 1,317' SOUTH TO THE STONE HE FOUND AT THE EAST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 33-15-12
  - 4) 2,634' SOUTH TO THE TEMPORARY STAKE HE SET FOR THE CENTER CORNER OF SECTION 33-15-12
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 196 DATED NOVEMBER 20, 1900 ORDERED BY MIKE ROBERTS TO PERMANENTLY ESTABLISH THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 33-15-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.44-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12
  - 2) 80.34-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-15-12
  - 3) 120.54-1/2 CHAINS WEST TO THE CENTER OF THE ROAD AT THE NORTHWEST CORNER OF SECTION 31-15-12 – **NO STONE**
- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGES 87 & 88 AT THE REQUEST OF W. D. BUCHANAN TO PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 28-15-12, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTH 1/4 CORNER OF SECTION 28-15-12 ON

THIS **PERMANENT SURVEY**. THE FIELD SURVEY WAS ON SEPTEMBER 12-15, 1911 AND ENTERED ON JANUARY 2, 1912. SEE ALSO PACKET "M 168" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,666' WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 28-15-12, AND HE DEEMED THIS STONE TO BE IN ITS ORIGINAL LOCATION AND TO MARK THE **TRUE SITE** OF THE SOUTHWEST CORNER OF SECTION 28-15-12
  - 2) 2,666' EAST TO THE 18" X 10" X 6-1/2" LIMESTONE MARKED WITH 3 NOTCHES ON THE WEST SIDE AND ONE NORTH ON THE NORTH SIDE HE PLANTED FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 28-15-12
  - 3) 1,323'-11" NORTH TO THE 18" X 12" X 5" LIMESTONE MARKED WITH A CROSS ON THE NORTH SIDE HE PLANTED FOR THE PERMANENT SOUTHEAST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 28-15-12
  - 4) 2,647'-10" NORTH TO THE 21" X 15" X 3" LIMESTONE MARKED WITH A CROSS ON THE NORTH AND SOUTH SIDES HE PLANTED FOR THE PERMANENT CENTER CORNER OF SECTION 28-15-12
- 6) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 135  
ON NOVEMBER 14, 1934 A PETITION SIGNED BY FRANK LEWIS AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 15-12 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON DECEMBER 19, 1934, AND THE FINAL ORDER WAS ISSUED ON DECEMBER 19, 1934 THAT **VACATED** THE FOLLOWING ROAD:
- 1) BEGINNING AT THE NORTHWEST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 28-15-12; THENCE RUNNING EAST ONE-HALF MILE TO THE NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 ; THENCE SOUTH ONE-FOURTH MILE TO THE SOUTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 28-15-12 AND TERMINATING THERE
  - 2) SAID ROAD SHOULD BE VACATED. SAID ROAD AS PETITIONED IS NOT PASSABLE FOR TRAFFIC BEYOND THE POLLOCK HOME.
  - 3) SAID ROAD DOES NOT SEEM TO BE OF PUBLIC UTILITY AND EVEN THOUGH IT WERE IMPROVED IS USAGE WOULD NOT JUSTIFY THE PUBLIC EXPENDITURE OF CONSTRUCTION AND MAINTENANCE
- 7) O. D. HENRY, COUNTY ENGINEER FROM 1929 TO 1944, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK 1 ON PAGE 23 FOR ROAD NUMBER 767, PETITIONER BY FRANK LEWIS AND OTHERS TO **VACATE** A ROAD IN TOWNSHIP 15-12 THAT WAS VIEWED ON JANUARY 5, 1935 AND WAS **VACATED** ON JANUARY 9, 1935 AS RECORDED ON PAGE 135 OF BOOK "A" OF THE COMMISSIONERS JOURNAL AS NOTED BY TED NEWCOMER, COUNTY CLERK. THE VIEWERS RECOMMENDED THAT THE ROAD AS PETITIONED IS NOT PASSABLE FOR TRAFFIC BEYOND THE POLLOCK HOME, AND SAID ROAD DOES NOT SEEM TO BE OF PUBLIC UTILITY, AND EVEN THOUGH IT WERE IMPROVED ITS USAGE WOULD NOT JUSTIFY THE PUBLIC EXPENDITURE OF CONSTRUCTION AND MAINTENANCE.  
THE FOLLOWING ROAD WAS VACATED: BEGINNING AT THE NORTHWEST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 28-15-12; THENCE RUNNING EAST ONE-HALF MILE TO THE NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 28; THENCE SOUTH ONE-FOURTH OF A MILE TO THE SOUTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 28-15-12 AND THERE ENDING.
- 8) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 15 AT THE REQUEST OF FRED BOLINE TO

LOCATE AND PERMANENTLY ESTABLISH THE SOUTH LINE OF THE NORTHWEST 1/4 OF SECTION 35-15-12 THAT WAS BEGAN ON MARCH 22, 1956 AND CONTINUED UNTIL THE SURVEY WAS COMPLETED ON MARCH 29, 1956, WITH THE EXCEPTION OF ONE DAY, NAMELY MARCH 27, SAID THAT **HE FOUND THE ORIGINAL STONE** AT THE NORTH 1/4 CORNER OF SECTION 33-15-12 ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN ON MARCH 22, 1956 AND WAS COMPLETED ON MARCH 29, 1956.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,666' EAST TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF SECTION 28-15-12
  - 2) 5,304.5' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 34-15-12
  - 3) 7,943.0' EAST TO THE IRON PIN HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 35-15-12
- 9) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 19, 1982, SAID THAT **HE FOUND THE BADLY DETERIORATED GLO STONE** AT THE SOUTH 1/4 CORNER OF SECTION 28-15-12 THAT WAS FOUND ON A 1911 PERMANENT SURVEY AND ON A 1956 PERMANENT SURVEY. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP IN THE CENTER OF THE MASS OF THE BROKEN STONE** FOR THE SOUTH 1/4 CORNER OF SECTION 28-15-12.
- 1) 9.0' EAST TO A LINE OF FENCE TO THE NORTH-EXTENDED
  - 2) 12.0' SOUTH TO A LINE OF FENCE TO THE WEST-EXTENDED
  - 3) 12.9' WNW TO A SPIKE & WASHER IN A 10" DIAMETER ASH TREE
  - 4) 45.3' WSW TO A SPIKE & WASHER IN A TWIN HACKBERRY TREE
  - 5) 2,666.9' EAST TO THE NORTHEAST CORNER OF SECTION 33
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 60 TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF SECTION 29-15-12 PETITIONED BY KEITH ROWLAND, OWNER OF THE NORTHEAST 1/4 AND AGENTS FOR THE NORTHWEST CORNER OF SECTION 29, AND BY HAROLD AND RUSSELL YEAGER, AGENTS FOR THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 29 THAT BEGAN DECEMBER 9, 1982 AND CONTINUED UNTIL COMPLETION OF DECEMBER 15, 1982, SAID THAT **HE FOUND THE BROKEN REMAINS OF THE GLO STONE** AT THE SOUTH 1/4 CORNER OF SECTION 28-15-12 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE. **HE SET A #5 REBAR WITH A LYON COUNTY CAP IN THE CENTER OF THE MASS, PLACING THE BROKEN STONE AROUND THE REBAR.** HE NOTED THAT THIS CORNER WAS ORIGINALLY FOUND BY HIM ON A ROAD SURVEY IN 1982.
- 1) 12.9' WNW TO A SPIKE & WASHER IN A 10" DIAMETER HACKBERRY TREE
  - 2) 45.3' WSW TO A SPIKE & WASHER IN A TWIN HACKBERRY TREE
  - 3) 9.0' EAST TO A LINE OF FENCE TO THE NORTH-EXTENDED
  - 4) 12.0' SOUTH TO A LINE OF FENCE TO THE WEST-EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,653.75' WEST TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 29-15-12
  - 2) 5,298.90' WEST TO THE 4" X 16" X 18" LIMESTONE HE FOUND AT THE **TRUE** SOUTH 1/4 CORNER OF SECTION 29-15-12, THAT WAS SET BY YINGLING IN SURVEY BOOK "D" ON PAGE 75 IN 1909
  - 3) 7,944.05' WEST TO THE 6" X 7" NOTCHED IRREGULAR LIMESTONE HE FOUND AT THE **TRUE** SOUTHWEST CORNER OF SECTION 29-15-12 WITH A 2" X 12" X 12" MARKED LIMESTONE ROAD STONE ON THE WEST SIDE OF THE IRREGULAR NOTCHED LIMESTONE, AND HE DROVE A #5 REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE OF BOTH STONES

HIS INFORMATION IS CONTINUED ON PAGE 4

- 4) 2,666.90' EAST TO THE 6-1/2" X 10" X 18" NOTCHED LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-15-12 THAT WAS SET BY YINGLING IN PERMANENT SURVEY BOOK 1 ON PAGE 87 IN 1911
- 11) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT **HE FOUND THE GLO STONE REMAINS WITH A 5/8" CAPPED REBAR IN THE CENTER OF THE REMAINS** AT THE NORTH 1/4 CORNER OF SECTION 33-15-12 FROM RECORDED TIES BY STEVEN S. BROSEMER, L.S. 752, DATED DECEMBER 1982, WHO FOUND THE GLO STONE REMNANTS FROM A 1911 PERMANENT SURVEY AND DROVE THIS 5/8" X 24" REBAR AND A LYON COUNTY CAP IN THE CENTER OF THE MASS OF THE STONE. KDOT CORNER 33405
- 1) 12.9' NNW TO A SPIKE & WASHER IN A 10" DIAMETER HACKBERRY TREE
  - 2) 9.0' EAST TO A LINE OF FENCE TO THE NORTH-EXTENDED
  - 3) 12.0' SOUTH TO A LINE OF FENCE TO THE WEST-EXTENDED
  - 4) 2,666.9' EAST TO THE NORTHEAST CORNER OF SECTION 33-PRIOR RECORDED BY STEVE BROSEMER AND CHECKED GOOD.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,653.77' WEST TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12
  - 2) 2,666.93' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-15-12
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 1, 2008 FOR PROJECT NUMBER 08089-02 AND SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, FOR A SURVEY FROM GLEN O. COATS TO ESTABLISH THE NORTH LINE OF THE EAST 1/2 OF THE NORTHWEST 1/4, AND THE NORTH LINE OF THE WEST 1/2 OF THE NORTHEAST 1/4, ALL IN SECTION 33-15-12, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 33-15-12 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE. **[NOTE: HIS PREVIOUS REFERENCES INDICATE THAT THIS REBAR WAS DRIVEN IN THE BROKEN REMAINS OF THE GLO STONE – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- 1) 12.9' NNW TO A SPIKE & WASHER IN A 10" DIAMETER HACKBERRY TREE
  - 2) 9.0' EAST TO A LINE OF FENCE TO THE NORTH-EXTENDED
  - 3) 12.0' SOUTH TO A LINE OF FENCE TO THE WEST-EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,326.89' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 33-15-12
  - 2) 2,653.78' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 33-15-12
  - 3) 1,333.46' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 33-15-12
  - 4) 2,666.92' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 33-15-12

NORTH QUARTER CORNER 33-15-12