

NORTH 1/16TH CORNER OF THE NORTHEAST QUARTER SECTION 33, TOWNSHIP 15 SOUTH, RANGE 12 EAST

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 1, 2008 FOR PROJECT NUMBER 08089-02 AND SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, FOR A SURVEY FROM GLEN O. COATS TO ESTABLISH THE NORTH LINE OF THE EAST 1/2 OF THE NORTHWEST 1/4, AND THE NORTH LINE OF THE WEST 1/2 OF THE NORTHEAST 1/4, ALL IN SECTION 33-15-12, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 33-15-12 ON TRUE LINE AND HALFWAY BETWEEN THE NORTH 1/4 CORNER OF SECTION 33-15-12 AND THE NORTHEAST CORNER OF SECTION 33-15-12.

- 1) 91.5' SE TO AN UNDERGROUND TELEPHONE SIGN
- 2) 61.0' EAST TO THE CENTERLINE TRAVELED WAY OF A DRIVEWAY TO THE SOUTH
- 3) 9.0' NORTH TO A FENCE LINE TO THE EAST EXTENDED
- 4) NO OTHER REFERENCES AVAILABLE

HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:

- 1) 1,333.46' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 33-15-12
- 2) 1,333.46' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 33-15-12
- 3) 2,660.35' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 33-15-12
- 4) 3,987.24' WEST TO THE THEORETICAL POSITION OF THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 33-15-12

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 33-15-12