

NORTHWEST CORNER SECTION 33, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 441 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 8" X 5"** FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-15-12, FROM WHICH:
 - 1) AN ELM TREE BEARS S. 80° E. AT 250 LINKS DISTANCE
 - 2) AN ELM TREE BEARS N. 82° E. AT 255 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION

 - 1) 39.55 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-15-12
 - 2) 79.10 CHAINS EAST TO THE 24" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-15-12

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 12 RECORDED IN SURVEY BOOK "A" ON PAGE 109 DATED FEBRUARY 12, 1868 TO SURVEY THE WEST LINE OF SECTION 33-15-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 33-15-12 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 40 CHAINS, 23 LINKS SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 33-15-12
 - 2) 80 CHAINS, 46 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 19 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 74 TO 76 FOR A PETITION BY J. E. LEEPER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-12 AND 16-12 [PACKET 8 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 26, 1879, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON APRIL 7, 1879, AND RECORDED ON APRIL 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 32-15-12 ON THIS ROAD SURVEY. HE NOTED THAT THE HEDGE FENCE ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 33-15-12 WAS TO BE EAST LINE OF THE ROAD.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL; THEN EXTENDS WEST ON THE 3RD STANDARD PARALLEL FOR 787 FEET TO THE NORTHEAST CORNER OF SECTION 5-16-12; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 17-16-12 TO THE TERMINUS OF THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 118 DATED JULY 13, 1882 ORDERED BY A. T. OLIN TO ESTABLISH THE CORNERS TO THE NORTH 1/2 OF SECTION 28-15-12, SAID THAT HE DID **NOT** FIND THE GOVERNMENT STONE AT THE SOUTHWEST CORNER OF SECTION 28-15-12. **HE SET A 14" X 8" X 2" STONE FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 28-15-12** ON THIS **PERMANENT SURVEY** FROM THE FOLLOWING WITNESS TREES: 250 LINKS N. 79° W. FROM A MARKED ELM TREE AND S. 81° W. FROM ANOTHER MARKED ELM TREE. AT THE INTERSECTION OF THESE LINES HE SET THE STONE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,655-1/2' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER ON THE WEST SIDE OF SECTION 28-15-12
 - 2) 5,311' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-15-12
- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 138 DATED DECEMBER 19, 1882 THROUGH JANUARY 3, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 31 & 32 IN TOWNSHIP 15, RANGE 12, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 32-15-12 ON LINE AND MIDWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-15-12 AND THE STONE THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
- 1) 40.18-1/4 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 32-15-12
 - 2) 80.36-1/2 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL
 - 3) 80.36-1/2 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-15-12
 - 4) 40.08-1/2 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-15-12
 - 5) 80.17 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12
 - 6) 100.24 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 31-15-12
 - 7) 120.31 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-15-12
 - 8) 140.31 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 31-15-12
 - 9) 160.08 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-15-12 ON THE RANGE LINE
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 165, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 165 FOR ROAD IN TOWNSHIP 15-12 FOR F. M. WEAVER, PRINCIPAL PETITIONER, DATED FEBRUARY 23, 1887, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 33-15-12 TO BEGIN THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 34-15-12 TO END THIS ROAD SURVEY
 - 2) **NOTE:** ONLY THE EAST MILE BETWEEN THE NORTH 1/4 CORNER OF SECTION 33-15-12 TO THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 34-15-12 WAS APPROVED – THE WEST 1/2 MILE FROM THE NORTHWEST CORNER OF SECTION 33-15-12 EAST TO THE NORTH 1/4 CORNER OF SECTION 33-15-12 WAS **REJECTED** – SEE ROAD RECORD BOOK "C" ON PAGE 356 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 352 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 354 TO 356 PETITION BY F. M. WEAVER AND OTHERS FOR A ROAD IN TOWNSHIP 15-12 [PACKET 595 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 23, 1887, WAS ESTABLISHED AS A 45 FOOT WIDE ROAD FOR THE EAST MILE AND THE WEST 1/2 MILE WAS REJECTED, AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS ON JULY 8, 1887, AND RECORDED ON SEPTEMBER 19, 1887 BY ROLAND LAKIN, COUNTY

CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 33-15-12 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING:

- 1) THE ROAD AS SURVEYED EXTENDS EAST ON THE SECTION LINES FOR 1-1/2 MILES "AS PER GOVERNMENT SURVEY" TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 34-15-12 TO END THE ROAD AS SURVEYED
- 2) THE PETITION FROM THE NORTHWEST CORNER OF SECTION 33-15-12 EAST FOR 1/2 MILE TO THE NORTH 1/4 CORNER OF SECTION 33-15-12 WAS **REJECTED**

- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 168 ORDERED BY J. E. LEEPER TO LOCATE THE NORTHWEST CORNER AND THE LINES AND CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 DATED MAY 5-7, 1887, SAID THAT **HE SET A 9" X 16" X 20" LIMESTONE** FOR THE PERMANENT NORTHWEST CORNER OF SECTION 33-15-12 ON THIS **PERMANENT SURVEY**. HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-15-12 SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL, AND FROM THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12 AND THE NORTH 1/4 CORNER OF SECTION 32-15-12 EAST THROUGH THE STONES HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-15-12 AND THE NORTHEAST CORNER OF SECTION 33-15-12.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,310-1/2' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTIONS 28-15-12-15-12
- 2) 1,327.6' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 33-15-12
- 3) 2,655.2' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 33-15-12
- 4) 5,310.5' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL
- 5) 2,666' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-15-12
- 6) 5,342' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-15-12

- 9) ROAD NUMBER 353: RECORDED IN ROAD RECORD BOOK "C" ON PAGES 362 TO 363 [PACKET 596 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE:

ON JULY 11, 1887 A PETITION BY J. E. LEEPER AND 12 OTHERS PRESENTED A PETITION FOR THE LOCATION OF A ROAD WITH OUT VIEW AND SURVEY COMMENCING AT THE NORTHWEST CORNER OF SECTION THIRTY-TWO (32), TOWNSHIP 15 OF RANGE 12, THENCE EAST ON THE SECTION LINE FOR 1 MILE TO THE NORTHEAST CORNER OF SECTION 32-15-12. THE LAND OWNERS ON WHICH THE ROAD IS TO BE LOCATED WAIVE ALL RIGHT TO DAMAGES AS THE ROAD IS FENCED OUT AND THE PUBLIC TRAVEL OVER IT AT THE PRESENT TIME.

WHEREAS, NO LEGAL OBJECTIONS HAVE BEEN MADE TO THE PETITION FOR A ROAD ON THE SECTION LINE, WITHOUT VIEW AND SURVEY, AND WHEREAS THE LAND OWNERS ADJOINING SAID PROPOSED ROAD HAVE RELEASED ALL CLAIMS FOR DAMAGES, AND WHEREAS WE ARE SATISFIED THE ROAD DESCRIBED IN SAID PETITION WILL BE A PUBLIC UTILITY: IT IS HEREBY ORDERED THAT THE WITHIN PETITION BE GRANTED WITHOUT VIEW AND SURVEY, AND SAID ROAD DECLARED LEGALLY ESTABLISHED FORTY FEET IN WIDTH. WITNESS THE BOARD OF COUNTY COMMISSIONERS OF SAID COUNTY AT EMPORIA THIS 11TH DAY OF JULY, 1887 BY T. E. McMILLAN, CHAIRMAN. THIS STATEMENT WAS ATTESTED BY

ROLAND LAKIN, COUNTY CLERK. IT WAS NOTED THAT THE TRUSTEE WAS NOTIFIED ON SEPTEMBER 7, 1887.

- 10) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 196 DATED NOVEMBER 20, 1900 ORDERED BY MIKE ROBERTS TO PERMANENTLY ESTABLISH THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 33-15-12 ON THIS **PERMANENT SURVEY**. HE SAID THAT HE WAS TO CHECK ON THE CORRECTNESS OF THIS CORNER AS THE LANDOWNERS BELIEVED IT WAS TOO FAR EAST.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 39.90 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-12
 - 2) 80.10 CHAINS WEST TO THE CENTER OF THE ROAD AT THE NORTHWEST CORNER OF SECTION 32-15-12 – **NO STONE FOUND**
 - 3) 20.13 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 33-15-12
 - 4) 40.27 CHAINS SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 33-15-12
 - 5) 80.52 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL
 - 6) 40.44-1/2 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-15-12
- 11) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 154, TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 75 DATED FEBRUARY 25-27, 1909 TO SUBDIVIDE SECTION 32-15-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,635' WEST TO THE STONE HE FOUND, AND HE DETERMINED THAT THIS STONE WAS **NOT** THE 1/4 CORNER
 - 2) 2,645' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 32-15-12
 - 3) 5,290' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12
 - 4) 1,327.5' SOUTH TO THE STONE HE FOUND AT THE EAST 1/8TH CORNER OF THE NE1/4 OF SECTION 32-15-12
 - 5) 2,655' SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 32-15-12
- 12) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY FOR ROAD NUMBER 642 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 437 THROUGH 443 PETITIONED BY MIKE ROBERTS AND OTHERS FOR A CHANGE IN A ROAD IN TOWNSHIP 15-12 [PACKET 894 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 10, 1908, WAS VIEWED ON NOVEMBER 10, 1908 BY THE BOARD OF COUNTY COMMISSIONERS, AND WAS ALLOWED ON DECEMBER 11, 1908 AS NOTED BY J. A. CLEMMER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 33-15-12 ON THIS ROAD SURVEY. HE BEGAN THIS ROAD SURVEY AT A POINT 1/4 MILE SOUTH OF THIS CORNER.

CONTINUED ON PAGE 5

- 13) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR COUNTY ROAD NUMBER 642 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 44 AT THE REQUEST OF MIKE ROBERTS, PRINCIPAL PETITIONER, FOR A ROAD IN TOWNSHIP 15-13, SAID THAT **HE FOUND THE STONE** MARKING THE NORTHWEST CORNER OF SECTION 33-15-12 TO BEGIN THIS ROAD SURVEY. THIS ROAD WAS SURVEYED ON DECEMBER 28, 1908 AND RECORDED ON DECEMBER 9, 1909. A NOTE IN THE UPPER RIGHT CORNER NOTES THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "D" ON PAGE 437.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327.5' SOUTH TO THE STONE HE FOUND AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 33-15-12
- 2) 2,655' SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 33-15-12 TO END THIS ROAD SURVEY

- 14) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGES 87 & 88 AT THE REQUEST OF W. D. BUCHANAN TO PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 28-15-12, SAID THAT **HE FOUND A QUESTIONABLE STONE** AT THE SOUTHWEST CORNER OF SECTION 28-15-12. HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 TO THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 21-15-12, AND CHAINING EAST FOR 132 FEET, WHICH POINT FELL ON THE WEST EDGE OF ELM TREES, WHICH MEASUREMENTS COINCIDED WITH THE GOVERNMENT FIELD NOTES. HE SAID THAT TAKING THE LINES AND MEASUREMENTS INTO CONSIDERATION, AND THE FACT THAT THE STONE WAS FIRMLY PLANTED IN THE GROUND, AND THAT TO THE BEST OF KNOWLEDGE OF PARTIES LIVING IN THE NEIGHBORHOOD THE STONE HAD NEVER BEEN MOVED, AND HAD BEEN KNOWN FOR A GREAT NUMBER OF YEARS TO HAVE BEEN IN ITS PRESENT SIGHT, AND NO ONE THERE PRESENT BEING ABLE TO SWEAR TO HAVING EVER SEEN SAID STONE IN ANY OTHER PLACE, HE DEEMED THAT SAID STONE TO BE IN ITS ORIGINAL POSITION AND TO MARK THE **TRUE SOUTHWEST CORNER OF SECTION 28-15-12** ON THIS **PERMANENT SURVEY**. HE NOTED THAT A STRAIGHT LINE FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 TO THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 28-15-12 FELL 11 INCHES EAST OF THIS STONE AT THE SOUTHWEST CORNER OF SECTION 28-15-12. THE FIELD SURVEY WAS ON SEPTEMBER 12-15, 1911 AND ENTERED ON JANUARY 2, 1912. SEE ALSO PACKET "M 168" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,326'-4-1/2" NORTH TO THE 28" X 14" X 3-1/2" LIMESTONE MARKED "1/8" ON THE SOUTH SIDE HE PLANTED FOR THE PERMANENT SOUTHWEST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 28-15-12. HE SET THIS STONE AT TWO FEET BELOW THE GROUND IN THE EAST SIDE OF A DITCH AT 6 FEET NORTH OF AN ELM TREE 3" IN DIAMETER
- 2) 2,652'-9" NORTH TO THE 19" X 11" X 6" LIMESTONE MARKED "1/4" ON THE WEST SIDE HE PLANTED FOR THE PERMANENT WEST 1/4 CORNER OF SEC. 28-15-12
- 3) 5,305'-6" NORTH TO THE 17" X 10" X 6" LIMESTONE MARKED WITH 4 NOTCHES ON THE WEST SIDE AND 2 NOTCHES ON THE NORTH SIDE HE PLANTED FOR THE PERMANENT NORTHWEST CORNER OF SECTION 28-15-12
- 4) 6,632'-9" NORTH TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 21-15-12

HIS INFORMATION IS CONTINUED ON PAGE 6

- 5) 7.960' NORTH TO THE STONE HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 21-15-12
 - 6) 2.666' EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/4 CORNER OF SECTION 28-15-12
 - 7) 5.332' EAST TO THE 18" X 10" X 6-1/2" LIMESTONE MARKED WITH 3 NOTCHES ON THE WEST SIDE AND ONE NOTCH ON THE NORTH SIDE HE PLANTED FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 28-15-12
- 15) REA BOOK 30 ON PAGE 23.5 SAYS THAT **THEY SET AN IRON PIN** FOR THE NORTHWEST CORNER OF SECTION 33-15-12 IN THE CENTER OF THE ROAD AND 5,310 FEET NORTH OF THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL, THAT THEY ALSO SET. THEY NOTED THAT AT 5,280 FEET NORTH OF THE SOUTHWEST CORNER OF SECTION 33-15-12 WAS THE FENCE FOR THE ROAD AND ALSO A LINE OF TIMBER AT THE EDGE OF A PLOWED FIELD ACROSS THE CREEK.
- 1) 68.33' SW TO A SQUARE WOODEN POST
 - 2) 38' NW TO A WITNESS PIN BY THE SOUTH SIDE OF A CONCRETE R/W MARKER
- 16) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-12 SHOWS A **REA PIN** AT THE "SW CORNER SECTION 28-15-12".
- 1) 68.33' SW TO A SQUARE WOODEN POST [REA]
 - 2) 38' NW TO A WITNESS PIN [REA] BY THE SOUTH SIDE OF A CONCRETE R/W MARKER
- 17) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 60 TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE SOUTHEAST 1/4 AND THE NORTHEAST 1/4 OF SECTION 29-15-12 PETITIONED BY KEITH ROWLAND, OWNER OF THE NORTHEAST 1/4 AND AGENTS FOR THE NORTHWEST CORNER OF SECTION 29, AND BY HAROLD AND RUSSELL YEAGER, AGENTS FOR THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 29 THAT BEGAN DECEMBER 9, 1982 AND CONTINUED UNTIL COMPLETION OF DECEMBER 15, 1982, SAID THAT THE SOUTHEAST CORNER OF SECTION 29-15-12 FALLS IN 10 FEET OR MORE OF FILL FOR THE CONSTRUCTION OF K-99 HIGHWAY AND IT WAS **NOT** DUG FOR. **HE RESET** THIS CORNER AT THE 1911 LEGAL SURVEY DISTANCE [5,305.5 FEET] SOUTH OF THE RESET NORTHEAST CORNER OF SECTION 29-15-12 AND AT THE SAME DISTANCE EAST OF THE SOUTH 1/4 CORNER STONE OF SECTION 29-15-12, I.E., 2,645.15 FEET. **HE SET A #5 REBAR WITH A LYON COUNTY CAP IN THE ASPHALT SURFACE OF K-99 HIGHWAY** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 29-15-12 ON THIS **PERMANENT SURVEY**.
- 1) 3.5' WEST TO THE TRAVELED WAY OF HIGHWAY K-99
 - 2) 77.0' SW TO THE NORTHEAST CORNER OF AN OLD FILLING STATION
 - 3) 90.5' NW TO THE SOUTHEAST CORNER OF AN ENCLOSED PORCH
 - 4) 3.0' NORTH TO THE TRAVELED WAY OF THE ROAD TO THE WEST
 - 5) 2,645.15' WEST TO A BAR SET FOR THE NORTH 1/4 CORNER OF SECTION 32
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,645.15' WEST TO THE 4" X 16" X 18" LIMESTONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 29-15-12 THAT WAS SET BY YINGLING IN SURVEY BOOK "D" ON PAGE 75 IN 1909. HE DROVE #5 REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE
 - 2) 5,290.30' WEST TO THE 6" X 7" NOTCHED IRREGULAR LIMESTONE HE FOUND AT THE **TRUE** SOUTHWEST CORNER OF SECTION 29-15-12 WITH A MARKED 2" X 12" X 12" LIMESTONE ROAD STONE FROM 1891 HE FOUND ON THE WEST SIDE OF THE IRREGULAR NOTCHED LIMESTONE. HE DROVE A #5 REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE OF BOTH STONES

HIS INFORMATION IS CONTINUED ON PAGE 7

- 3) 2,657.75' NORTH TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 29-15-12
 - 4) 5,315.20' NORTH TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 29-15-12
 - 5) 2,653.75' EAST TO THE BROKEN REMAINS OF THE GLO STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 28-15-12. HE DROVE A #5 REBAR WITH A LYON COUNTY CAP IN THE CENTER OF THE MASS OF STONE, PLACING PIECES OF THE BROKEN GLO STONE AROUND THE REBAR
 - 6) 5,320.65' EAST TO THE 6-1/2" X 10" X 18" NOTCHED LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-15-12 THAT WAS SET BY YINGLING IN PERMANENT SURVEY BOOK 1 ON PAGE 87 IN 1911
- 18) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56K-7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT **HE FOUND THE 5/8" CAPPED REBAR AT 0.4 FEET DEEP** AT THE NORTHEAST CORNER OF SECTION 32 FROM RECORDED TIES BY STEVEN S. BROSEMER, L.S. 752, DATED DECEMBER 1982 IN PERMANENT SURVEY BOOK 2 ON PAGE 60. **NOTE:** THIS MONUMENT IS 0.8 FEET NORTH AND 4.7 FEET EAST OF THE STONE CORNER MONUMENT MENTIONED ON THE 1928 COUNTY ROAD PLANS AND 1931 HIGHWAY PLANS AND DEEDS. **THE MONUMENT FOUND WAS ESTABLISHED ON A PERMANENT SURVEY, PER LYON COUNTY COUNSELOR OPINION IN CORRESPONDENCE DATED MAY 20, 2004, FROM THE LYON COUNTY ENGINEER.** KDOT CORNER NUMBER 32505
- 1) 3.5' WEST TO TRAVEL WAY OF K-99 HIGHWAY
 - 2) 77.0' SW TO NORTHEAST CORNER OF OLD FILLING STATION
 - 3) 90.5' NW TO SOUTHEAST CORNER OF ENCLOSED PORCH
 - 4) 3.0' NORTH TO TRAVEL WAY OF ROAD TO WEST
 - 5) **4.93' WNW TO 1/2" IRON BAR OF UNKNOWN ORIGIN**
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,646.02' WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-12
 - 2) 5,289.99' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-12
 - 3) 2,652.42' NORTH TO THE 5/8" REBAR HE FOUND AT THE WEST 1/4 CORNER OF SECTION 28-15-12
 - 4) 5,305.31' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-15-12
 - 5) 2,653.77' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-15-12
 - 6) 5,320.70' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-15-12
 - 7) 2,657.83' SOUTH TO THE 1/2" REBAR WITH KDOT ALUMINUM CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-15-12
 - 8) 5,315.66' SOUTH TO THE 1/2" REBAR WITH KDOT ALUMINUM CAP HE SET FOR THE SOUTHWEST CORNER OF SECTION 33-15-12
- 19) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 15-12 FOR PROJECT NUMBER 08089-02 DATED APRIL 01, 2008, A SURVEY FOR GLEN O. COATS TO ESTABLISH THE NORTH LINE OF THE EAST 1/2 OF THE NORTHWEST 1/4, AND THE NORTH LINE OF THE WEST 1/2 OF THE NORTHEAST 1/4, ALL IN SECTION 33-15-12, SHOWS THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTHWEST CORNER OF SECTION 33-15-12 AS THE LOCATION WAS UNDER CONSTRUCTION FOR KDOT BRIDGE REPLACEMENT PROJECT 99-56K-7443-01.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,326.89' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 33-15-12
 - 2) 2,653.78' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 33-15-12
 - 3) 3,987.24' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/4 OF THE NE1/4 OF SECTION 33-15-12
 - 4) 5,320.70' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 33-15-12
- 20) STEVEN L. WILLETT, L.S. 955, KDOT DISTRICT ONE SURVEYOR, E-MAILED ME A *NOTICE OF COMPLETION OF ENDANGERMENT ACTIVITY AND REPORT OF RESTORATION* BY TIM SLOAN, L.S. 783 OF SLOAN MEIER HANDCOCK-ENGINEERS SURVEYORS, P.A. DATED DECEMBER 18, 2007 THAT INDICATED THAT "**SLOAN SET A 1/2" X 24" REBAR WITH AN ALUMINUM CAP**" AT THE NORTHEAST CORNER OF SECTION 32-15-12 FROM KDOT PROJECT 99-56K-7443-01. HE SENT THE FOLLOWING **HORIZONTAL TIES:**
- 1) 46.4' NE TO THE CENTER OF THE TOP OF A TELEPHONE PEDESTAL
 - 2) 49.54' EAST TO A SURVEY RIGHT-OF-WAY MONUMENT
 - 3) 110.8' NE TO A SURVEY RIGHT-OF-WAY MONUMENT
 - 4) 51.40' SE TO A SPIKE & WASHER IN A 60" OAK TREE
 - 5) 118.4' NW TO A 1/2" X 24" REBAR AT STATION 270+02.36
 - 6) 209.9' WSW TO A SURVEY RIGHT-OF-WAY MONUMENT

NORTHWEST CORNER 33-15-12