

SOUTH 1/4 CORNER SECTION 33, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 7 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 4"** ON A NORTHEAST SLOPE FOR THE SOUTH 1/4 CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON OCTOBER 2, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE 28" X 10" X 2" LIMESTONE THEY SET ON A NORTHWEST SLOPE FOR THE CORNER TO SECTIONS 32 & 33-15-12
 - 2) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 26" X 9" X 3" LIMESTONE THEY SET IN A CREEK BOTTOM FOR THE CORNER TO SECTIONS 33 & 34-15-12
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 13 RECORDED IN SURVEY BOOK "A" ON PAGE 109 DATED FEBRUARY 12, 1868 FOR A SURVEY OF MARION WEAVER'S LAND, BEING THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 33-15-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 20.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE POST HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 33-15-12
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 168 ORDERED BY J. E. LEEPER TO LOCATE THE NORTHWEST CORNER AND THE LINES AND CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 DATED MAY 5-7, 1887, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 214 AND DATED JULY 1901, APPARENTLY DID **NOT** FIND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL AS HE DID NOT MENTION THIS CORNER ON THIS ROAD SURVEY.

- 5) REA BOOK 30 ON PAGE 24 SAYS THAT **THEY SET AN IRON PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING IT; THIS CORNER WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

- 1) 27' SOUTH TO A WITNESS PIN UNDER A FENCE AND 6" EAST OF A POST

- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-12 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 33-15-12" ON THE 3RD STANDARD PARALLEL. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING IT; THIS CORNER WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

- 1) 27' SOUTH TO A WITNESS [REA]

- 7) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SAID THAT HE DUG FOR THE CORNERSTONE AT THE SOUTH 1/4 CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL WITH A LYON COUNTY ROAD GRADER, BUT HE DID **NOT** FIND THE STONE. HE DETERMINED THAT THE CORNERSTONE WAS **DESTROYED**

BY ROAD CONSTRUCTION. HE DID **NOT** RESET THE SOUTH 1/4 CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS SURVEY.

SOUTH QUARTER CORNER 33-15-12