

SOUTHWEST CORNER SECTION 33, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 7 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 28" X 10" X 2"** ON A NORTHWEST SLOPE FOR THE CORNER TO SECTIONS 32 & 33-15-12 ON THE 3RD STANDARD PARALLEL ON OCTOBER 2, 1855. THEY COMMENTED THAT THE LIMESTONE ROCK IS ON THE BANK OF THE RAVINE. SANDSTONE FOUND ON THE LAST CROPPING OF THE RAVINE FOR THE FIRST TIME ON THIS LINE.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 18" X 14" X 4" LIMESTONE THEY SET ON A NORTHEAST SLOPE FOR THE SOUTH 1/4 CORNER OF SECTION 33-15-12
 - 2) 80.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 26" X 9" X 3" LIMESTONE THEY SET IN A CREEK BOTTOM FOR THE CORNER TO SECTIONS 33 & 34-15-12

- 2) IN NOTES FOR THE STATE ROAD FROM DRAGON CREEK ON THE WYANDOTTE AND SANTA FE ROAD IN OSAGE COUNTY TO ALLEN IN BRECKENRIDGE COUNTY AS RECORDED IN ROAD RECORD BOOK "A" ON PAGE 36; THEY APPARENTLY **FOUND** THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY. THE ROAD WAS 66 FEET WIDE.
THE SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL WITH A DEVIATION BETWEEN SECTION 36-15-12 AND SECTION 1-16-12 TO THE SOUTHWEST CORNER OF THE TOWNSHIP [SOUTHWEST CORNER SECTION 31-15-11]; THENCE ??
 - 2) THIS ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL TO THE SOUTHEAST CORNER OF SECTION 34-15-13 AT THE CORNER WHERE THE COUNTY LINE BETWEEN BRECKENRIDGE AND OSAGE COUNTIES INTERSECTS THE 3RD STANDARD PARALLEL

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 12 RECORDED IN SURVEY BOOK "A" ON PAGE 109 DATED FEBRUARY 12, 1868 TO SURVEY THE WEST LINE OF SECTION 33-15-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40 CHAINS, 23 LINKS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 33-15-12
 - 2) 80 CHAINS, 46 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 163 DATED MARCH 28, 1879, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL FOR 787 FEET TO THE NORTHEAST CORNER OF SECTION 5-16-12; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 17-16-12 TO THE TERMINUS OF THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 19 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 74 TO 76 FOR A PETITION BY J. E. LEEPER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-12 AND 16-12 [PACKET 8 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 26, 1879, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON APRIL 7, 1879, AND RECORDED ON APRIL 15, 18790 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY. HE NOTED THAT THE HEDGE FENCE ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 33-15-12 WAS TO BE EAST LINE OF THE ROAD.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL FOR 787 FEET TO THE NORTHEAST CORNER OF SECTION 5-16-12; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 17-16-12 TO THE TERMINUS OF THIS ROAD SURVEY
- 6) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 138 DATED DECEMBER 19, 1882 THROUGH JANUARY 3, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 31 & 32 IN TOWNSHIP 15, RANGE 12, SAID THAT **HE SET A STONE** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON LINE WITH THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-12 AND THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER SECTION 32-15-12 AND AT DOUBLE THE DISTANCE BETWEEN THESE TWO STONES ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
- 1) 40.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE 1/4 CORNER OF ON THE SOUTH LINE SECTION 32-15-12
 - 2) 80.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-12
 - 3) 40.18 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 32-15-12
 - 4) 80.36-1/2 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 32-15-12
 - 5) 160.73 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-15-12
- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 16 DATED MARCH 17-18, 1884 ORDERED BY JAMES JONES FOR A SURVEY TO ESTABLISH THE SOUTH 1/4 CORNER AND THE CENTER CORNER SECTION 5-16-12, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-12, RECORDED IN VOLUME 41 ON PAGE 13 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-13 TO SET THE PERMANENT NORTH 1/4 CORNER OF SECTION 5-16-12 AND THE PERMANENT NORTHEAST CORNER OF SECTION 5-16-12.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 11.90 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE 3" X 12" X 18" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 5-16-12
- HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) 40.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12
 - 3) 51.95 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE 3" X 10" X 20" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 5-16-12
 - 4) 80.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-12
- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 168 ORDERED BY J. E. LEEPER TO LOCATE THE NORTHWEST CORNER AND THE LINES AND CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 DATED MAY 5-7, 1887, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,655.3' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 33-15-12
 - 2) 3,982.9' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 33-15-12
 - 3) 5,310-1/2' NORTH TO THE 9" X 16" X 20" LIMESTONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 33-15-12
 - 4) 10,621' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-15-12
- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 196 DATED NOVEMBER 20, 1900 ORDERED BY MIKE ROBERTS TO PERMANENTLY ESTABLISH THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 40.25 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 33-15-12
 - 2) 60.39 CHAINS NORTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 33-15-12
 - 3) 80.52 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12
- 10) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 567 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 133 THROUGH 136 PETITION BY M. H. COATS AND OTHERS FOR A ROAD IN TOWNSHIP 15-12 ON THE 3RD STANDARD PARALLEL [PACKET 711 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON APRIL 23, 1901, WAS ESTABLISHED AND OPENED AS A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE 3RD STANDARD PARALLEL, ON OCTOBER 10, 1901 AS NOTED BY JOHN LANGLEY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON DECEMBER 14, 1901 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL TO END THIS ROAD SURVEY.
HIS NOTES/SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL FOR 5,292 FEET TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-15-12, THEN CONTINUES EAST ON THE 3RD STANDARD PARALLEL FOR 2,644-1/2 FEET

TO THE 6" X 6" X 18" LIMESTONE MARKED "R" ON THE WEST FACE HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 34-15-12 TO BEGIN THIS ROAD SURVEY

- 11) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 33, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 214 DATED JULY 1, 1901 FOR A ROAD ON THE 3RD STANDARD PARALLEL ON THE SOUTH SIDE OF SECTIONS 33 & 34-15-12 FOR M. H. COATS, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL TO END THIS ROAD SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL FOR 5,292 FEET TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-15-12, THEN CONTINUES EAST ON THE 3RD STANDARD PARALLEL FOR 2,644-1/2 FEET TO THE 6" X 6" X 18" LIMESTONE MARKED "R" ON THE WEST FACE HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 34-15-12 TO BEGIN THIS ROAD SURVEY
- 12) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 154, TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 75 DATED FEBRUARY 25-27, 1909 TO SUBDIVIDE SECTION 32-15-12, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
- 13) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR COUNTY ROAD #642 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 44 AT THE REQUEST OF MIKE ROBERTS, PRINCIPAL PETITIONER, FOR A ROAD IN TOWNSHIP 15-13, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE ORIGINAL GOVERNMENT STONE** AT THE SOUTHWEST CORNER OF 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT ROAD SURVEY**. THIS ROAD WAS SURVEYED ON DECEMBER 28, 2908 AND ENTERED ON DECEMBER 9, 1909. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "D" ON PAGE 437.
- 14) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S. 6-3, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 23.5 SAID THAT **THEY SET AN IRON PIN** FOR THE SOUTHWEST CORNER OF SECTION 33-15-12 AFTER PRODUCING THE SECTION LINE BETWEEN SECTIONS 32 & 33-15-12 ON THE 3RD STANDARD PARALLEL AND 755 FEET EAST OF THE NORTH END OF THE LINE BETWEEN SECTIONS 4 & 5-16-12.
 - 1) 34' SW TO A WITNESS PIN 1' NE OF A FENCE POST
 - 2) 39.5' SE TO A WITNESS PIN 6" EAST OF A FENCE POST
- 15) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-12 SHOWS A **REA PIN** AT THE "SW CORNER SECTION 33-15-12" ON THE 3RD STANDARD PARALLEL. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S. 6-3, COUNTY SURVEYOR**
 - 1) 39' SE TO A WITNESS [REA]
 - 2) 34' SW TO A WITNESS [REA]

CONTINUED ON PAGE 5

- 16) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT HE DUG FOR THE CORNERSTONE AT THE SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL WITH A LYON COUNTY ROAD GRADER, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 1/2" REBAR WITH A KDOT ALUMINUM CAP AT 0.5 FEET DEEP** FOR THE SOUTHEAST CORNER OF SECTION 32-15-12 AT THE PROPORTIONATE DISTANCE AND ON THE LATITUDINAL CURVED LINE BETWEEN THE SOUTH 1/4 CORNER OF SECTION 32-15-12 AND THE SOUTH 1/4 CORNER OF SECTION 34-15-12 ON THE 3RD STANDARD PARALLEL. KDOT CORNER NUMBER 32705
- 1) 32.8' SE TO A SET SPIKE & KDOT WASHER IN THE TOP OF A FENCE POST
 - 2) 21.9' SSW TO A SET SPIKE & KDOT WASHER IN THE TOP OF A FENCE POST
 - 3) 47.5' NE TO A SET SPIKE & KDOT WASHER IN THE TOP OF A CORNER FENCE POST
 - 4) 42.0' NNW TO A DEADMAN AT THE GROUND
 - 5) 47.5' WEST TO A LINE OF POWER POLES TO THE NORTH
 - 6) 27.0' EAST TO A LINE OF FENCE TO THE NORTH
 - 7) 9.0' NORTH TO THE TRAVEL WAY OF THE EAST-WEST PUBLIC ROAD
 - 8) 20.8' SOUTH TO AN EAST-WEST FENCE LINE
- NOTE:** A LINE OF FENCE TO THE NORTH IS APPROXIMATELY THE EAST RIGHT-OF-WAY LINE OF K-99 HIGHWAY TO THE NORTH AND EXTENDED SOUTH.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,649.68' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12
 - 2) 2,657.84' NORTH TO THE 1/2" REBAR WITH AN ALUMINUM KDOT CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-15-12
 - 3) 5,315.66' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12
 - 4) 7,949.11' EAST TO THE 1/2" REBAR HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 34-15-12

SOUTHWEST CORNER 33-15-12