

WEST 1/4 CORNER SECTION 33, TOWNSHIP 15 SOUTH, RANGE 12 EAST

1) ON PAGE 441 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 32 & 33-15-12.

2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 12 RECORDED IN SURVEY BOOK "A" ON PAGE 109 DATED FEBRUARY 12, 1868 TO SURVEY THE WEST LINE OF SECTION 33-15-12, SAID THAT HE SET A **TEMPORARY POST** FOR THE WEST 1/4 CORNER OF SECTION 33-15-12 WHEN HE RAN THE SECTION LINES ON THIS SURVEY. HE SAID THAT HE "MOVED THE TEMPORARY POST 23 LINKS NORTH AND 13 LINKS EAST, BEING A POINT 1-1/2 LINKS WEST OF THE 1/4 CORNER".

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40 CHAINS, 23 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12
- 2) 40 CHAINS, 23 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12

3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 13 RECORDED IN SURVEY BOOK "A" ON PAGE 109 DATED FEBRUARY 12, 1868 FOR A SURVEY OF MARION WEAVER'S LAND, BEING THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 33-15-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 33-15-12 ON THIS SURVEY.

4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 138 DATED DECEMBER 19, 1882 THROUGH JANUARY 3, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 31 & 32 IN TOWNSHIP 15, RANGE 12, SAID THAT **HE SET A STONE** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 32-15-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 32-15-12 AND THE STONE THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.18-1/4 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL
- 2) 40.18-1/4 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 32-15-12
- 3) 120.54-3/4 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-15-12
- 4) 80.17 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 32-15-12

5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 168 ORDERED BY J. E. LEEPER TO LOCATE THE NORTHWEST CORNER AND THE LINES AND CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 DATED MAY 5-7, 1887, SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 33-15-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 33-15-12 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,655.3' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL
 - 2) 1,327.6' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 33-15-12
 - 3) 2,655.2' NORTH TO THE 9" X 16" X 20" LIMESTONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 33-15-12
 - 4) 7,965.7' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-15-12
 - 5) 1,330' EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE NW1/4 OF SECTION 33-15-12
 - 6) 2,660' EAST TO THE TEMPORARY STAKE HE SET FOR THE CENTER CORNER OF SECTION 33-15-12
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 196 DATED NOVEMBER 20, 1900 ORDERED BY MIKE ROBERTS TO PERMANENTLY ESTABLISH THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE AT THE WEST 1/4 CORNER OF SECTION 33-15-12, FROM WHICH ANOTHER STONE BEARS N. 45° E. AT 7 FEET, ON THIS PERMANENT SURVEY.**
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 40.25 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL
 - 2) 20.14 CHAINS NORTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 33-15-12
 - 3) 40.27 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12
- 7) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 154, TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 75 DATED FEBRUARY 25-27, 1909 TO SUBDIVIDE SECTION 32-15-12, SAID THAT **HE FOUND THE STONE FIRMLY IN THE GROUND AND APPARENTLY UNDISTURBED** AT THE EAST 1/4 CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY.**
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,327.5' NORTH TO THE STONE HE FOUND AT THE EAST 1/8TH CORNER OF THE NE1/4 OF SECTION 32-15-12
 - 2) 2,655' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-12
 - 3) 1,322.5' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE SW1/4 OF THE NE1/4 OF SECTION 32-15-12
 - 4) 2,645' WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 32-15-12
- 8) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "D" ON PAGES 437 THROUGH 443 FOR ROAD NUMBER 642 ON A PETITION BY MIKE ROBERTS [PACKET 894 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED DECEMBER 1909, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 33-15-12 ON THIS ROAD SURVEY.
- 9) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR COUNTY ROAD #642 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 44 AT THE REQUEST OF MIKE ROBERTS, PRINCIPAL PETITIONER, FOR A ROAD IN TOWNSHIP 15-13, SAID

THAT HE FOUND THE 1/4 SECTION STONE ON THE WEST SIDE OF SECTION 33-15-12 TO END THIS PERMANENT ROAD SURVEY. THIS ROAD WAS SURVEYED DECEMBER 28, 1908 AND ENTERED ON DECEMBER 9, 1909. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "D" ON PAGE 437.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327.5' NORTH TO THE STONE HE FOUND AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 33-15-12
 - 2) 2,655.0' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12 TO BEGIN THIS ROAD SURVEY
- 10) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S. 6-3, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 23.5 SAID THAT **THEY SET A RAILROAD SPIKE** IN THE HARD GRAVEL ROAD FOR THE WEST 1/4 CORNER OF SECTION 33-15-12 AT 2,640 FEET NORTH OF THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3RD STANDARD PARALLEL AND AT 145 FEET NORTH OF A HEDGE, BUT APPARENTLY LINES UP WITH A FENCE IN THE DISTANCE WEST.
- 1) 39' EAST TO A WITNESS PIN
 - 2) 35' SOUTH TO A WITNESS PIN
 - 3) 40.6' SE TO A HEDGE STUMP AT THE CORNER OF AN OLD HEDGE
- 11) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-12 SHOWS A **REA PIN** AT THE "SW CORNER NW 1/4 SECTION 33-15-12". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S. 6-3, COUNTY SURVEYOR**
- 1) 39' EAST TO A WITNESS [REA]
- 12) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT HE DUG FOR THE CORNERSTONE AT THE EAST 1/4 CORNER OF SECTION 32 IN AN AREA 5' X 6' X 3.5' DEEP IN THE ASPHALT ROAD, BUT HE DID NOT FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS LOST. **HE SET A 1/2" X 24" REBAR WITH A KDOT ALUMINUM CAP AT 0.2 FEET DEEP** FOR THE EAST 1/4 CORNER OF SECTION 32-15-12 ON TRUE LINE AND AT HALF-DISTANCE BETWEEN THE NORTHEAST CORNER OF SECTION 32-15-12 AND THE SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL. KDOT CORNER NUMBER 32605
- 1) 46.6' NE TO A SET SPIKE & KDOT WASHER IN THE TOP OF A FENCE POST
 - 2) 30.2' EAST TO A SET SPIKE & KDOT WASHER IN THE TOP OF A GATE POST
 - 3) 42.1' SE TO A SET SPIKE & KDOT WASHER IN THE TOP OF A CORNER FENCE POST
 - 4) 37.0' WEST TO A SET SPIKE & KDOT WASHER IN A POWER POLE
 - 5) 14.5' NORTH TO THE TRAVEL WAY OF A FIELD ENTRANCE
 - 6) 2.0' WEST TO THE TRAVEL WAY OF K-99 HIGHWAY
 - 7) IN LINE WITH A FENCE EXTENDED FROM THE WEST
 - 8) 26.0' SOUTH TO A HEDGE LINE TO THE EAST
 - 9) IN LINE WITH A SECOND HEDGE ROW 1/4 MILE TO THE EAST
- HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:
- 1) 1,313.93' WEST TO THE STONE HE FOUND AT THE SOUTH 1/16TH CORNER OF THE NE1/4 OF SECTION 32-15-12
 - 2) 2,657.83' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-12

HIS INFORMATION IS CONTINUED ON PAGE 4

- 3) 2,657.83' SOUTH TO THE 1/2" REBAR WITH A KDOT ALUMINUM CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3RD STANDARD PARALLEL

WEST QUARTER CORNER 33-15-12