

**WEST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST QUARTER SECTION 33, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 19 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 74 TO 76 FOR A PETITION BY J. E. LEEPER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-12 AND 16-12 [PACKET 8 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 26, 1879, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON APRIL 7, 1879, AND RECORDED ON APRIL 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE SET A ROAD STONE** AT THE NORTHWEST CORNER THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 ON THIS ROAD SURVEY. HE NOTED THAT THE HEDGE FENCE ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 33-15-12 WAS TO BE THE EAST LINE OF THE ROAD.

**HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:**

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINE TO THE SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL; THEN EXTENDS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL FOR 787 FEET TO THE NORTHEAST CORNER OF SECTION 5-16-12; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 17-16-12 TO THE TERMINUS OF THIS ROAD SURVEY
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 168 ORDERED BY J. E. LEEPER TO LOCATE THE NORTHWEST CORNER AND THE LINES AND CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 DATED MAY 5-7, 1887, SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 33-15-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 33-15-12 AND THE STONE THAT HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 33-15-12 ON THIS **PERMANENT SURVEY**.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,327.6' NORTH TO THE 9" X 16" X 20" LIMESTONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 33-15-12
  - 2) 1,327.6' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 33-15-12
  - 3) 3,982.9' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL
  - 4) 1,331.5' EAST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF THE NW1/4 OF SECTION 33-15-12
  - 5) 2,663' EAST TO THE STONE HE FOUND AT THE EAST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 33-15-12
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 196 DATED NOVEMBER 20, 1900 ORDERED BY MIKE ROBERTS TO PERMANENTLY ESTABLISH THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 ON THIS **PERMANENT SURVEY**. HE NOTED THAT THIS CORNER WAS THE CORNER WHICH THIS SURVEY WAS CALLED TO ESTABLISH.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.13 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12
  - 2) 20.14 CHAINS SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 33-15-12
  - 3) 60.39 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL
- 4) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A ROAD SURVEY FOR ROAD NUMBER 642 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 437 THROUGH 443 PETITIONED BY MIKE ROBERTS AND OTHERS FOR A CHANGE IN A ROAD IN TOWNSHIP 15-12 [PACKET 894 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 10, 1908, WAS VIEWED ON NOVEMBER 10, 1908 BY THE BOARD OF COUNTY COMMISSIONERS, AND WAS ALLOWED ON DECEMBER 11, 1908 AS NOTED BY J. A. CLEMMER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE** AT 1/4 OF A MILE SOUTH OF THE NORTHWEST CORNER OF 33-15-12 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) BEGINNING AT A POINT 1/4 MILE SOUTH OF THE NORTHWEST CORNER OF SECTION 33-15-12, I CLEARLY DEFINED THE CENTER LINE OF THE ROAD RUNNING TO THE 1/4 SECTION STONE BY DRIVING STAKES AT FREQUENT INTERVALS
- 5) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 154, TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 75 DATED FEBRUARY 25-27, 1909 TO SUBDIVIDE SECTION 32-15-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/8<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 CORNER OF SECTION 32-15-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327.5' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-12
  - 2) 1,327.5' SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 32-15-12
  - 3) 1,322.5' WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF THE NE1/4 OF SECTION 32-15-12
- 6) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR COUNTY ROAD NUMBER 642 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 44 AT THE REQUEST OF MIKE ROBERTS, PRINCIPAL PETITIONER, FOR A ROAD IN TOWNSHIP 15-13, SAID THAT **HE PASSED OVER THE WEST SIDE OF THE STONE** AT THE WEST 1/8<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 33-15-12 ON THIS **PERMANENT ROAD SURVEY**. THIS ROAD WAS SURVEYED DECEMBER 28, 1908 AND ENTERED ON DECEMBER 9, 1909. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "D" ON PAGE 437.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327.5' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-12 TO BEGIN THIS ROAD SURVEY
  - 2) 1,327.5' SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 33-15-12 TO END THIS ROAD SURVEY
- 7) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGES 87 & 88 AT THE REQUEST OF W. D.

BUCHANAN TO PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 28-15-12, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 ON THIS **PERMANENT SURVEY**. THE FIELD SURVEY WAS ON SEPTEMBER 12 TO 15, 1911 AND ENTERED ON JANUARY 2, 1912. SEE ALSO PACKET "M 168" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

WEST SIXTEENTH CORNER NORTHWEST QUARTER 33-15-12