

**WEST 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST QUARTER SECTION 33, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 19 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 74 TO 76 FOR A PETITION BY J. E. LEEPER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-12 AND 16-12 [PACKET 8 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 26, 1879, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON APRIL 7, 1879, AND RECORDED ON APRIL 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE SET A ROAD STONE** AT THE SOUTHWEST CORNER THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 33-15-12 ON THIS ROAD SURVEY. HE NOTED THAT THE HEDGE FENCE ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 AND THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 33-15-12 WAS TO BE EAST LINE OF THE ROAD.

**HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:**

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 32-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL; THEN EXTENDS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL FOR 787 FEET TO THE NORTHEAST CORNER OF SECTION 5-16-12; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 17-16-12 TO THE TERMINUS OF THIS ROAD SURVEY

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 33-15-12