

**WEST 1/4 CORNER SECTION 34, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 439 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-15-12.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 13 RECORDED IN SURVEY BOOK "A" ON PAGE 109 DATED FEBRUARY 12, 1868 FOR A SURVEY OF MARION WEAVER'S LAND, BEING THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 33-15-12, SAID THAT **HE FOUND THE STONE AT THE EAST 1/4 CORNER OF SECTION 33-15-12 ON THIS SURVEY.**
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 168, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 168 DATED MAY 5-7, 1887 ORDERED BY J. E. LEEPER TO LOCATE THE NORTHWEST CORNER AND THE LINES AND CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12, SAID THAT **HE FOUND THE STONE AT THE WEST 1/4 CORNER OF SECTION 33-15-12 ON THIS PERMANENT SURVEY.**
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 196 DATED NOVEMBER 20, 1900 ORDERED BY MIKE ROBERTS TO PERMANENTLY ESTABLISH THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 33-15-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE NEAR** THE EAST 1/4 CORNER OF SECTION 33-15-12 ON THIS **PERMANENT SURVEY.** HE COMMENTED THAT **THE STONE HAD BEEN WASHED OUT AND RESET "NEAR ITS FORMER POSITION BY ONE OF THE PROPERTY OWNERS WITHOUT A SURVEY".**  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.20 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL
  - 2) 40.35 CHAINS NORTH TO THE CENTER OF THE CROSSROADS AT THE NORTHEAST CORNER OF SECTION 33-15-12 – **NO STONE**
- 5) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 60  
ON MARCH 5, 1950 A PETITION SIGNED BY ALT M. WEAVER AND OTHERS FOR THE LOCATION OF A ROAD IN TOWNSHIP 15-12 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND R. W. BALL, COUNTY ENGINEER, ON MARCH 23, 1950 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON MARCH 28, 1950 OPENED THE FOLLOWING ROAD:
  - 1) BEGINNING AT THE NORTH LINE OF SECTIONS 33 & 34-15-12 AND TERMINATING AT THE WEAVER RESIDENCE OR 1/2 MILE SOUTH OF THE BEGINNING
  - 2) ROAD TO BE 40 FEET WIDE
- 6) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 20, 1985, SURVEY F34001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, FOR A SURVEY OF A 7.0 ACRE TRACT, LOCATED IN THE NORTHWEST 1/4 OF SECTION 34-15-12, SAID THAT **HE FOUND A 4" X 10" X 20" LIMESTONE AT THE WEST 1/4 CORNER OF SECTION 34-15-12. HE SET REBARS ON THE EAST AND WEST SIDES OF THE STONE.** THIS SURVEY WAS RECORDED IN VOLUME 415 ON PAGE 454 IN THE REGISTER OF DEEDS OFFICE ON APRIL 22, 1985.

HIS TIES ARE ON PAGE 2

- 1) 31.5' EAST TO A LINE OF WIRE FENCE TO THE NORTH
- 2) 25.0' WEST TO A LINE OF WIRE FENCE AND HEDGE TO THE NORTH
- 3) IN LINE WITH A HEDGE TO THE EAST
- 4) 8.0' NORTH TO A LINE OF HEDGE TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 460.0' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST TRACT CORNER
- 2) 2,644.4' NORTH TO THE CORNER STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-15-12
- 3) 663.0' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST TRACT CORNER

- 7) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY RECORDED IN VOLUME 433 ON PAGE 807 IN THE REGISTER OF DEEDS OFFICE ON JULY 17, 1987, FOR PROJECT NUMBER 87025 DATED FEBRUARY 10, 1987, A PLAT OF SURVEY FOR A 69.5 ACRE TRACT IN THE WEST 1/2 OF SECTION 34-15-12, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 34-15-12. A COPY OF THE SURVEY WAS FILED IN THE COUNTY ENGINEER'S OFFICE AS SURVEY F34004 IN THE SURVEY FILE FOR TOWNSHIP 15-12. THE TIES HE SUBMITTED HAVE APPARENTLY BEEN REMOVED FROM THE TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 460.0' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND FROM A PREVIOUS SURVEY
- 2) 2,664.4' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-15-12
- 3) 663.0' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND FROM A PREVIOUS SURVEY
- 4) 166.0' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST TRACT CORNER

- 8) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY FILED IN VOLUME 433, PAGE 809 IN THE REGISTER OF DEEDS OFFICE ON JULY 17, 1987, FOR PROJECT NUMBER 87119 DATED JUNE 3, 1987, FOR A SURVEY OF TWO TRACTS OF LAND LYING IN THE NORTHEAST 1/4 OF SECTION 34-15-12, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 34-15-12. A COPY OF THE SURVEY WAS FILED IN THE COUNTY ENGINEER'S OFFICE AS SURVEY F34005 IN THE SURVEY FILE FOR TOWNSHIP 15-12. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.

- 9) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT **HE FOUND THE 4" X 10" X 20" LIMESTONE WITH REBARS ON THE EAST AND WEST SIDES** AT THE EAST 1/4 CORNER OF SECTION 33-15-12 FROM RECORDED TIES BY STEVEN S. BROSEMER, L.S. 752, DATED APRIL 1985. KDOT CORNER NUMBER 33605

- 1) 31.5' EAST TO A LINE OF WIRE FENCE TO THE NORTH
- 2) 25.0' WEST TO A LINE OF WIRE FENCE AND HEDGE TO THE NORTH
- 3) IN LINE WITH A HEDGE TO THE EAST
- 4) 8.0' NORTH TO A LINE OF HEDGE TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,309.31' WEST TO THE 1/2" REBAR WITH AN ALUMINUM KDOT CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-15-12
- 2) 2,664.30' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-15-12

CONTINUED ON PAGE 3

- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 1, 2008 FOR PROJECT NUMBER 08089-02, SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 15-12, SAID THAT **HE FOUND THE 4" X 10" STONE WITH 1/2" REBARS ON THE EAST AND WEST SIDES** AT THE EAST 1/4 CORNER OF SECTION 33-15-12 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 51.8' SE TO THE TOP CENTER OF OSAGE RWD #8 METER
  - 2) 26.4' WSW TO A CONCRETE NAIL & BOTTLE CAP IN A 12" DIAMETER HEDGE TREE
  - 3) 25' WEST TO A HEDGE TO THE SOUTH
  - 4) 8' NORTH TO A HEDGE TO THE WEST
  - 5) 3.8' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "S" NORTH-SOUTH

WEST QUARTER CORNER 34-15-12