

**SOUTH 1/4 CORNER SECTION 35, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 9 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 13" X 4"** ON LEVEL GROUND FOR THE SOUTH 1/4 CORNER OF SECTION 35-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON OCTOBER 2, 1855, FROM WHICH:
  - 1) A WALNUT TREE 22" IN DIAMETER BEARS N. 34-1/2° W. AT 47 LINKS DISTANCE
  - 2) A BURR OAK TREE 24" IN DIAMETER BEARS S. 46-1/2° E. AT 56 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

  - 1) 40.00 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 24" X 9" X 4" LIMESTONE THEY SET ON A GENTLE SLOPE TO THE SOUTHEAST FOR THE CORNER TO SECTIONS 34 & 35-15-12
  - 2) 40.00 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 31" X 7" X 5" LIMESTONE THEY SET ON AN EAST SLOPE NEAR TIMBER FOR THE CORNER TO SECTIONS 35 & 36-15-12
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 10 RECORDED IN SURVEY BOOK "A" ON PAGE 108 DATED JANUARY 24, 1868 TO SURVEY W. L. ALLEN'S LAND, BEING THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 34-15-12. SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 35-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 80 CHAINS, 18 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35-15-12
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 11 RECORDED IN SURVEY BOOK "A" ON PAGE 108 AND DATED JANUARY 1868, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 35-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS SURVEY.
- 4) REA BOOK 30 ON PAGE 24 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 35-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL AT 2.649 FEET EAST OF THE SOUTHWEST CORNER OF SECTION 35-15-12 AND IN LINE WITH A HEDGE TO THE NORTH. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING THIS IRON PIN AS IT WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 28' SOUTH TO A WITNESS PIN 6" WEST OF A SMALL POST
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-12 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 35-15-2" ON THE 3<sup>RD</sup> STANDARD PARALLEL. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING THIS IRON PIN AS IT WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 28' SOUTH TO A WITNESS [REA]
- 6) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER/COUNTY SURVEYOR FROM 1952 TO 1981, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 15 AND DATED MARCH 26, 1956 SAID THAT HE DID **NOT** FIND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 35-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. HE DID **NOT** RESET THE SOUTH 1/4 CORNER OF SECTION 35-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS PERMANENT SURVEY.

SOUTH QUARTER CORNER 35-15-12