

**WEST 1/4 CORNER SECTION 35, TOWNSHIP 15 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 437 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 34 & 35-15-12.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 10 RECORDED IN SURVEY BOOK "A" ON PAGE 108 DATED JANUARY 24, 1868 TO SURVEY W. L. ALLEN'S LAND, BEING THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 34-15-12. SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 35-15-12 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 79 CHAINS, 89 LINKS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 35-15-12
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 11 RECORDED IN SURVEY BOOK "A" ON PAGE 108 DATED JANUARY 24, 1868 FOR A SURVEY OF JAMES McCOY'S LAND, BEING THE SURVEY OF A LINE BETWEEN THE SOUTHEAST 1/4 AND THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 35-15-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 35-15-12 ON THIS SURVEY.
- 4) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 15 AT THE REQUEST OF FRED BOLINE TO LOCATE AND PERMANENTLY ESTABLISH THE SOUTH LINE OF THE NORTHWEST 1/4 OF SECTION 35-15-12 THAT WAS BEGAN ON MARCH 22, 1956 AND CONTINUED UNTIL THE SURVEY WAS COMPLETED ON MARCH 29, 1956, WITH THE EXCEPTION OF ONE DAY, NAMELY MARCH 27, SAID THAT HE DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 35-15-12. **HE SET AN IRON PIN** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 35-15-12 ON LINE AND HALFWAY BETWEEN THE IRON PIN THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 35-15-12 AND THE IRON PIN THAT HE SET FOR THE PERMANENT SOUTHWEST CORNERS OF SECTION 35-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,644.85' NORTH TO THE IRON PIN HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 35-15-12
  - 2) 2,644.85' SOUTH TO THE IRON PIN SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 35-15-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL
- 5) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT WITH NO DATE, SAID THAT **HE FOUND A 1/2" REBAR** AT THE EAST 1/4 CORNER OF SECTION 35-15-12 THAT WAS SET BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A 1956 PERMANENT SURVEY.
  - 1) 25.3' NE TO A PK NAIL IN A GATE POST
  - 2) 31.7' SW TO THE NEAR FACE OF THE NORTH BRACE POST
  - 3) 20.5' EAST TO A LINE OF FENCE TO THE NORTH
  - 4) IN LINE WITH A FENCE TO THE WEST
  - 5) 1.5' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
- 6) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY FILED IN VOLUME 433, PAGE 809 IN THE REGISTER OF DEEDS OFFICE ON JULY 17, 1987, FOR PROJECT NUMBER 87119 DATED JUNE 3, 1987, FOR A SURVEY OF TWO TRACTS OF LAND LYING IN THE NORTHEAST 1/4 OF SECTION 34-15-12, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 1/2" REBAR** ATTRIBUTABLE TO L. M. GOULD IN A 1956 PERMANENT

**SURVEY** AT THE EAST 1/4 CORNER OF SECTION 34-15-12. A COPY OF THE SURVEY WAS FILED IN THE COUNTY ENGINEER'S OFFICE AS SURVEY F34005 IN THE SURVEY FILE FOR TOWNSHIP 15-12. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,319.65' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF A 79.84 ACRE TRACT IN THE NE1/4 OF SEC. 34-15-12
- 2) 2,640.60' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER CORNER OF SECTION 34-15-12
- 3) 2,644.49' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-15-12 ATTRIBUTABLE TO L. M. GOULD

WEST QUARTER CORNER 35-15-12