

WEST 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 20, TOWNSHIP 15 SOUTH, RANGE 13 EAST

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 26, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 26 DATED APRIL 21-23, 1884 TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 19-15-13 FOR CHARLES CHRIST TO SURVEY THE NORTHEAST 1/4 OF SECTION 19-15-13, SAID THAT **HE SET A STONE** FOR THE PERMANENT EAST 1/8TH CORNER OF THE NORTHEAST 1/4 OF SECTION 19-15-13 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-15-13 ON THE LYON AND WABAUNSEE COUNTY LINE AND THE STONE THAT HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 19-15-13 ON THIS **PERMANENT SURVEY**. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 15 ON JANUARY 27, 1889 AT THE REGISTER OF DEEDS OFFICE AND AS SURVEY F19001 IN THE SURVEY FILE FOR TOWNSHIP 19, RANGE 13.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,324.0' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-15-13 ON THE LYON AND WABAUNSEE COUNTY LINE
 - 2) 1,324.0' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 19-15-13
 - 3) 3,972.0' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-15-13

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 4, 1998, FOR PROJECT 97309-02, SURVEY F20001 IN THE SURVEY FILE FOR TOWNSHIP 15-13 FOR A SUBDIVISION OF THE NORTH 1/2 OF THE NORTHWEST 1/4 OF SECTION 20-15-13, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP AS A WITNESS** FOR THE WEST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 20-15-13 ON THE RIGHT-OF-WAY LINE **AT 25.0' EAST OF THE TRUE POSITION.**
HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION FROM THE TRUE POSITION OF THE 1/16TH CORNER:
 - 1) 660.00' NORTH TO THE NORTHEAST CORNER OF THE ADDITIONAL 15 ACRE TRACT AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25' EAST OF THE TRUE CORNER
 - 2) 1,325.5' NORTH TO THE RAILROAD SPIKE HE SET FOR THE NORTHWEST CORNER OF SECTION 20-15-13 ON THE LYN AND WABAUNSEE COUNTY LINE
 - 3) 1,325.5' SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 20-15-13 THAT WAS SET BY EDMISTON
 - 4) 1,650.00' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH-EAST CORNER OF THE ADDITIONAL 15 ACRE TRACT
 - 5) 2,642.31' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/16TH CORNER OF THE NW1/4 OF SECTION 20-15-13

WEST SIXTEENTH CORNER NORTHWEST QUARTER 20-15-13