

**CENTER CORNER SECTION 30, TOWNSHIP 15 SOUTH, RANGE 13 EAST**

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 34, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 34 DATED JUNE 2 & 3, 1884 TO PERMANENTLY ESTABLISH THE CENTER CORNER AND THE EAST 1/4 CORNER OF SECTION 30-15-13 AT THE REQUEST OF B. SANFORD, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 30-15-13 AT THE INTERSECTION OF TWO RIGHT LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS **PERMANENT SURVEY**. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 21 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND IS SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 15, RANGE 13.
  
- 2) DENNIS L. HANDKE, L.S. 786 OF ILC OF TOPEKA AND LAWRENCE, LLC, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 20, 2003 BUT NOT RECEIVED UNTIL APRIL 18, 2011 FOR PROJECT NUMBER 02-257, SAID THAT HE CONSIDERED THAT THE CENTER CORNER OF SECTION 30-15-13 WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH "HANDKE 786" CAP** FOR THE CENTER CORNER OF SECTION 30-15-13. THE LAND SURVEY REFERENCE REPORT WAS FILED AT THE KANSAS STATE HISTORICAL SOCIETY ON DECEMBER 29, 2004. **VERIFY AND CHECK FOR THE STONE OF RECORD AS HE DID NOT INDICATE THE METHODOLOGY HE USED TO DETERMINE THE LOCATION FOR THIS CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 1.35' EAST TO A SPIKE IN A CORNER FENCE POST
  - 2) 6.15' SOUTH TO A SPIKE IN THE SIDE OF A BRACE POST
  - 3) 48.25' NNW TO A SPIKE IN A 24" DIAMETER HEDGE
  - 4) ON THE WEST SIDE OF A CORNER FENCE POST

CENTER CORNER 30-15-13