

NORTHWEST CORNER SECTION 30, TOWNSHIP 15 SOUTH, RANGE 13 EAST

- 1) ON PAGE 26 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 13" X 4"** FOR THE CORNER TO SECTIONS 19 & 30-15-13 ON THE WEST TOWNSHIP BOUNDARY.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 38.50 CHAINS EAST TO THE 19" X 17" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-15-13
- 2) 78.50 CHAINS EAST TO THE 18" X 17" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-15-13
- 3) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 10" X 2-1/2" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 19-15-13
- 4) 80.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 17" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE NORTHWEST CORNER OF SECTION 19-15-13 ON THE COUNTY LINE

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 25 RECORDED IN SURVEY BOOK "A" ON PAGE 120 DATED MARCH 6, 1868 FOR A SURVEY OF L. HATHAWAY'S LAND, BEING THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 25-15-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 25-15-12 ON THE RANGE LINE ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS WEST TO THE STONE HE SET FOR THE NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 25-15-12
- 2) 160 RODS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 25-15-12

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 59 RECORDED IN SURVEY BOOK "A" ON PAGE 158 DATED MAY 23, 1868 FOR A SURVEY OF THE LAND OWNED BY JOHNSON, ROSE AND OTHERS, BEING SECTION 19-15-13, TO ESTABLISH THE CENTER CORNER AND DIVIDE THE SOUTHWEST 1/4 INTO TWO EQUAL PARTS BY A LINE RUNNING NORTH AND SOUTH, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 19-15-13 ON THE RANGE LINE ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 321 RODS, 3 LINKS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-15-13 ON THE LYON AND WABAUNSEE COUNTY LINE
- 2) 76 RODS, 7-1/2 LINKS EAST TO THE STONE HE SET FOR THE DIVISIONAL CORNER TO DIVIDE THE SW1/4 INTO TWO EQUAL PARTS
- 3) 152 RODS, 15 INKS EAST TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 19-15-13
- 4) 312 RODS, 15 INKS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-15-13

NORTHWEST CORNER 30-15-13