

SOUTH 1/4 CORNER SECTION 34, TOWNSHIP 15 SOUTH, RANGE 13 EAST

- 1) ON PAGE 10 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 12" X 3"** ON A GENTLE SLOPE FOR THE SOUTH 1/4 CORNER OF SECTION 34-15-13 ON THE 3RD STANDARD PARALLEL ON OCTOBER 3, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING DISTANCES:

- 1) 40.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE 26" X 12" X 3" SANDSTONE THEY SET ON A GENTLE SLOPE TO THE SOUTHWEST FOR THE CORNER TO SECTIONS 33 & 34-15-13
- 2) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 26" X 11" X 2-1/2" LIMESTONE THEY SET ON AN EAST SLOPE FOR THE CORNER TO SECTIONS 34 & 35-15-13 ON THE COUNTY LINE
- 2) RICHARD L. MATTSON, L.S. 1447, OF MIDLAND SURVEYING, INC., IN A REVISED LAND SURVEY REFERENCE REPORT DATED FEBRUARY 3, 2014 FOR PROJECT NUMBER AG-6215-D-13-0019 FOR TWO GRASSLAND EASEMENT SURVEYS FOR THE RUDEEN BROTHERS LAND COMPANY, L.L.C. IN SECTION 34-15-13, SURVEYS SR # 34002 AND SR # 34003 IN THE LARGE SURVEY DRAWER FOR TOWNSHIP 15-13, SAID THAT **HE FOUND AN 8" X 13" X 2" STONE** AT THE SOUTH 1/4 CORNER OF SECTION 34-15-13 ON THE 3RD STANDARD PARALLEL. HE NOTED THAT THE LOCATION AGREES WELL WITH THE MID-POINT ON THE SOUTH LINE OF SECTION 34-15-13 AND THE LINES OF OCCUPATION. **HE SET A 5/8" IRON BAR WITH ALUMINUM CAP STAMPED "CLS 176" BESIDE THE STONE.** HE SENT THE FOLLOWING

HORIZONTAL TIES:

- 1) 29.55' SOUTHWEST TO A SET NAIL AND SHINER IN THE NORTHEAST FACE OF A WOOD BRACE POST WITH FENCE RUNNING EAST AND WEST
- 2) 25.45' SOUTH/SOUTHWEST TO A SET NAIL AND SHINER IN THE NORTH FACE OF A WOOD GATE POST WITH FENCE RUNNING WEST AND A GATE TO THE EAST
- 3) 25.85' SE TO A SET NAIL AND SHINER IN THE NORTH FACE OF A WOOD GATE POST WITH FENCE RUNNING EAST AND A GATE TO THE WEST
- 4) 24.60' NORTH/NORTHWEST TO A SET NAIL AND SHINER IN THE SOUTH FACE OF A 24" TREE
- 5) **NOTE:** POINT FALLS APPROXIMATELY 1' NORTH OF THE CENTERLINE OF THE GRAVEL ROAD EAST AND WEST, AND 3' EAST OF A FENCE RUNNING NORTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,647.22' WEST ON THE 3RD STANDARD PARALLEL TO THE 1/2" BAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-15-13 AS NOTED BY STEVEN S. BROSEMER, L.S 752, IN MAY 2000
- 2) 2,648.39' EAST ON THE 3RD STANDARD PARALLEL TO THE 1/2" BAR OF **UNKNOWN ORIGIN** HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-15-13 ON THE LYON AND OSAGE COUNTY LINE
- 3) 2,393.08' NORTH TO THE 5/8" IRON BAR AND ALUMINUM CAP STAMPED "CLS 176" HE SET ON THE NORTH BOUNDARY OF THE SAC & FOX RESERVE
- 4) 2,653.11' NORTH TO THE 5/8" IRON BAR AND ALUMINUM CAP STAMPED "CLS 176" HE SET FOR THE CENTER CORNER OF SECTION 34-15-13
- 5) 5,323.35' NORTH TO THE STONE HE FOUND IN PIECES AT THE NORTH 1/4 CORNER OF SECTION 34-15-13
- 6) 10,639.99' NORTH TO THE 5/8" BAR WITH YELLOW ILLEGIBLE CAP HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 27-15-13

SOUTH QUARTER CORNER 34-15-13