

NORTHWEST CORNER SECTION 07, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) ON PAGE 38 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 4"** FOR THE CORNER TO SECTIONS 6 & 7-16-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE ON DECEMBER 30, 1860.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 37.50 CHAINS EAST TO THE 15" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-16-10
 - 2) 77.50 CHAINS EAST TO THE 18" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTION S5, 6, 7 & 8-16-10
 - 3) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-16-10
 - 4) 78.23 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 18" X 12" X 6" LIMESTONE THEY SET FOR THE CLOSING CORNER AT THE NORTHWEST CORNER OF SECTION 6-16-10 ON THE 3RD STANDARD PARALLEL
 - 5) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 16" X 4" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 7-16-10
 - 6) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 20" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-16-10
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 5, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 185 DATED APRIL 2-4 AND MAY 8-9, 1900 AT THE ORDER OF THE RICHARDS BROTHERS FOR A SURVEY OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 6-16-10, SAID THAT **HE FOUND THE STONE MIDWAY BETWEEN TWO STONE POSTS** AT THE SOUTHWEST CORNER OF SECTION 6-16-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 50" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 19.94 CHAINS NORTH ON THE RANGE LINE AND COUNTY LINE TO THE 16" X 8" X 3" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 6-16-10
 - 2) 39.89 CHAINS NORTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-16-10
 - 3) 78.10 CHAINS NORTH ON THE RANGE LINE AND COUNTY LINE TO THE STANDARD CORNER STONE HE FOUND AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-16-10 ON THE 3RD STANDARD PARALLEL
 - 4) 17.25 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 6-16-10
 - 5) 38.63 CHAINS EAST TO THE CALCULATED POSITION FOR THE SOUTH 1/4 CORNER OF SECTION 6 – **NO STONE**
 - 6) 76.20 CHAINS EAST TO THE 14" X 8" X 3" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 6-16-10
 - 7) 115.98 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-16-10 ON LINE BETWEEN FENCES
 - 8) 155.79 CHAINS EAST TO THE CENTER OF THE NORTH & SOUTH ROAD AT THE SOUTHEAST CORNER OF SECTION 5-16-10 – **NO STONE**

CONTINUED ON PAGE 2

- 3) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 13, 2002, FOR SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 16-10 FOR A SURVEY FOR JAMES RICHARDS IN THE WEST FRACTIONAL HALF OF SECTION 7-10-10, SAID THAT HE EXCAVATED FOR THE GLO STONE CALLED OUT BY ALVA J. SMITH IN 1900 AT THE NORTHWEST CORNER OF SECTION 7-16-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE. HE FOUND THE GLO STONE LYING FLAT IN THE NORTH-SOUTH ROAD. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" REBAR WITH HIS "LS 82" CAP** FOR THE NORTHWEST CORNER OF SECTION 7-16-10 FROM CALLS IN THE STATUTORY SURVEY BY ALVA J. SMITH DATED 1900 AND RECORDED IN SURVEY BOOK "E" ON PAGE 185 IN THE LYON COUNTY SURVEYOR'S OFFICE.
- 1) 20.0' WEST TO THE NEAR FACE OF A LARGE STONE POST
 - 2) 28.5' EAST TO THE NEAR FACE OF A LARGE STONE POST
 - 3) 10.0' EAST TO A 1/2" REBAR WITH HIS "LS 82" CAP
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,118.50' EAST TO THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET FOR THE NORTHEAST CORNER OF THE 85.0 ACRE TRACT
 - 2) 1,138.5' EAST TO THE 4" STEEL CORNER POST HE SET FOR THE NORTHEAST CORNER OF GOVERNMENT LOT 1 IN THE NW1/4 OF SECTION 7-16-10
 - 3) 5,275.51' SOUTH ON THE RANGE LINE AND COUNTY LINE TO THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET FOR THE SOUTHWEST CORNER OF SEC. 7-16-10

NORTHWEST CORNER SECTION 07-16-10