

WEST 1/4 CORNER SECTION 08, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) ON PAGE 144 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 16" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 8-16-10.

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 5, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 185 DATED APRIL 2-4 AND MAY 8-9, 1900 AT THE ORDER OF THE RICHARDS BROTHERS FOR A SURVEY OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 6-16-10, SAID THAT HE DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 7-16-10 ON THIS **PERMANENT SURVEY**. HE USED A POINT IN THE MIDDLE OF THE ROAD ON THE EAST SIDE OF SECTION 7-16-10 FOR LINE. THERE IS ADDITIONAL INFORMATION IN PACKET "M 50" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION FROM THE MIDDLE OF THE ROAD ON THE EAST LINE OF SECTION 7-16-10:
 - 1) 20.21 CHAINS WEST TO THE STONE HE FOUND ON THE SOUTH LINE OF THE NE1/4 OF SECTION 7-16-10
 - 2) 76.48 CHAINS WEST TO THE STONE FENCE ON THE WEST LINE OF SECTION 7-16-10 ABOUT THE POINT WHERE THE 1/4 CORNER STONE SHOULD BE, BUT HE DID **NOT** FIND THE STONE

WEST QUARTER CORNER SECTION 08-16-10