

**CENTER CORNER SOUTHWEST 1/4 SECTION 10, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 2, 2010 FOR PROJECT NUMBER 10230-02, SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 16-10, A SURVEY OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 10-16-10 FOR JIM MASTERS, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE CENTER OF THE SOUTHWEST 1/4 OF SECTION 10-16-10 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/16<sup>TH</sup> CORNERS OF THE SOUTHWEST 1/4 OF SECTION 10-16-10 ON THIS SURVEY.
  - 1) 21.2' EAST TO A LINE OF FENCE RUNNING NORTH AND SOUTH
  - 2) 548.73' EAST TO A 1/2" REBAR WITH "LS 752" CAP SET ON THE NORTH LINE OF THE W1/2 OF THE SE1/4 OF THE SW1/4 [**HORIZONTAL TIE**]
  - 3) 13.10' WEST TO A CONCRETE NAIL & BOTTLECAP IN A 15" LOCUST TREE
  - 4) 38.90' SW TO A CONCRETE NAIL & BOTTLECAP IN A 15" LOCUST TREE
  - 5) 16.15' WNW TO A CONCRETE NAIL & BOTTLECAP IN A TRIPLE LOCUST TREE
  - 6) 1,326.63' SOUTH TO A 1/2" REBAR WITH "LS 752" CAP AT THE SW CORNER OF THE SE1/4 OF THE SW1/4 [**HORIZONTAL TIE**]

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

  - 1) 1,329.45' WEST TO THE THEORETICAL POSITION FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 10-16-10
  - 2) 1,326.63' NORTH TO THE THEORETICAL POSITION FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 10-16-10
  - 3) 1,329.46' EAST TO THE THEORETICAL POSITION FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 10-16-10

CENTER CORNER SOUTHWEST QUARTER 10-16-10