

**WEST 1/16 CORNER SOUTHWEST 1/4 SECTION 10, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 113 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 38 TO 40 PETITIONED BY JESSE LEYTON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-10 [PACKET 362 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 31, 1881, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 15, 1881 AS NOTED BY J. W. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 8, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 9-16-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 4-16-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 4.80 CHAINS TO AN ANGLE TO THE SOUTHEASTERLY DUE TO ROCK CREEK; THEN INTERSECTS THE SECTION LINE AT 412 FEET NORTH OF THE NORTHEAST CORNER OF SECTION 16-16-10; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 16-16-10 TO COMMENCE THIS ROAD SURVEY
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 220 BUT NOT DATED, FOR A ROAD SURVEY IN TOWNSHIP 16-10 APPARENTLY **FOUND THE STONE** AT THE EAST 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 9-16-10 AT AN ANGLE POINT ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 4-16-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 4.80 CHAINS TO AN ANGLE TO THE SOUTHEASTERLY DUE TO ROCK CREEK; THEN INTERSECTS THE SECTION LINE AT 412 FEET NORTH OF THE NORTHEAST CORNER OF SECTION 16-16-10; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 16-16-10 TO COMMENCE THIS ROAD SURVEY
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 16-10 DATED SEPTEMBER 2, 1910 FOR PROJECT NUMBER 10230-02, A SURVEY OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 10-16-10 FOR JIM MASTERS, SAID THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 10-16-10 TO BE ON LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 10-16-10 AND THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 10-16-10, BUT THAT THE POSITION WAS **NOT MONUMENTED** ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,324.64' SOUTH TO THE 80 D NAIL OVER A RAILROAD SPIKE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 10-16-10
- 2) 1,324.65' NORTH TO THE 1/2" REBAR WITH "CLS 27" CAP HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 10-16-10
- 3) 3,974.22' NORTH TO THE 1/2" REBAR WITH "CLS 27" CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 10-16-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 1,329.45' EAST TO THE 1/2" REBAR WITH "LS 752" CAP HE SET FOR THE CENTER OF THE SW1/4 OF SECTION 10-16-10
- 5) 1,994.18' EAST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF THE SW1/4 OF SECTION 10-16-10
- 6) 2,658.91' EAST TO THE THEORETICAL POSITION FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 10-16-10

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 10-16-10