

**NORTH 1/16 CORNER NORTHWEST 1/4 SECTION 15, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 2, 2010 FOR PROJECT NUMBER 10230-02, SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 16-10, A SURVEY OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 10-16-10 FOR JIM MASTERS, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 10-16-10 ON TRUE LINE AND AT HALF THE DISTANCE BETWEEN THE SOUTHEAST CORNER OF SECTION 10-16-10 AND THE SOUTH 1/4 CORNER OF SECTION 10-16-10. HE GAVE THE FOLLOWING **HORIZONTAL TIES:**

- 1) 28.00' NORTH TO A 1/2" REBAR WITH "LS 752" CAP SET IN AN EAST-WEST FENCE LINE
- 2) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY FOR A DIRT LANE RUNNING EAST-WEST
- 3) 1.5' EAST TO A LINE OF FENCE TO THE NORTH EXTENDED
- 4) 664.72' EAST TO A 1/2" REBAR WITH "LS 752" CAP
- 5) 114.90' SOUTH TO A 40 D NAIL & WASHER IN THE TOP OF A HEDGE FENCE POST
- 6) 56.5' SOUTH TO THE CENTERLINE TRAVELED WAY FOR U. S. 56 HIGHWAY

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,329.43' WEST TO THE 80 D NAIL OVER THE RAILROAD SPIKE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 10-16-10
- 2) 664.72' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF THE SW1/4 OF SEC. 10-16-10
- 3) 1,329.44' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 10-16-10
- 4) 3,997.66' EAST TO THE 2" ALUMINUM CAP STAMPED "LS 727" HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 10-16-10
- 5) 1,326.63' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER CORNER OF THE SW1/4 OF SECTION 10-16-10
- 6) 2,653.26' NORTH TO THE THEORETICAL POSITION FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 10-16-10

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 15-16-10