

WEST 1/16 CORNER SOUTHWEST 1/4 SECTION 15, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 85 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 342 TO 344 PETITIONED BY GEORGE W. LEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-10 [PACKET 225 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 27, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD FOR THE FIRST 80 RODS AND THE BALANCE TO BE 60 FEET WIDE ON OCTOBER 5, 1880 AS NOTED BY J. A. TAYLOR, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 15, 1880 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND OR SET THE STONE** AT 1,320 FEET SOUTH OF THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 16-16-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS 40 FOOT WIDE ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1,320 FEET [80 RODS] TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10 TO COMMENCE THIS ROAD SURVEY
- 2) THIS 60 FOOT WIDE ROAD ANGLES TO THE SOUTHWESTERLY AND INTERSECTS THE SECTION LINE AT THE NORTHEAST CORNER OF SECTION 21-16-10; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 33-16-10 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 192 DATED SEPTEMBER 27, 1880, APPARENTLY **FOUND OR SET A STONE** AT 1,320' SOUTH OF THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 16-16-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS 40 FOOT WIDE ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1,320 FEET [80 RODS] TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10 TO COMMENCE THIS ROAD SURVEY
- 2) THIS 60 FOOT WIDE ROAD ANGLES TO THE SOUTHWESTERLY AND INTERSECTS THE SECTION LINE AT THE NORTHEAST CORNER OF SECTION 21-16-10; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 33-16-10 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY

- 3) JOHN R. YOUNG, L.S. 112 OF SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH IN JUNE THROUGH AUGUST OF 1981, LARGE SURVEY SR #21001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A "MONUMENT"** AT THE SOUTHWEST CORNER OF THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 16-16-10 ON THIS SURVEY. [**NOTE:** THE SURVEY DOES NOT STATE THE TYPE OF MONUMENT, BUT **THEY SET 3/4" REBARS** AT THE OTHER CORNERS ON THIS SURVEY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

- 1) 27.9' WEST TO A SPIKE & 1 WASHER IN THE SIDE OF A FENCE POST
- 2) 35.7' SW TO A SPIKE & 2 WASHERS IN A POWER POLE
- 3) 19.9' SSE TO A SPIKE & 3 WASHERS IN A GUY POLE
- 4) 2' WEST TO THE TRAVELED WAY OF THE NORTH-SOUTH ROAD

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,325.66' NORTH TO THE 3/4" BAR HE SET FOR THE EAST 1/4 CORNER OF SECTION 16-16-10
- 2) 1,325.66' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 16-16-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 1,313.41' WEST TO THE 3/4" BAR HE SET FOR THE CENTER CORNER OF THE SOUTHEAST QUARTER OF SECTION 16-16-10
- 4) 2,626.82' WEST TO THE THEORETICAL LOCATION FOR THE WEST 1/16TH CORNER OF THE SE1/4 OF SECTION 16 -16-10

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 15-16-10