

**CENTER CORNER SECTION 16, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) JOHN R. YOUNG, L.S. 112 OF SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH IN JUNE TO AUGUST OF 1981, LARGE SURVEY SR 21001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT **THEY SET A 3/4" REBAR** FOR THE CENTER CORNER OF SECTION 16-16-10.
  - 1) 50.7' NW TO A SPIKE & 2 WASHERS IN A 20" MULBERRY TREE
  - 2) 30.5' NW TO A SPIKE & 3 WASHERS IN THE TOP OF A FENCE POST
  - 3) 12' NORTH TO AN EAST-WEST FENCE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 1,313.87' WEST TO THE 3/4" BAR HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 16-16-10
  - 2) 2,627.73' WEST TO THE 3/4" BAR HE SET FOR THE WEST 1/4 CORNER OF SECTION 16-16-10
  - 3) 1,313.87' EAST TO THE 3/4" BAR HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 16-16-10
  - 4) 2,627.73' EAST TO THE 3/4" BAR HE SET FOR THE EAST 1/4 CORNER OF SECTION 16-16-10
  - 5) 1,313.79' SOUTH TO THE THEORETICAL POSITION FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 16-16-10
  - 6) 2,635.58' SOUTH TO THE 3/4" BAR HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 16-16-10
  
- 2) MARTIN G. LONG, L.S 1081, OF CP ENGINEERS AND LAND SURVEYORS, INC., IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 17, 1998, FOR PROJECT 97-22 S, A SURVEY FOR THE KANSAS DEPARTMENT OF TRANSPORTATION FOR PROJECT 56-56-56-K-1088-01, THE BRIDGE REPLACEMENT ON BLUFF CREEK ON HIGHWAY 56, SURVEY F09001 IN THE SURVEY FILE FOR TOWNSHIP 16-10, SAID THAT **HE FOUND THE 0.018 M REBAR AT 0.020 METERS DEEP** AT THE CENTER CORNER OF SECTION 16-16-10 THAT WAS SET BY SCHWAB-EATON, INC. IN AUGUST 1981. **METRIC TIES:**
  - 1) 803.403 M SOUTH OF CENTERLINE STATION 4 + 050.744; SE ANGLE = 89°05'03"
  - 2) 9.394 M NW TO A SPIKE & WASHER IN THE TOP OF A BRACE POST
  - 3) 4.475 M NORTH TO A SPIKE & WASHER IN THE SIDE OF A "T" FENCE POST
  - 4) 9.032 M NE TO A SPIKE & WASHER IN THE SIDE OF A "T" FENCE POST
  - 5) 4.3 M NORTH TO A FENCE LINE EAST-WEST

HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:

  - 1) 800.949 METERS WEST TO THE 5/8" IRON PIN HE FOUND AT THE WEST 1/4 CORNER OF SECTION 16-16-10
  - 2) 801.106 METERS EAST TO THE 5/8" IRON PIN HE FOUND AT THE EAST 1/4 CORNER OF SECTION 16-16-10
  - 3) 804.857 METERS NORTH TO THE 1/2" REBAR WITH "CORP LS-27" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 16-16-10
  - 4) 1,612.036 METERS NORTH TO THE CALCULATED POSITION FOR THE CENTER CORNER OF SECTION 9-16-10
  - 5) 2,419.215 METERS NORTH TO THE 1/2" REBAR WITH "CORP LS-27" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 9-16-10

CENTER CORNER SECTION 16-16-10