

NORTH 1/4 CORNER SECTION 18, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) ON PAGE 144 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 12" X 10" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 18-16-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 36.65 CHAINS WEST TO THE 20" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-16-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE
 - 2) 40.00 CHAINS EAST TO THE 28" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-16-10

- 2) PLANS FOR KDOT PROJECT 50N-56-149, DATED 1941, SHOWS A **1" IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 18-16-10.
 - 1) 9.68' NORTH OF BASELINE STATION 392 + 72.81
 - 2) 79.90' NNW TO A SPIKE & WASHER IN THE TOP OF A FENCE POST
 - 3) 76.00' NORTH TO A SPIKE & WASHER IN THE TOP OF A FENCE POST
 - 4) 95.30' NE TO A SPIKE & WASHER IN THE TOP OF A FENCE POST

NORTH QUARTER CORNER SECTION 18-16-10