

NORTHWEST CORNER SECTION 20, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) ON PAGE 142 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-16-10.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST TO THE 18" X 21" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-16-10
- 2) 80.00 CHAINS EAST TO THE 18" X 18" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-16-10
- 3) 31.20 CHAINS SOUTH TO THE 30" X 15" X 12" LIMESTONE THEY SET ON THE NORTH BOUNDARY OF THE KANSAS INDIAN DIMINISHED RESERVATION
- 4) 40.00 CHAINS SOUTH TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 20-16-10
- 5) 80.00 CHAINS SOUTH TO THE 24" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-16-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE TOP RIGHT SIDE PAGE 165 DATED JUNE 11, 1879, FOR A COUNTY ROAD IN TOWNSHIP 16 SOUTH OF RANGE 10 EAST, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 19-16-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 5,280' WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-16-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO COMMENCE THIS ROAD SURVEY
- 2) 5,280' EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-16-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 31 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 122 & 123 PETITIONED BY JAMES FYFFE AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-10 [PACKET 117 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 11, 1879, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 16, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 19-16-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE NORTHWEST CORNER OF SECTION 19-16-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE NORTHEAST CORNER OF SECTION 20-16-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 38 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 154 TO 156 PETITION BY W. T KITCHEN AND OTHERS FOR THREE ROADS IN TOWNSHIPS 16-10 AND 17-10 [PACKET 134 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 2, 1879, WERE ESTABLISHED AT 60 FEET WIDE ON OCTOBER 6, 1879, AND WERE RECORDED ON OCTOBER 6, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 19-16-10 ON THE THIRD ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS THIRD ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 7-16-10 AT THE TERMINUS OF THIS THIRD ROAD ON THIS ROAD SURVEY
 - 2) THIS THIRD ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1,320' TO THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 20-16-10 AT AN ANGLE TO THE SOUTHWESTERLY DUE TO BLUFF CREEK AND INTERSECTS THE SECTION LINES AT THE 1/4 CORNER ON THE EAST LINE OF SECTION 19-16-10; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 30-16-10 TO COMMENCE THIS THIRD ROAD ON THIS ROAD SURVEY
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGES 190 & 191 FOR ROAD NUMBER 151 BY A PETITION BY E. BARCLAY [PACKET 379 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED JUNE 1881, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 19-16-10 ON THIS ROAD SURVEY FOR A 40 FOOT ROAD. **[NOTE:** A PENCIL NOTE UNDER THE PLAT STATES: "ALL DISALLOWED EXCEPT THAT PART THAT RUNS AROUND STONE FENCE OF MR. BARCLAY" – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 6) JOHN R. YOUNG, L.S. 122 OF SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH IN JUNE THROUGH AUGUST OF 1981, LARGE SURVEY SR 21001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A BOLT WITH SQUARE HEAD AT 6" BELOW THE SURFACE AND THEY ACCEPTED THIS BOLT** AS THE NORTHWEST CORNER OF SECTION 20-16-10 ON THIS SURVEY.
- 1) 21.9' SOUTH TO A SPIKE & 1 WASHER IN THE TOP OF A CORNER FENCE POST
 - 2) 54.5' NE TO A SPIKE & 2 WASHERS IN THE TOP OF A FENCE POST
 - 3) 34.8' NW TO A SPIKE & 3 WASHERS IN THE TOP OF A CORNER FENCE POST
 - 4) TRAVELED WAY OF EAST-WEST ROAD ON LINE
 - 5) TRAVELED WAY OF ROAD BEARS NORTH ON LINE
 - 6) 2' WEST TO A FENCE TO THE SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,311.22' SOUTH TO THE 3/4" BAR HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 NW1/4 OF SECTION 20-16-10
 - 2) 2,019.59' SOUTH TO THE STONE HE FOUND ON THE SECTION LINE AND INDIAN RESERVE LINE
 - 3) 2,622.43' SOUTH TO THE 3/4" BAR HE SET FOR THE WEST 1/4 CORNER OF SECTION 20-16-10
 - 4) 5,231.65' SOUTH TO THE 3/4" BAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 20-16-10
 - 5) 2,638.32' EAST TO THE 3/4" BAR HE SET FOR THE NORTH 1/4 CORNER OF SECTION 20-16-10
 - 6) 3,965.72' EAST TO THE THEORETICAL LOCATION FOR THE NORTH 1/16TH CORNER OF THE SE1/4 OF SECTION 20-16-10
 - 7) 5,293.12' EAST TO THE 3/4" BAR HE SET FROM REFERENCES FOR THE NORTHEAST CORNER OF SECTION 20-16-10

NORTHWEST CORNER SECTION 20-16-10