

**WEST 1/4 CORNER SECTION 20, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 142 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 20-16-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 8.90 CHAINS NORTH TO THE 30" X 15" X 12" LIMESTONE THEY SET ON THE NORTH BOUNDARY OF THE KANSAS INDIAN DIMINISHED RESERVATION
  - 2) 40.00 CHAINS NORTH TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-16-10
  - 3) 40.00 CHAINS SOUTH TO THE 24" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-16-10
  
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 38 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 154 TO 156 PETITION BY W. T KITCHEN AND OTHERS FOR THREE ROADS IN TOWNSHIPS 16-10 AND 17-10 [PACKET 134 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 2, 1879, WERE ESTABLISHED AT 60 FEET WIDE ON OCTOBER 6, 1879, AND WERE RECORDED ON OCTOBER 6, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 19-16-10 ON THE THIRD ROAD ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS THIRD ROAD EXTENDS NORTHWESTERLY DUE TO BLUFF CREEK AND INTERSECTS THE SECTION LINES AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 20-16-10; THEN CONTINUES NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 7-16-10 AT THE TERMINUS OF THIS THIRD ROAD ON THIS ROAD SURVEY
  - 2) THIS THIRD ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 30-16-10 TO COMMENCE THIS THIRD ROAD ON THIS ROAD SURVEY
  
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGES 190 & 191 FOR ROAD NUMBER 151 BY A PETITION BY E. BARCLAY [PACKET 379 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED JUNE 1881, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 19-16-10 ON THIS ROAD SURVEY FOR A 40 FOOT ROAD. [**NOTE:** A PENCIL NOTE UNDER THE PLAT STATES: "ALL DISALLOWED EXCEPT THAT PART THAT RUNS AROUND STONE FENCE OF MR. BARCLAY" – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
  
- 4) S. K. McCrary, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 602 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 277 THROUGH 280 PETITIONED BY W. W. BAIN AND OTHERS FOR THE LOCATION AND VACATION OF ROADS IN TOWNSHIP 16-10 [PACKET 743 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 16, 1905, WAS VACATED ON JULY 6, 1905 AS NOTED BY W. H. MAYES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON JULY 27, 1905 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT HE ENDED THE VACATION FOR ROAD NUMBER 6 IN TOWNSHIP 16-10 AT THE INTERSECTION OF ROAD NUMBER 422 NEAR THE WEST 1/4 CORNER OF SECTION 20-16-10.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS VACATED ROAD EXTENDS SOUTH BETWEEN SECTIONS 19 & 20 AND SOUTH BETWEEN SECTIONS 29 & 30 TO A POINT 1/4 OF A MILE [80 RODS] NORTH OF THE SOUTHWEST CORNER OF SECTION 29-16-12 TO BEGIN THE ROAD VACATED ON THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 5) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 172 DATED NOVEMBER 22, 1917 ORDERED BY J. O. SOUTHARD TO ESTABLISH THE LINE BETWEEN SOUTHARD AND TROUTMAN BETWEEN SECTIONS 19 & 20-16-10, SAID THAT **HE SET A STONE** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 19-16-10 ON THIS **PERMANENT SURVEY**. HE SET THE STONE ON LINE WITH THE STONE THAT HE FOUND ON THE KAW DIMINISHED RESERVE LINE TO THE NORTH OF THIS CORNER, TO THE STONE THAT HE SET SOUTH OF THE SOUTHEAST CORNER OF SECTION 19-16-10 SOUTH OF AN EAST AND WEST STONE FENCE ON THE SECTION LINE. HE NOTED THAT THIS SURVEY WAS RECORDED DECEMBER 15, 1917.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 2,640' SOUTH TO THE LOCATION FOR THE NORTHEAST CORNER OF SECTION 30-16-10 – **NO STONE SET**
  - 2) 5,290' SOUTH TO THE STONE HE FOUND IN PLACE AT THE EAST 1/4 CORNER OF SECTION 30-16-10
  - 3) 7,940' SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 30-16-10
- 6) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 151  
ON MARCH 13, 1937 A PETITION SIGNED BY C. S. GILBERT AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 16-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON APRIL 10, 1937, AND THE FINAL ORDER DATED MAY 5, 1937 **VACATED** THE FOLLOWING ROAD:
- 1) BEGINNING AT A POINT ON THE EAST LINE OF SECTION 20-16-10, NEAR THE EAST QUARTER CORNER OF SAID SECTION 20, AND RUNNING IN A WESTERLY DIRECTION THROUGH SECTION 20 APPROXIMATELY ONE MILE TO THE WEST LINE OF SAID SECTION AND ENDING THERE.
  - 2) SAID ROAD SHOULD BE VACATED.
  - 3) THE PRESENT ROAD IS FENCED AT ONE END AND A LARGE CULVERT COMPLETELY OUT AT THE OTHER. AND THE INTERLINING PORTION IS ALMOST IMPOSSIBLE TO TRAVEL.
  - 4) SINCE THERE IS NO EVIDENCE OF THE ROAD HAVING BEEN TRAVELED FOR SOME TIME, THE NATURAL CONCLUSION IS THAT IT IS OF VERY LITTLE PUBLIC UTILITY, IF ANY.
  - 5) AT THE TIME OF FENCING THERE WERE NO OBJECTIONS REGISTERED BECAUSE OF THE CLOSING OF THE ROAD, AND IT DOES NOT SEEM TO BE NEEDED, AS AN OUTLET FOR ANY HOUSEHOLDER OR LANDOWNER.
  - 6) THIS IS OUR DECISION FOR CLOSING THE ROAD IN ACCORDANCE WITH THE OLD PETITION PROPERLY SIGNED AND FILED.
- 7) JOHN R. YOUNG, L.S. 122 OF SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH IN JUNE THROUGH AUGUST OF 1981, LARGE SURVEY SR #21001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 3/4" REBAR** FOR THE WEST 1/4 CORNER OF SECTION 20-16-10 ON THIS SURVEY.
- 1) 21.5' WEST TO A SPIKE & 1 WASHER IN THE TOP OF A FENCE POST
  - 2) 7.6' ENE TO A SPIKE & 2 WASHERS IN THE TOP OF A FENCE POST
  - 3) 14.9' EAST TO A SPIKE & 3 WASHERS IN THE TOP OF A CORNER FENCE POST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 602.84' NORTH TO THE STONE HE FOUND ON THE SECTION LINE AND THE INDIAN RESERVE LINE
  - 2) 1,311.21' NORTH TO THE 3/4" BAR HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 20-16-10

HIS INFORMATION IS CONTINUED ON PAGE 3

- 3) 2,609.22' SOUTH TO THE 3/4" BAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 20-16-10
- 4) 2,632.25' EAST TO THE 3/4" BAR HE SET FOR THE CENTER CORNER OF SECTION 20-16-10
- 5) 3,957.88' EAST TO THE 3/4" BAR HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE NE1/4 OF SECTION 20-16-10
- 6) 5,283.31' EAST TO THE 3/4" BAR HE SET FOR THE WEST 1/4 CORNER OF SECTION 21-16-10

WEST QUARTER CORNER SECTION 20-16-10