

**NORTH 1/4 CORNER SECTION 21, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 138 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 21-16-10.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.96 CHAINS WEST TO THE 18" X 18" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-16-10
- 2) 39.97 CHAINS EAST TO THE 20" X 18" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-16-10

- 2) AI CHAMNESS, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 108 ORDERED BY GWENNIE THOMAS AND SARAH A. ELDRED FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS OF FIVE TRACTS OF LAND, EACH CONTAINING 80 ACRES MORE OR LESS, AND ARE DESCRIBED AS THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 21, ALL IN TOWNSHIP 16 SOUTH, RANGE 10 EAST, SAID THAT HE SET A **TEMPORARY POINT** FOR THE NORTH 1/4 CORNER OF SECTION 21-16-10 ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN JULY 6, 1936, THE REPORT WAS FILED JULY 28, 1936, AND THE SURVEY WAS RECORDED AUGUST 21, 1936. HE FIELD NOTES ARE IN BOOK "R" ON PAGE 26 OF THE KRETSINGER COLLECTION OF FIELD BOOKS.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 2,636.5' WEST TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 21-16-10, AT 24.5' SOUTH OF THE NORTH FENCE AND 20' WEST OF THE FENCE ON THE EAST SIDE OF THE ROAD
- 2) 2,636.5' EAST TO THE GOVERNMENT CORNERSTONE HE FOUND IN PLACE AT THE NORTHEAST CORNER OF SECTION 21-16-10, UPRIGHT, WITH 3 MARKS ON THE SOUTH FACE AND 3 MARKS ON THE WEST EDGE OF THE STONE, AND APPEARS TO BE IN LINE WITH A FENCE EASTWARD IN THE DISTANCE
- 3) 2,646.24' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 21-16-10
- 4) 3,967.62' SOUTH TO THE ROUND IRON PIN HE SET FOR THE PERMANENT WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 21-16-10
- 5) 5,289' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 28-16-10
- 6) 6,612.5' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT WEST 1/16<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 28-16-10
- 7) 7,936' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 28-16-10
- 8) 9,259.5' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 28-16-10
- 9) 10,583' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 28-16-10

- 3) JOHN R. YOUNG, L.S. 112, OF SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH IN JUNE THROUGH AUGUST OF 1981, LARGE SURVEY SR #21001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 3/4" REBAR** FOR THE SOUTH 1/4 CORNER OF SECTION 16-16-10 ON THIS SURVEY.

- 1) 128.0' NNW TO A SPIKE & 1 WASHER IN A 10" HEDGE TREE
- 2) APP. 250' SOUTHWEST TO THE NORTHEAST END OF A POND DAM

HIS TIES ARE CONTINUED ON PAGE 2

3) IN LINE WITH THE ROAD ON THE WEST HORIZON

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,315.64' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 16-16-10
- 2) 2,633.78' WEST TO THE 3/4" BAR HE SET FROM REFERENCES FOR THE NORTHEAST CORNER OF SECTION 20-16-10
- 3) 1,321.97' EAST TO THE THEORETICAL LOCATION FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 16-16-10
- 4) 2,643.93' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 16-16-10
- 5) 2,668.52' SOUTH TO THE 5/8" BAR HE FOUND AT THE CENTER CORNER OF SECTION 21-16-10
- 6) 5,310.71' SOUTH TO THE 1/2" SQUARE BAR HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 21-16-10

NORTH QUARTER CORNER SECTION 21-16-10