

NORTHWEST CORNER SECTION 22, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) ON PAGE 134 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 18" X 5"** FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-16-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.81 CHAINS EAST TO THE 22" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-16-10
 - 2) 79.62 CHAINS EAST TO THE 24" X 16" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-16-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 85 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 342 TO 344 PETITIONED BY GEORGE W. LEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-10 [PACKET 225 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 27, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD FOR THE FIRST 80 RODS AND THE BALANCE TO BE 60 FEET WIDE ON OCTOBER 5, 1880 AS NOTED BY J. A. TAYLOR, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 15, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND OR SET THE STONE** AT THE NORTHEAST CORNER OF SECTION 21-16-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS 60 FOOT WIDE ROAD ANGLES NORTHWESTERLY AND THEN INTERSECTS THE SECTION LINE AT 1,320 FEET [80 RODS] SOUTH OF THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10; THEN CONTINUES NORTH ON THE SECTION LINES AS A 40 FOOT WIDE ROAD FOR 1,320 FEET [80 RODS] TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS 60 FOOT WIDE ROAD CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 33-16-10 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 192 DATED SEPTEMBER 27, 1880, APPARENTLY **FOUND THE STONE** AT 5,280 FEET NORTH OF THE SOUTHEAST CORNER OF SECTION 21-16-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS 60 FOOT WIDE ROAD ANGLES NORTHWESTERLY AND THEN INTERSECTS THE SECTION LINE AT 1,320 FEET [80 RODS] SOUTH OF THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10; THEN CONTINUES NORTH ON THE SECTION LINES AS A 40 FOOT WIDE ROAD FOR 1,320 FEET [80 RODS] TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS 60 FOOT WIDE ROAD CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 33-16-10 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 18, RECORDED IN SURVEY BOOK "E" ON PAGE 18 DATED MARCH 10, 1884 FOR A ROAD SURVEY IN TOWNSHIP 16, RANGE 10 FOR HIRAM DRIGGS, PRINCIPAL PETITIONER, SAID THAT **HE APPARENTLY FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 16 AT THE INTERSECTION OF THE ROAD RUNNING NORTH AND SOUTH TO END THIS ROAD SURVEY THAT BEGAN ONE MILE WEST ON THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 17-16-10.

CONTINUED ON PAGE 2

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 260 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 626 TO 628 PETITIONED BY HIRAM DRIGGS AND OTHERS FOR THE LOCATION AND VACATION OF A COUNTY ROAD IN TOWNSHIP 16-10 [PACKET 500 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON APRIL 7, 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON APRIL 14, 1884 AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONER, AND RECORDED ON MAY 15, 1884 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 16-16-10 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 17-16-10 TO COMMENCE THIS ROAD SURVEY
- 6) AI CHAMNESS, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 108 ORDERED BY GWENNIE THOMAS AND SARAH A. ELDRED FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS OF FIVE TRACTS OF LAND, EACH CONTAINING 80 ACRES MORE OR LESS, AND ARE DESCRIBED AS THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 21, ALL IN TOWNSHIP 16 SOUTH, RANGE 10 EAST, SAID THAT **HE FOUND THE GOVERNMENT CORNER STONE UPRIGHT WITH 3 MARKS ON THE SOUTH SIDE AND THREE MARKS ON THE WEST EDGE** IN LINE WITH A FENCE EASTWARD IN THE DISTANCE AT THE NORTHEAST CORNER OF SECTION 21-16-10 ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN JULY 6, 1936, THE REPORT WAS FILED JULY 28, 1936 AND THE SURVEY WAS RECORDED ON AUGUST 21, 1936. HIS FILED NOTES ARE IN BOOK "R" ON PAGE 26 IN THE KRETSINGER COLLECTION OF FIELD BOOKS.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,636.5' WEST TO THE TEMPORARY POINT HE SET FOR THE NORTH 1/4 CORNER OF SECTION 21-16-10
 - 2) 5,273' WEST TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 21-16-10, AT 24.5' SOUTH OF THE NORTH FENCE AND 20' WEST OF THE FENCE ON THE EAST SIDE OF THE ROAD
 - 3) 2,649.5' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 21-16-10
 - 4) 3,974.25' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 21-16-10
 - 5) 5,299' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 21-16-10, ABOUT IN THE CENTER OF THE NORTH-SOUTH ROAD
 - 6) 6,623.5' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 28-16-10
 - 7) 7,948' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 28-16-10
 - 8) 9,272.5' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 28-16-10
 - 9) 10,597' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTH-EAST CORNER OF SECTION 28-16-10
- 7) JOHN R. YOUNG, L.S. 112, OF SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH IN JUNE THROUGH AUGUST, 1981, LARGE SURVEY SR #21001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT

HE FOUND THE STONE AT THE SOUTHEAST CORNER OF SECTION 16-16-10. HE CHISELED A PLUS (“+”) CUT ON THE TOP OF THE STONE.

- 1) 1/2” X 18” REBAR ON THE WEST SIDE OF THE STONE
- 2) NO OTHER REFERENCES AVAILABLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,321.96’ WEST TO THE THEORETICAL LOCATION FOR THE SOUTH 1/16TH CORNER OF THE SE1/4 OF SECTION 16-16-10
- 2) 2,643.93’ WEST TO THE 3/4” BAR HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 16-16-10
- 3) 3,959.57’ WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 16-16-10
- 4) 5,277.71’ WEST TO THE 3/4” BAR HE SET FROM REFERENCES AT THE NORTHEAST CORNER OF SECTION 20-16-10
- 5) 2,646.39’ SOUTH TO THE 3/4” BAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 21-16-10

NORTHWEST CORNER SECTION 22-16-10