

WEST 1/4 CORNER SECTION 25, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) ON PAGE 126 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 26-16-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 30" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-16-10
 - 2) 40.00 CHAINS SOUTH TO THE 30" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-16-10

- 2) MICHAEL A. ADAMS, L.S. 1126, OF COOK, FLATT & STROBEL ENGINEERS, IN A LAND SURVEY REFERENCE REPORT DATED MAY 18, 2000, FOR JOB NUMBER 00-018K, SAID THAT HE CONSIDERED THAT THE WEST 1/4 CORNER OF SECTION 25-16-10 WAS **LOST**. **HE SET A 1/2" REBAR WITH CAP** FOR THE WEST 1/4 CORNER OF SECTION 25-16-10 BY SINGLE PROPORTIONATE MEASUREMENT.
 - 1) 41.85' EAST TO A SPIKE & WASHER IN THE SIDE OF A FENCE CORNER POST
 - 2) 45.30' SE TO A SPIKE & WASHER IN A TELEPHONE SIGN POST
 - 3) 47.15' SW TO A SPIKE & WASHER IN A POWER POLE
 - 4) 43.70' WEST TO A SPIKE & WASHER IN THE TOP OF A FENCE CORNER POST
 - 5) IN THE CENTER OF NORTH-SOUTH ASPHALT PAVEMENT
 - 6) 24.0' NORTH TO THE CENTER OF FIELD ENTRANCE TO THE EAST

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 23, 2014, FOR PROJECT NUMBER 14142-02, THE SURVEY FOR AN EASEMENT IN THE NORTHEAST 1/4 OF SECTION 26-16-10 FOR WESTAR/BURRIS, SAID THAT **HE FOUND THE EXISTING 1/2" IRON PIN WITH A CAP** AT THE EAST 1/4 CORNER OF SECTION 26-16-10 FROM THE EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE BY M. ADAMS, L.S. 1226, IN 2000.
 - 1) 48.0' NE TO THE NEAR FACE OF A 4" PIPE BRACE POST
 - 2) 45.2' SE TO A 40 D NAIL & WASHER IN A TELEPHONE SIGN POST
 - 3) 47.1' SW TO A 40 D NAIL & WASHER IN A POWER POLE
 - 4) 43.6' WSW TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 5) IN THE TRAVELED WAY OF ASPHALT COUNTY ROAD "F" NORTH-SOUTH
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,657.63' NORTH TO THE 1/2" IRON PIN WITH THE REMAINS OF A CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 26-16-10

- 4) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 25, 2016, FOR PROJECT NUMBER 14142-02, THE SURVEY FOR AN EASEMENT IN THE NORTHEAST 1/4 OF SECTION 26-16-10 FOR WESTAR/BURRIS ON JULY 2, 2014, SAID THAT **HE FOUND THE EXISTING 1/2" IRON PIN WITH A CAP** AT THE EAST 1/4 CORNER OF SECTION 26-16-10 FROM THE EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE. HE NOTED THAT THIS CAPPED IRON PIN WAS SET BY M. ADAMS, L.S. 1226, IN 2000.
 - 1) 48.0' NE TO THE NEAR FACE OF A 4" PIPE BRACE POST
 - 2) 45.2' SE TO A 40 D NAIL & WASHER IN A TELEPHONE SIGN POST
 - 3) 47.1' SW TO A 40 D NAIL & WASHER IN A POWER POLE
 - 4) 43.6' WSW TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER POST
 - 5) IN THE TRAVELED WAY OF THE ASPHALT ROAD NORTH-SOUTH [COUNTY ROAD "F", THE AMERICUS-BUSHONG ROAD]

WEST QUARTER CORNER 25-16-10