

**NORTHWEST CORNER SECTION 26, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 130 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 14" X 4"** FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-16-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.92 CHAINS EAST TO THE 16" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-16-10
  - 2) 79.84 CHAINS EAST TO THE 30" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-16-10
  
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 165, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 135 DATED JULY 10-13, 1888 FOR LESTER NOPPER AND F. WILLIAMSON TO ESTABLISH THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4, THE CORNERS OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4, AND THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4, ALL IN SECTION 27, TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE IN THE GROUND IN GOOD CONDITION** AT THE NORTHEAST CORNER OF SECTION 27-16-10 ON THIS **AGREEMENT SURVEY**. THIS SURVEY WAS FILED IN VOLUME 41 ON PAGE 414 ON OCTOBER 18, 1888 IN THE REGISTER OF DEEDS OFFICE AND SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 16-10 IS A COPY OF THE RECORDED SURVEY.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 2,618.5' WEST TO THE FLAG HE SET FOR THE NORTH 1/4 CORNER OF SECTION 27-16-10
  - 2) 3,927.75' WEST TO THE 20" X 8" X 3" LIME STONE MARKED "1/8" ON THE NORTH SIDE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 27-16-10
  - 3) 5,237' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-16-10
  - 4) 1,319.5' SOUTH TO THE FLAG HE SET FOR THE EAST 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 27-16-10
  - 5) HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-16-10 SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-16-10 ON THE TOWNSHIP LINE
  
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 102, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 86 DATED MAY 7, 1886 FOR A ROAD IN TOWNSHIP 16, RANGE 10 FOR H. W. YUNDT, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 27-16-10 TO BEGIN THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD, BEING 25 FEET EACH SIDE OF THE SECTION LINE.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINE FOR 3/4 OF A MILE "PER GOVERNMENT SURVEY" TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 27-16-10 TO END THIS ROAD SURVEY
  
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 328 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 262 TO 264 PETITIONED BY H. W. YUNDT AND OTHERS FOR VACATING AND RELOCATING A ROAD IN TOWNSHIP 16-10 [PACKET 591 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 5, 1886, WAS ESTABLISHED AS

A 50 FOOT WIDE ROAD ON JULY 7, 1886 AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 3, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 27-16-10 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 3/4 OF A MILE "PER THE GOVERNMENT SURVEY" AT 25 FEET ON EACH SIDE OF THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 27-16-10 TO END THIS ROAD SURVEY
- 2) THE PETITIONED ROAD TO BE VACATED EXTENDED WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-16-10 WAS REJECTED BY THE BOARD OF COUNTY COMMISSIONERS

NORTHWEST CORNER SECTION 26-16-10