

WEST 1/16 CORNER NORTHEAST 1/4 SECTION 28, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 63, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 63 DATED SEPTEMBER 10, 1884 FOR LESTER FULLER, E. A. FOREST, JOHN FRODE, AND B. F. SILFIES TO SUBDIVIDE SECTION 28-16-10, WITH ONLY A DRAWING AND NO FIELD NOTES, SHOWS ON HIS DRAWING THAT **HE SET A STONE** FOR THE WEST 1/4/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 28-16-10 ON THIS **AGREEMENT SURVEY**.

- 2) AI CHAMNESS, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 108 ORDERED BY GWENNIE THOMAS AND SARAH A. ELDERD FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS OF FIVE TRACTS OF LAND, EACH CONTAINING 80 ACRES MORE OR LESS, AND ARE DESCRIBED AS THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 21, ALL IN TOWNSHIP 16 SOUTH, RANGE 10 EAST, SAID THAT **HE SET A SQUARE IRON PIN** FOR THE PERMANENT WEST 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 28-16-10 ON LINE AND HALFWAY BETWEEN THE SQUARE IRON PIN THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 28-16-10 AND THE SQUARE IRON PIN THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 28-16-10 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS BEGUN ON JULY 6, 1936, THE REPORT WAS FILED JULY 28, 1936, AND THE SURVEY RECORDED ON AUGUST 21, 1936. HIS FIELD NOTES ARE IN BOOK "R" ON PAGE 26 IN THE KRETSINGER COLLECTION OF FIELD BOOKS.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323.5' NORTH TO THE SQUARE IRON HE PIN SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 28-16-10
- 2) 2,644.88' NORTH TO THE ROUND IRON PIN HE SET FOR THE PERMANENT WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 21-16-10
- 3) 3,966.26' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 21-16-10
- 4) 6,612.5' NORTH TO THE TEMPORARY POINT HE SET FOR THE NORTH 1/4 CORNER OF SECTION 21-16-10
- 5) 1,323.5' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 28-16-10
- 6) 2,647' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT WEST 1/16TH CORNER OF THE SE1/4 OF SECTION 28-16-10
- 7) 3,970.5' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 28-16-10
- 8) 2,651' EAST TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 28-16-10

WEST SIXTEENTH CORNER NORTHEAST QUARTER 28-16-10