

NORTHWEST CORNER SECTION 29, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) ON PAGE 141 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 14" X 3"** FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-16-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.78 CHAINS EAST TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-16-10
 - 2) 49.25 CHAINS EAST TO THE 18" X 16" X 4" LIMESTONE THEY SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN DIMINISHED RESERVATION
 - 3) 79.56 CHAINS EAST TO THE 30" X 16" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-16-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 38 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 154 TO 156 PETITION BY W. T KITCHEN AND OTHERS FOR THREE ROADS IN TOWNSHIPS 16-10 AND 17-10 [PACKET 134 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 2, 1879, WERE ESTABLISHED AT 60 FEET WIDE ON OCTOBER 6, 1879, AND WERE RECORDED ON OCTOBER 6, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 30-16-10 ON THE THIRD ROAD ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS THIRD ROAD EXTENDS NORTH ON THE SECTION LINES TO THE 1/4 CORNER ON THE EAST LINE OF SECTION 19-16-10 AT A TURN TO THE NORTHWESTERLY DUE TO BLUFF CREEK, AND INTERSECTS THE SECTION LINES AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 20-16-10; THEN CONTINUES NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 7-16-10 AT THE TERMINUS OF THIS THIRD ROAD ON THIS ROAD SURVEY
 - 2) THIS THIRD ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 30-16-10 TO COMMENCE THIS THIRD ROAD ON THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGES 190 & 191 FOR ROAD NUMBER 151 BY A PETITION BY E. BARCLAY [PACKET 379 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED JUNE 1881, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 30-16-10 ON THIS ROAD SURVEY FOR A 40 FOOT ROAD. [NOTE: A PENCIL NOTE UNDER THE PLAT STATES: "ALL DISALLOWED EXCEPT THAT PART THAT RUNS AROUND STONE FENCE OF MR. BARCLAY" – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 14, A ROAD SURVEY RECORDED IN ROAD SURVEY BOOK "E" ON PAGE 194 DATED SEPTEMBER 11, 1900, FOR A ROAD IN TOWNSHIP 16-10 FOR CHARLES BLUE, PRINCIPAL PETITIONER, SAID THAT HE ENDED THIS ROAD SURVEY AT A POINT 778 FEET NORTH OF THE SOUTHWEST CORNER OF SECTION 20-16-10.

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 460 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 105 THROUGH 109 PETITIONED BY CHARLES BLUE FOR AN **OUTLET ROAD** [PACKET 700 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 9, 1900, WAS ESTABLISHED AS A 25 FOOT WIDE ROAD, 12-1/2 FEET EACH SIDE OF THE SURVEYED CENTER LINE, ON DECEMBER 7, 1900 AS NOTED BY W. H. MAYES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON DECEMBER 10,

1900 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT HE ENDED THIS ROAD SURVEY AT A POINT IN A NORTH AND SOUTH ROAD AT **788 FEET NORTH** OF THE SOUTHWEST CORNER OF SECTION 20-16-10.

HIS SURVEY NOTES SHOWS THE FOLLOWING CENTERLINE FROM THE ENDING POINT AT 788 FEET NORTH OF THE SOUTHWEST CORNER OF SECTION 20-16-10:

1) THIS ROAD EXTENDS EAST PARALLEL WITH THE SECTION LINE VARIANCE 8°25' E. FOR 482 FEET TO A POINT 12-1/2 FEET NORTH OF THE WEST END OF A WIRE FENCE, THEN S. 85°20' E. [MAGNETIC MERIDIAN] AND 12-1/2 FEET NORTH OF AND PARALLEL TO THE WIRE FENCE FOR 800 FEET TO A POINT 604 FEET NORTH OF THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 20-16-10 TO BEGIN THIS ROAD OUTLET SURVEY

6) S. K. McCrARY, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 602 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 277 THROUGH 280 PETITIONED BY W. W. BAIN AND OTHERS FOR THE LOCATION AND VACATION OF ROADS IN TOWNSHIP 16-10 [PACKET 743 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 16, 1905, WAS **VACATED** ON JULY 6, 1905 AS NOTED BY W. H. MAYES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON JULY 27, 1905 BY ALVA J. SMITH, COUNTY SURVEYOR, FOR THE **VACATION** FOR ROAD NUMBER 6 IN TOWNSHIP 16-10, APPARENTLY FOUND THE NORTHWEST CORNER OF SECTION 29-16-10 ON THIS ROAD **VACATION** SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS **VACATED** ROAD EXTENDS NORTH BETWEEN SECTIONS 19 & 20 TO THE INTERSECTION OF ROAD NUMBER 422 NEAR THE WEST 1/4 CORNER OF SECTION 20-16-10 TO END THIS ROAD **VACATION** SURVEY

2) THIS **VACATED** ROAD EXTENDS SOUTH BETWEEN SECTIONS 29 & 30 TO A POINT 1/4 OF A MILE [80 RODS] NORTH OF THE SOUTHWEST CORNER OF SECTION 29-16-12 TO BEGIN THE ROAD **VACATED** ON THIS ROAD SURVEY

7) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 172 DATED NOVEMBER 22, 1917 ORDERED BY J. O. SOUTHARD TO ESTABLISH THE LINE BETWEEN SOUTHARD AND TROUTMAN BETWEEN THE SECTIONS 19 & 20-16-10, SAID THAT HE DID **NOT** FIND THE STONE AT THE SOUTHEAST CORNER OF SECTION 19-16-10 ON THIS **PERMANENT SURVEY**. **HE SET A STONE** ON THE NORTH-SOUTH SECTION LINE JUST SOUTH OF AN EAST-WEST STONE FENCE **FOR LINE ONLY**, BUT **HE CALCULATED THE TRUE POSITION** FOR THE SOUTHEAST CORNER OF SECTION 19-16-10. HE NOTED THAT THIS SURVEY WAS RECORDED DECEMBER 15, 1917.

HIS NOTES/DRAWING SHOWS THE FOLLOWING DISTANCE FROM THE TRUE POSITION OF THE SOUTHEAST CORNER OF SECTION 19-16-10:

1) 2,640' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 19-16-10

2) 2,650' SOUTH TO THE STONE HE FOUND IN PLACE AT THE EAST 1/4 CORNER OF SECTION 30-16-10

3) 5,300' SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 30-16-10

7) JOHN R. YOUNG, L.S. 112. OF SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH IN JUNE THROUGH AUGUST OF 1981, LARGE SURVEY SR #21001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 3/4" REBAR** FOR THE SOUTHWEST CORNER OF SECTION 20-16-10 ON THIS SURVEY.

1) 6' EAST TO A NORTH-SOUTH ROCK FENCE

2) 85.5' SOUTH TO A LIMESTONE ON THE SECTION LINE

3) 86' SOUTH TO A FENCE CORNER [NORTH-SOUTH-WEST]

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 85.49' SOUTH TO THE ROAD STONE HE FOUND ON THE SECTION LINE
- 2) 2,650.62' SOUTH TO THE 3/4" BAR HE SET FOR THE WEST 1/4 CORNER OF SECTION 29-16-10
- 3) 3,975.91' SOUTH TO THE 3/4" BAR HE SET FOR HE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 29-16-10
- 4) 5,301.20' SOUTH TO THE 3/4" BAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 29-16-10

NORTHWEST CORNER SECTION 29-16-10