

**WEST 1/4 CORNER SECTION 29, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 141 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 30-16-10.
  
- 2) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 172 DATED NOVEMBER 22, 1917 ORDERED BY J. O. SOUTHARD TO ESTABLISH THE LINE BETWEEN SOUTHARD AND TROUTMAN BETWEEN THE SECTIONS 19 & 20-16-10, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE EAST 1/4 CORNER OF SECTION 30-16-10 ON THIS **PERMANENT SURVEY**. HE NOTED THAT THIS SURVEY WAS RECORDED DECEMBER 15, 1917.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,650' SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 30-16-10
  - 2) 2,650' NORTH TO THE TRUE POSITION FOR THE NORTHEAST CORNER OF SECTION 30-16-10 – **NO STONE SET**
  - 3) 5,290' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 19-16-10
  
- 3) JOHN R. YOUNG, L.S. 112, OF SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH IN JUNE THROUGH AUGUST OF 1981, LARGE SURVEY SR #21001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 3/4" REBAR** FOR THE WEST 1/4 CORNER OF SECTION 29-16-10 ON THIS SURVEY.
  - 1) 21.6' ENE TO A SPIKE & 1 WASHER IN THE TOP OF A FENCE POST
  - 2) 33.7' SE TO A SPIKE & 2 WASHERS IN THE TOP OF A FENCE POST
  - 3) 92.4' SSE TO A SPIKE & 3 WASHERS IN THE TOP OF A FENCE POST
  - 4) 20' EAST TO A NORTH-SOUTH FENCEHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,565.13' NORTH TO THE ROAD STONE HE FOUND ON THE SECTION LINE
  - 2) 2,650.62' NORTH TO THE 3/4" BAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 20-16-10
  - 3) 2,640.87' EAST TO THE 3/4" BAR HE SET FOR THE CENTER CORNER OF SECTION 29-16-10
  - 4) 1,325.29' SOUTH TO THE 3/4" BAR HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 29-16-10
  - 5) 2,650.58' SOUTH TO THE 3/4" BAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 29-16-10

WEST QUARTER CORNER SECTION 29-16-10