

**CENTER CORNER SECTION 32, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) LLOYD J. DOBLER, L.S. 541, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 3, 1991, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 16-10, A CORRECTED SURVEY FOR THE WALKUP & DENISON SURVEY TO LOCATE AND STAKE THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 32-16-10 RECORDED IN VOLUME 459 ON PAGE 558 IN THE REGISTER OF DEEDS OFFICE ON JUNE 5, 1991, SAID THAT **HE COMPUTED** THE LOCATION OF THE CENTER CORNER OF SECTION 32-16-10 TO BE AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS, BUT HE DID **NOT** MONUMENT THE POSITION.

**HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:**

- 1) 2,651.17' WEST TO THE 1/2" PIN HE SET FOR THE WEST 1/4 CORNER OF SECTION 32-16-10
- 2) 1,330.10' NORTH TO THE 1/2" PIN HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 32-16-10
- 3) 2,660.20' NORTH TO THE PIN HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-16-10
- 4) 2,640.76' EAST TO THE **COMPUTED POSITION** FOR THE EAST 1/4 CORNER OF SECTION 32-16-10
- 5) 2,663.57' SOUTH TO THE 1/2" PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 32-16-10

CENTER CORNER SECTION 32-16-10