

**NORTH 1/4 CORNER SECTION 33, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 137 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 14" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-16-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.96 CHAINS WEST TO THE 30" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-16-10
  - 2) 39.97 CHAINS EAST TO THE 20" X 16" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-16-10
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 75 DATED NOVEMBER 27, 1883 FOR A ROAD IN TOWNSHIP 16, RANGES 10, 11, 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 28-16-10 AT A TURN ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE FOR 1/4<sup>TH</sup> OF A MILE TO THE STONE HE FOUND OR SET FOR A TURN IN THIS ROAD SURVEY
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 248 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 TO 580 PETITION BY L. W. HUTCHASON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10, 16-11, 16-12 AND 16-13 [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED IN NOVEMBER 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, **EXCEPT** ON THE SOUTH LINE OF SECTION 28-16-12 ITS WIDTH IS TO BE 80 FEET FOR 8 RODS, ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1884 BY ROLAND LARKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 29-16-10 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1-1/2 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS NORTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 MILE LESS 20 FEET; THENCE EAST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET AT 20 FEET SOUTH OF THE EAST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 27-16-10; THEN SOUTH ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-16-10; THEN EAST ON THE SECTION LINES FOR 8 MILES TO THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE; THEN EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12; THENCE EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4-3/4 MILES TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY.
  
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 63, AN AGREEMENT SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 63 DATED

SEPTEMBER 10, 1884 FOR LESTER FULLER, E. A. FOREST, JOHN FRODE, AND B. F. SILFIES TO SUBDIVIDE SECTION 28-16-10, WITH ONLY A DRAWING AND NO FIELD NOTES, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 28-16-10 ON THIS AGREEMENT SURVEY.

5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 77, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 157 DATED JULY 7, 1903 AT THE REQUEST OF STEPHEN SIFFIES FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28 AND THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 33, ALL IN TOWNSHIP 16 AND RANGE 10 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN THE CENTER OF THE EAST-WEST ROAD AND ON LINE WITH THE FENCE ON THE WEST SIDE OF THE ROAD TO THE NORTH** AT THE NORTH 1/4 CORNER OF SECTION 33-16-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 184 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 160" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

6) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 663 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 82 FOR H. C. SILFIES, PRINCIPAL PETITIONER, FOR THE SURVEY OF A ROAD TO BE LOCATED ON THE SECTION LINE BETWEEN SECTIONS 27 & 34, AND 28 & 33 IN TOWNSHIP 16, RANGE 10, AND THE VACATION OF A PORTION OF THE ROAD IN SECTIONS 27 & 28 OF THE ABOVE TOWNSHIP AND RANGE AS VIEWED BY THE COUNTY COMMISSIONERS ACTING AS VIEWERS AND THE COUNTY SURVEYOR ON SEPTEMBER 2, 1909, SURVEYED ON MARCH 29 & 21, 1910 AND ENTERED IN THE PERMANENT SURVEY BOOK ON MARCH 31, 1910, SAID THAT **HE SET A 4 X 6 X 14 INCH ROAD STONE MARKED "R" ON THE NORTH SIDE** FOR THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-16-10 AT THE TERMINATION OF THE SECOND ROAD ON THIS ROAD SURVEY. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "E" ON PAGE 20.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THE SECOND ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,641 FEET TO THE ESTABLISHED STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-16-10 TO END THE SECOND ROAD ON THIS ROAD SURVEY
- 2) THE NEW ROADS ARE 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS DESCRIBED
- 3) THE ROAD **VACATED** BEGAN AT A POINT 80 RODS NORTH OF THE SOUTHEAST CORNER OF SECTION 27-16-10; THENCE WEST TO THE POINT 80 RODS NORTH OF THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-16-10; THENCE SOUTH TO THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-16-10, **EXCEPT** BEGINNING AT A POINT 80 RODS NORTH OF THE SOUTHWEST CORNER OF SECTION 16-10 AND RUNNING WEST FOR 608 FEET WILL **NOT** BE VACATED.

7) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 663 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 20 PETITION BY H. C. SILFIES AND OTHERS FOR THE LOCATION AND VACATION OF A ROAD IN TOWNSHIP 16-10 [PACKET 909 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS ON SEPTEMBER 2, 1909, AND WAS GRANTED ON JANUARY 2, 1911, SAID THAT **HE SET A 4 X 6 X 14 INCH**

**ROAD STONE MARKED "R" ON THE NORTH SIDE** FOR THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-16-10 AT THE TERMINATION OF THE SECOND ROAD ON THIS ROAD SURVEY. HE SAID TO SEE SURVEYOR RECORD 1 ON PAGE 82 FOR DESCRIPTIONS OF THE MARKS AND A LARGE PLAT.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE SECOND ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,641 FEET TO THE ESTABLISHED STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-16-10 TO END THE SECOND ROAD ON THIS ROAD SURVEY
- 2) THE NEW ROADS ARE 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS DESCRIBED
- 3) THE ROAD **VACATED** BEGAN AT A POINT 80 RODS NORTH OF THE SOUTHEAST CORNER OF SECTION 27-16-10; THENCE WEST TO THE POINT 80 RODS NORTH OF THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-16-10; THENCE SOUTH TO THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-16-10, **EXCEPT** BEGINNING AT A POINT 80 RODS NORTH OF THE SOUTHWEST CORNER OF SECTION 16-10 AND RUNNING WEST FOR 608 FEET WILL **NOT** BE VACATED.

8) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 1

ON AUGUST 2, 1909 A PETITION SIGNED BY H. C. SELFIES AND OTHERS FOR THE LOCATION AND VACATION OF CERTAIN ROADS IN TOWNSHIP 16-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROADS WERE VIEWED ON SEPTEMBER 2, 1909, AND THE FINAL ORDER FOR THE LOCATION AND VACATION OF THE FOLLOWING ROADS WAS ISSUED.

- 1) THE **VACATED** ROAD ENDS AT THIS CORNER AND EXTENDS NORTH FOR 80 RODS; THEN EXTENDS EAST FOR 1-1/2 MILES TO BEGIN THE ROAD **VACATED**
- 2) THE ROAD LOCATED EXTENDS EAST FOR 1-1/2 MILES TO THE SOUTHWEST CORNER OF SECTION 26-16-10 TO BEGIN THIS ROAD THAT IS 40 FEET WIDE

9) AI CHAMNESS, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 108 ORDERED BY GWENNIE THOMAS AND SARAH A. ELDRED FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS OF FIVE TRACTS OF LAND, EACH CONTAINING 80 ACRES MORE OR LESS, AND ARE DESCRIBED AS THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 21, ALL IN TOWNSHIP 16 SOUTH, RANGE 10 EAST, SAID THAT **HE SET A SQUARE IRON PIN** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 28-16-10 ON LINE AND HALFWAY BETWEEN THE SQUARE IRON PIN THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 28-16-10 AND THE SQUARE IRON PIN THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 28-16-10 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS BEGUN JULY 6, 1936, THE REPORT WAS FILED JULY 28, 1936, AND THE SURVEY WAS RECORDED ON AUGUST 21, 1936. HIS FIELD NOTES ARE IN BOOK "R" ON PAGE 26 IN THE KRETSINGER COLLECTION OF FIELD BOOKS.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,646.5' WEST TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 28-16-10
- 2) 2,646.5' EAST TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 28-16-10
- 3) 1,323.5' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 28-16-10
- 4) 2,647' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 28-16-10

HIS INFORMATION IS CONTINUED ON PAGE 4

- 5) 3,970.5' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT WEST 1/16<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 28
  - 6) 5,294' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 28-16-10
  - 7) 6,615.38' NORTH TO THE ROUND IRON PIN HE SET FOR THE PERMANENT WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 21-16-10
  - 8) 7,936.76' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 21-16-10
  - 9) 10,583' NORTH TO THE TEMPORARY POINT HE SET FOR THE NORTH 1/4 CORNER OF SECTION 21-16-10
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 2, 2010, FOR PROJECT NUMBER 09354-02, SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 16-10, TO SURVEY A TRACT IN THE NORTHEAST 1/4 OF SECTION 33-16-10 FOR GATES REALTY, SAID THAT HE EXCAVATED FOR THE GLO STONE AT THE NORTH 1/4 CORNER OF SECTION 33-16-10 THAT WAS FOUND BY ALVA J. SMITH IN 1903 IN SURVEY BOOK "F" ON PAGE 157 AND BY MATTHEW BROWN IN A 1910 ROAD SURVEY RECORDED IN ROAD RECORD BOOK "E" ON PAGE 20, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS BOTH **LOST** AND **OBLITERATED**. HE RESET THIS CORNER IN LINE WITH THE FENCE TO THE NORTH AS PER THE 1884 ROAD SURVEY BY ROBERT MILLIKEN RECORDED IN ROAD RECORD BOOK "B" ON PAGE 578 AND BY THE PERMANENT SURVEY BY SMITH IN SECTION 33-16-10 [WEST SIDE OF OLD ROAD]. THE SQUARE #4 REBAR SET BY AI CHAMNESS IN A PERMANENT SURVEY IN SECTION 28-16-10 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 108 WAS USED FOR NORTH-SOUTH POSITION. **HE SET A 5/8" X 12" REBAR WITH A LYON COUNTY CAP IN A ROCK LEDGE** FOR THE NORTH 1/4 CORNER OF SECTION 33-16-10.
- 1) 21.90' NNW TO A NAIL & BOTTLE CAP IN THE TOP OF A CORNER FENCE POST
  - 2) 42.15' SE TO A NAIL & BOTTLE CAP IN THE WEST FACE OF A CORNER FENCE POST
  - 3) 29.40' SSE TO A NAIL & BOTTLECAP IN THE WEST FACE OF A CORNER FENCE POST
  - 4) 8.0' SOUTH TO THE CENTERLINE TRAVELED-WAY OF COUNTY ROAD 320 EAST-WEST
  - 5) IN LINE WITH A FENCE TO THE NORTH
  - 6) **21.34' EAST TO A SQUARE #4 BENT REBAR SET BY CHAMNESS [PERMANENT SURVEY BOOK 1, PAGE 108] FOR THE SOUTH 1/4 CORNER OF SECTION 28-16-10. HE REPLACED THIS BENT SQUARE #4 REBAR WITH A 1/2" X 24" REBAR WITH HIS "LS 752" CAP.**
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,666.00' EAST TO THE COTTON GIN SPINDLE HE SET FOR THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 33-16-10

NORTH QUARTER CORNER SECTION 33-16-10