

NORTHWEST CORNER SECTION 33, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) ON PAGE 136 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 30" X 14" X 3"** FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-16-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.96 CHAINS EAST TO THE 14" X 14" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-16-10
 - 2) 79.93 CHAINS EAST TO THE 20" X 16" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-16-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 39 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 158 & 159 PETITION BY SAMUEL SOWERS AND OTHERS FOR THREE ROADS IN TOWNSHIPS 16-10 AND 17-10 [PACKET 136 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 5, 1879, WERE ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 6, 1879, AND WERE RECORDED ON OCTOBER 6, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT HE FOUND THE STONE AT THE SOUTHEAST CORNER OF SECTION 29-16-10 ON THE FIRST ROAD ON THIS ROAD SURVEY. [NOTE: SEE THE RECORD FOR THE EXISTING ROAD FROM THE SOUTHEAST CORNER OF SECTION 17-16-10 THAT EXTENDED SOUTHEASTERLY AND THEN SOUTHWESTERLY TO THE SOUTHWEST CORNER OF LOT 4 IN THE SOUTHEAST CORNER OF SECTION 5-17-10 WAS VACATED ON THIS ROAD SURVEY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS FIRST ROAD EXTENDS NORTH ON THE SECTION LINES TO A POINT 391' NORTH OF THE EAST 1/4 CORNER OF SECTION 20-16-10 TO AN ANGLE TO THE NORTHEASTERLY; THEN INTERSECTS THE SECTION LINE AT 1,653' SOUTH OF THE SOUTHEAST CORNER OF SECTION 17-16-10; THEN CONTINUES NORTH ON THE SECTION LINES FOR 1,653' TO THE NORTHEAST CORNER OF SECTION 17-16-10 TO COMMENCE THE FIRST ROAD ON THIS ROAD SURVEY
 - 2) THIS FIRST ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE EAST 1/4 CORNER OF SECTION 5-17-10 AT A TURN TO THE EAST

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 75 DATED NOVEMBER 27, 1883 FOR A ROAD IN TOWNSHIP 16, RANGES 10, 11, 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER 28-16-10 AT A TURN ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS NORTH EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10 AT A TURN TO THE NORTH ON THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 248 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 TO 580 PETITION BY L. W. HUTCHASON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10, 16-11, 16-12 AND 16-13 [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED IN NOVEMBER 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, EXCEPT ON THE SOUTH LINE OF SECTION 28-16-12 ITS WIDTH IS TO BE 80 FEET FOR 8 RODS, ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1884 BY ROLAND LARKIN,

COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 29-16-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1/2 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 26-16-10; THEN NORTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 MILE LESS 20 FEET; THENCE EAST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET AT 20 FEET SOUTH OF THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 27-16-10; THEN SOUTH ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-16-10; THEN EAST ON THE SECTION LINES FOR 8 MILES TO THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE; THEN EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12; THENCE EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4-3/4 MILES TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY.
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 63, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 63 DATED SEPTEMBER 10, 1884 FOR LESTER FULLER, E. A. FOREST, JOHN FRODE, AND B. F. SILFIES TO SUBDIVIDE SECTION 28-16-10, WITH ONLY A DRAWING AND NO FIELD NOTES, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 28-16-10 ON THIS **AGREEMENT SURVEY**.
- 6) S. K. McCRRARY, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 602 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 277 THROUGH 280 PETITIONED BY W. W. BAIN AND OTHERS FOR THE LOCATION AND VACATION OF ROADS IN TOWNSHIP 16-10 [PACKET 743 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 16, 1905, WAS **VACATED** ON JULY 6, 1905 AS NOTED BY W. H. MAYES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON JULY 27, 1905 BY ALVA J. SMITH, COUNTY SURVEYOR, FOR THE **VACATION** FOR ROAD NUMBER 7 IN TOWNSHIP 16-10, SAID THAT HE BEGAN THIS ROAD **VACATION** SURVEY AT A POINT ON THE NORTH SIDE OF ROAD NUMBER 248 **CLOSE** TO THE SECTION CORNER TO SECTIONS 28, 29, 32 & 33-16-10.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD **VACATION** EXTENDS NORTH BETWEEN SECTIONS 29 & 30, AND NORTH BETWEEN SECTIONS 20 & 21 TO THE INTERSECTION OF ROAD NUMBER 422 ON THE WEST LINE OF THE NORTHWEST 1/4 OF SECTION 21-16-10 TO END THIS ROAD **VACATION** SURVEY
 - 7) AI CHAMNESS, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 108 ORDERED BY GWENNIE THOMAS AND SARAH A. ELDRED FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS OF FIVE TRACTS OF LAND, EACH CONTAINING 80 ACRES MORE OR LESS, AND ARE DESCRIBED AS THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 21, ALL IN TOWNSHIP 16 SOUTH, RANGE 10 EAST, SAID THAT **HE SET A SQUARE IRON PIN IN LINE WITH A**

WIRE FENCE TO THE SOUTH AND AN OSAGE HEDGE TO THE NORTH FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 28-16-10 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS BEGUN ON JULY 6, 1936, THE REPORT WAS FILED JULY 28, 1936, AND THE SURVEY WAS RECORDED ON AUGUST 21, 1936. HIS FIELD NOTES ARE IN BOOK "R" ON PAGE 26 IN THE KRETSINGER COLLECTION OF FIELD BOOKS.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,645' NORTH TO THE TEMPORARY POINT HE SET FOR THE WEST 1/4 CORNER OF SECTION 28-16-10
 - 2) 5,290' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 28-16-10, IN LINE WITH A FENCE AND OLD POSTS TO THE SOUTH
 - 3) 7,925.75' NORTH TO THE TEMPORARY POINT HE SET FOR THE WEST 1/4 CORNER OF SECTION 21-16-10
 - 4) 10,561.5' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 21-16-10, AT 24.5' SOUTH OF THE NORTH FENCE AND 20' WEST OF THE FENCE ON THE EAST SIDE OF THE ROAD
 - 5) 2,646.5' EAST TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 28-16-10
 - 6) 5,293' EAST TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 28-16-10
- 8) SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH IN JUNE THROUGH AUGUST OF 1981, LARGE SURVEY SR #21001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A 1/2" BAR IN BENT CONDITION** AT THE NORTHWEST CORNER OF SECTION 33-16-10 ON THIS SURVEY.
- 1) 21.4' SOUTH TO A SPIKE & 1 WASHER IN THE TOP OF A FENCE POST
 - 2) 44.8' SW TO A SPIKE & 1 WASHER IN THE TOP OF A FENCE POST
 - 3) 22.1' NE TO A SPIKE & 1 WASHER IN AN 80" HEDGE TREE
 - 4) THE TRAVELED WAY OF THE EAST-WEST ROAD IS ON LINE
 - 5) A HEDGE ROW BEARS NORTH ON LINE
 - 6) 20' WEST TO A FENCE THAT BEARS SOUTH
- 9) SCHWAB-EATON, P.A., IN THE SURVEY FOR THE KIZLER RANCH AND BEARSKIN RANCH IN NOVEMBER 1986, LARGE SURVEY SR #21002 IN THE SURVEY DRAWER FOR TOWNSHIP 16-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 1/2" REBAR IN BENT CONDITION** AT THE NORTHWEST CORNER OF SECTION 33-16-10 ON THIS SURVEY.
- 1) 21.4' SOUTH TO A SPIKE & 1 WASHER IN THE TOP OF A FENCE POST
 - 2) 44.8' SW TO A SPIKE & 1 WASHER IN THE TOP OF A FENCE POST
 - 3) 22.1' NE TO A SPIKE & 1 WASHER IN AN 80" HEDGE TREE
 - 4) THE TRAVELED WAY OF THE EAST-WEST ROAD IS ON LINE
 - 5) A HEDGE ROW BEARS NORTH ON LINE
 - 6) 20' WEST TO A FENCE THAT BEARS SOUTH
- 10) LLOYD J. DOBLER, L.S. 541, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 3, 1991, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 16-10, A CORRECTED SURVEY FOR THE WALKUP & DENISON SURVEY TO LOCATE AND STAKE THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 32-16-10 RECORDED IN VOLUME 459 ON PAGE 558 IN THE REGISTER OF DEEDS OFFICE ON JUNE 5, 1991, SAID THAT **HE FOUND A 3/4" IRON PIN** AT THE NORTHEAST CORNER OF SECTION 32-16-10.
- 1) 22.20' SOUTH TO A NAIL IN THE TOP OF A POST
 - 2) 45.0' WSW TO A NAIL IN THE TOP OF THE WEST GATE POST

HIS TIES ARE CONTINUED ON PAGE 4

3) 28.45' NNW TO A NAIL IN THE TOP OF A FENCE POST

HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:

- 1) 2,652.70' WEST TO THE PIN HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-16-10
- 2) 5,305.27' WEST TO THE PIN HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-16-10
- 3) 1,325.73' SOUTH TO THE 1/2" PIN HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 32-16-10
- 4) 2,651.46' SOUTH TO THE **COMPUTED LOCATION** FOR THE EAST 1/4 CORNER OF SECTION 32-16-10
- 5) 5,302.31' SOUTH TO THE PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 32-16-10

NORTHWEST CORNER SECTION 33-16-10