

**NORTHWEST CORNER SECTION 34, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 133 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 5"** FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-16-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.87 CHAINS EAST TO THE 14" X 10" X 6" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-16-10
  - 2) 79.75 CHAINS EAST TO THE 20" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-16-10
  
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 85 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 342 TO 344 PETITIONED BY GEORGE W. LEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-10 [PACKET 225 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 27, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD FOR THE FIRST 80 RODS AND THE BALANCE TO BE 60 FEET WIDE ON OCTOBER 5, 1880 AS NOTED BY J. A. TAYLOR, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 15, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT HE FOUND THE STONE AT THE SOUTHEAST CORNER OF SECTION 28-16-10 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS 60 FOOT WIDE ROAD EXTENDS NORTH ON THE SECTION LINE TO THE NORTHEAST CORNER OF SECTION 21-16-10; THEN ANGLES NORTHWESTERLY AND THEN INTERSECTS THE SECTION LINE AT 1,320 FEET [80 RODS] SOUTH OF THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10; THEN CONTINUES NORTH ON THE SECTION LINES AS A 40 FOOT WIDE ROAD FOR 1,320 FEET [80 RODS] TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10 TO COMMENCE THIS ROAD SURVEY
  - 2) THIS 60 FOOT WIDE ROAD CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 33-16-10 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY
  
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 192 DATED SEPTEMBER 27, 1880, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 28-16-10 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS 60 FOOT WIDE ROAD EXTENDS NORTH ON THE SECTION LINE TO THE NORTHEAST CORNER OF SECTION 21-16-10; THEN ANGLES NORTHWESTERLY AND THEN INTERSECTS THE SECTION LINE AT 1,320 FEET [80 RODS] SOUTH OF THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10; THEN CONTINUES NORTH ON THE SECTION LINES AS A 40 FOOT WIDE ROAD FOR 1,320 FEET [80 RODS] TO THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 16-16-10 TO COMMENCE THIS ROAD SURVEY
  - 2) THIS 60 FOOT WIDE ROAD CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 33-16-10 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY
  
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 63, AN AGREEMENT SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 63 DATED SEPTEMBER 10, 1884 FOR LESTER FULLER, E. A. FOREST, JOHN FRODE, AND B. F. SILFIES TO SUBDIVIDE SECTION 28-16-10, WITH ONLY A DRAWING AND NO FIELD NOTES, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 28-16-10 ON THIS AGREEMENT SURVEY.

CONTINUED ON PAGE 2

- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 165, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 135 DATED JULY 10-13, 1888 FOR LESTER NOPPER AND F. WILLIAMSON TO ESTABLISH THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4, THE CORNERS OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4, AND THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 , ALL IN SECTION 27, TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE IN THE GROUND IN GOOD CONDITION** AT THE SOUTHWEST CORNER OF SECTION 27-16-10 ON THIS **AGREEMENT SURVEY**. THIS SURVEY WAS FILED IN VOLUME 41 ON PAGE 414 ON OCTOBER 18, 1888 IN THE REGISTER OF DEEDS OFFICE AND SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 16-10 IS A COPY OF THE RECORDED SURVEY.

**HIS NOTES SHOW THE FOLLOWING INFORMATION:**

- 1) 1,320' NORTH TO THE TEMPORARY STAKE HE SET FOR THE WEST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 27-16-10
  - 2) 2,640' NORTH TO THE TEMPORARY STAKE HE SET FOR THE WEST 1/4 CORNER OF SECTION 27-16-10
  - 3) 3,960' NORTH TO A STONE HE FOUND AT THE WEST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 27-16-10 FROM A FORMER SURVEY
  - 4) 5,280' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-16-10
  - 5) 7,887' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35-16-10
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 77, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 157 DATED JULY 7, 1903 AT THE REQUEST OF STEPHEN SIFFIES FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28 AND THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 33, ALL IN TOWNSHIP 16 AND RANGE 10 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT HE FOUND THE TOP PIECE OF THE ORIGINAL STONE **LYING ON THE GROUND** AT THE NORTHEAST CORNER OF SECTION 33-16-10. HE DUG FOR AND HE FOUND THE BOTTOM PIECE OF THE ORIGINAL STONE IN A ROCK LEDGE. **HE MADE A LARGE HOLE AND HE SET A 15" X 12" X 8" STONE DRESSED WITH A CHISELED SQUARE ON THE TOP** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 33-16-10. HE PUT THE TOP OF THE ORIGINAL STONE BY THE SIDE OF THE NEW STONE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 184 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 160" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 3.00 CHAINS SOUTH TO THE 24" X 12" X 3" STONE DRESSED WITH A CHISELED SQUARE ON THE TOP HE SET FOR A PERMANENT PROPERTY CORNER
- 2) 20.04 CHAINS SOUTH TO THE STONE HE FOUND AT THE EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 33-16-10 THAT WAS "SET BY UNKNOWN PARTIES"
- 3) 40.10 CHAINS SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 33-16-10 THAT WAS SET BY BROWN
- 4) 80.21 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-16-10 ON THE TOWNSHIP LINE, LOCATED 30 FEET NORTH AND 27 FEET WEST OF THE CORNER OF HEDGES
- 5) 20.08 CHAINS NORTH TO THE 20" X 12" X 8" STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 28-16-10 THAT STANDS 3 FEET NORTH OF THE FENCES ON THE NORTH SIDE OF THE ROAD

HIS INFORMATION IS CONTINUED ON PAGE 3

- 6) 40.16 CHAINS NORTH TO THE LOCATION FOR THE EAST 1/4 CORNER OF SECTION 28-16-10
  - 7) 60.24 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 28-16-10 THAT WAS SET BY EDMISTON IN 1884
  - 8) 80.30 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-16-10
- 7) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 663 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 82 FOR H. C. SILFIES, PRINCIPAL PETITIONER, FOR THE SURVEY OF A ROAD TO BE LOCATED ON THE SECTION LINE BETWEEN SECTIONS 27 & 34, AND 28 & 33 IN TOWNSHIP 16, RANGE 10, AND THE VACATION OF A PORTION OF THE ROAD IN SECTIONS 27 & 28 OF THE ABOVE TOWNSHIP AND RANGE AS VIEWED BY THE COUNTY COMMISSIONERS ACTING AS VIEWERS AND THE COUNTY SURVEYOR ON SEPTEMBER 2, 1909, SURVEYED ON MARCH 29 & 21, 1910 AND ENTERED IN THE PERMANENT SURVEY BOOK ON MARCH 31, 1910, SAID THAT **HE FOUND THE ESTABLISHED STONE** AT THE SOUTHWEST CORNER OF SECTION 27-16-10 TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "E" ON PAGE 20.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) THE FIRST ROAD ENDS AT THE 6 X 8 X 12 INCH ROAD STONE MARKED "R" ON THE NORTH SIDE HE PLANTED AT 152 FEET NORTH; THENCE S. 87°45' E. FOR 3,995 FEET TO THE 2 X 14 X 12 INCH ROAD STONE HE PLANTED ON THE SECTION LINE; THENCE EAST ON THE SECTION LINE FOR 1,317 FEET TO THE 8 X 12 X 15 INCH ROAD STONE MARKED "R" ON THE NORTH SIDE HE PLANTED FOR THE SOUTHEAST CORNER OF SECTION 27-16-10 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
  - 2) THE SECOND ROAD EXTENDS WEST ON THE SECTION LINES FOR 2,641 FEET TO THE TO THE 4 X 6 X 4 INCH ROAD STONE MARKED "R" ON THE NORTH FACE HE PLANTED AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-16-10 TO END THE SECOND ROAD ON THIS ROAD SURVEY
  - 3) THE NEW ROADS ARE 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS DESCRIBED
- 8) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 663 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 20 PETITION BY H. C. SILFIES AND OTHERS FOR THE LOCATION AND VACATION OF A ROAD IN TOWNSHIP 16-10 [PACKET 909 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS ON SEPTEMBER 2, 1909, AND WAS GRANTED ON JANUARY 2, 1911, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 27-16-10 TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY. HE SAID TO SEE SURVEYOR RECORD 1 ON PAGE 82 FOR DESCRIPTIONS OF THE MARKS AND A LARGE PLAT.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE FIRST ROAD ENDS AT THE 6 X 8 X 12 INCH ROAD STONE MARKED "R" ON THE NORTH SIDE HE PLANTED AT 152 FEET NORTH; THENCE S. 87°45' E. FOR 3,995 FEET TO THE 2 X 14 X 12 INCH ROAD STONE HE PLANTED ON THE SECTION LINE; THENCE EAST ON THE SECTION LINE FOR 1,317 FEET TO THE 8 X 12 X 15 INCH ROAD STONE MARKED "R" ON THE NORTH SIDE HE PLANTED FOR THE SOUTHEAST CORNER OF SECTION 27-16-10 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
  - 2) THE SECOND ROAD EXTENDS WEST ON THE SECTION LINES FOR 2,641 FEET TO THE TO THE 4 X 6 X 4 INCH ROAD STONE MARKED "R" ON THE NORTH FACE HE

PLANTED AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-16-10 TO END THE SECOND ROAD ON THIS ROAD SURVEY

- 3) THE NEW ROADS ARE 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS DESCRIBED
  
- 9) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 86 FOR THE SURVEY OF A STRIP OF LAND DEEDED TO LYON COUNTY FOR ROAD PURPOSES BY HOWARD C. SILFIES FOR THE CONSIDERATION OF ONE HUNDRED (\$100.00) DOLLARS, SAID THAT ON THE 16<sup>TH</sup> DAY OF OCTOBER 1911 HE MADE THE ROAD SURVEY AND THAT HOWARD C. SILFIES AND JOSEPH FULLS, THE TOWNSHIP TRUSTEE WERE PRESENT. **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 28-16-10 ON THIS ROAD SURVEY.  
HIS FIELD NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) BEGINNING AT A POINT ON THE SECTION LINE 804 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 28-16-10 HE PLANTED A LIMESTONE 18" X 9" X 7"; THENCE N. 67°50' W. FOR 289 FEET AND PLANTED A LIMESTONE 15" X 12" X 5"; THENCE S. 79°10' W. FOR 75 FEET AND PLANTED A STONE 20" X 12" X 5"; THENCE S. 36°30' W. FOR 117 FEET TO THE SECTION LINE AND PLANTED A STONE 15" X 10" X 8" AT THE TERMINUS OF THIS ROAD SURVEY
  - 2) SAID LINE AS ABOVE DESCRIBED BEING THE CENTERLINE OF THE SAID STRIP OF LAND WHICH WAS TO BE 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS DESCRIBED
  - 3) THE STONES AS DESCRIBED WERE PLANTED FIRMLY IN THE GROUND AND MARKED THE BEGINNING, EACH ANGLE, AND THE TERMINUS OF SAID LINE
  - 4) ENTERED THIS 6<sup>TH</sup> DAY OF NOVEMBER 1911 BY MATHEW BROWN, COUNTY SURVEYOR, BY J. MAX YINGLING, DEPUTY
  - 5) THE ABOVE ROAD IS RECORDED IN BOOK "E" ON PAGE 23 OF THE ROAD RECORDS
  - 6) THE DEED IS ON FILE AT THE REGISTER OF DEEDS
  
- 10) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROD NUMBER 666 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 23 FOR A ROAD DEEDED TO LYON COUNTY.  
THE SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) BEGINNING AT A POINT ON THE SECTION LINE 804 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 28-16-10 HE PLANTED A LIMESTONE 18" X 9" X 7"; THENCE N. 67°50' W. FOR 289 FEET AND PLANTED A LIMESTONE 15" X 12" X 5"; THENCE S. 79°10' W. FOR 75 FEET AND PLANTED A STONE 20" X 12" X 5"; THENCE S. 36°30' W. FOR 117 FEET TO THE SECTION LINE AND PLANTED A STONE 15" X 10" X 8" AT THE CLOSING POINT OF THIS ROAD SURVEY
  - 2) THE ABOVE LINE AS DESCRIBED BEING THE CENTERLINE OF A STRIP OF LAND 40 FEET WIDE DEEDED TO LYON COUNTY FOR ROAD PURPOSES, THE LAND LYING 20 FEET ON EACH SIDE OF THE LINE AS DESCRIBED, AND THE STARTING POINT, EACH ANGLE, AND THE CLOSING POINT ON THE ABOVE LINE BEING MARKED BY STONES SET FIRMLY IN THE GROUND AS DESCRIBED
  - 3) FOR A LARGE PLAT OF THE ABOVE ROAD SEE BOOK 1 ON PAGE 86 OF THE SURVEYORS RECORD
  - 4) ENTERED NOVEMBER 6, 1911 AND RECORDED DECEMBER 6, 1911 BY MATTHEW BROWN, COUNTY SURVEYOR, BY J. MAX YINGLING, DEPUTY
  
- 11) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 1  
ON AUGUST 2, 1909 A PETITION SIGNED BY H. C. SELFIES AND OTHERS FOR THE LOCATION AND VACATION OF CERTAIN ROADS IN TOWNSHIP 16-10 WAS

PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROADS WERE VIEWED ON SEPTEMBER 2, 1909, AND THE FINAL ORDER FOR THE LOCATION OF THE FOLLOWING ROAD WAS ISSUED.

- 1) THE ROAD LOCATED EXTENDS EAST FOR 1 MILES TO THE SOUTHWEST CORNER OF SECTION 26-16-10 TO BEGIN THIS ROAD THAT IS 40 FEET WIDE
  - 2) THE ROAD LOCATED EXTENDS WEST FOR 1/2 MILE TO END THIS ROAD THAT IS 40 FEET WIDE
- 12) REA BOOK NUMBER 30 ON PAGE 14 SHOWS A **STONE** AT THE NORTHWEST CORNER OF SECTION 34-16-10.
- 1) 25' SE TO A WITNESS PIN 18" EAST OF A CORNER FENCE POST
  - 2) 25' SW TO A WITNESS PIN 9" NORTH OF A POST
- 13) AI CHAMNESS, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 108 ORDERED BY GWENNIE THOMAS AND SARAH A. ELDRED FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS OF FIVE TRACTS OF LAND, EACH CONTAINING 80 ACRES MORE OR LESS, AND ARE DESCRIBED AS THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 28; THE SOUTH 1/2 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 21, ALL IN TOWNSHIP 16 SOUTH, RANGE 10 EAST, SAID THAT **HE SET A SQUARE IRON PIN** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 28-16-10 ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN ON JULY 6, 1936, THE REPORT WAS FILED JULY 28, 1936, AND THE SURVEY WAS RECORDED ON AUGUST 21, 1936. HIS FIELD NOTES ARE IN BOOK "R" ON PAGE 26 IN THE KRETSINGER COLLECTION OF FIELD BOOKS
- 1) 30' SOUTHEAST OF A CORNER FENCE POST
  - 2) 29.66' SW OF A TELEPHONE POLE
  - 3) 22.5' EAST AND 20' NORTH AND SOUTH OF FENCES
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 4) 2,646.5' WEST TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 28-16-10
  - 5) 5,293' WEST TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 28-16-10, IN LINE WITH A WIRE FENCE TO THE SOUTH AND AN OSAGE HEDGE TO THE NORTH
  - 6) 1,324.5' NORTH TO AN IRON PIN HE SET FOR THE PERMANENT EAST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 28-16-10
  - 7) 2,649' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 28-16-10
  - 8) 3,973.5' NORTH TO THE IRON PIN HE SET FOR THE PERMANENT EAST 1/16<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 28-16-10
  - 9) 5,298' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 28-16-10, ABOUT IN THE CENTER OF THE NORTH-SOUTH ROAD
  - 10) 6,622.75' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT EAST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 21-16-10
  - 11) 7,947.5' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 21-16-10
  - 12) 10,597' NORTH TO THE GOVERNMENT CORNERSTONE HE FOUND IN PLACE AT THE NORTHEAST CORNER OF SECTION 21-16-10, UPRIGHT WITH 3 MARKS ON THE SOUTH SIDE AND 3 MARKS ON THE WEST EDGE OF THE STONE, AND THE STONE APPEARS TO BE IN LINE WITH A FENCE EASTWARD IN THE DISTANCE
- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 2, 2010 FOR PROJECT NUMBER 09354-02, SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 16, 10 FOR A SURVEY FOR A

TRACT IN THE NORTHEAST 1/4 OF SECTION 33-16-10 FOR GATES REALTY, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 33-16-10, BUT HE DID **NOT** FIND THE STONE. HE FOUND THE STONE THAT WAS SET BY ALVA J. SMITH IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 157 **AT 3 CHAINS SOUTH OF THE NORTHEAST CORNER OF SECTION 33-16-10.** HE DEEMED THAT THE SECTION CORNER WAS BOTH **LOST** AND **OBLITERATED.** HE RESET THIS SECTION CORNER AT 3 CHAINS NORTH OF THE STONE THAT WAS SET BY SMITH AND IN THE CENTER OF THE EAST-WEST ROAD AS PER A SURVEY BY AI CHAMNESS RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 108. HE SAID THAT THIS POSITION FITS THE RECORD CALL TO THE ROAD TO THE EAST AND TO THE NORTH. **HE SET A COTTON GIN SPINDLE IN A ROCK LEDGE** FOR THE NORTHEAST CORNER OF SECTION 33-16-10.

- 1) 43.05' NW TO A 40 D NAIL IN THE SOUTH FACE OF A POWER POLE
- 2) 41.95' SE TO THE TOP CENTER OF A TELEPHONE RISER
- 3) 42.15' NE TO A 40 D NAIL IN THE WEST FACE OF A DEADMAN POLE
- 4) 5.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 320 TO THE WEST
- 5) 1.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "D" NORTH-SOUTH
- 6) 198.0' SOUTH TO SMITH'S 1903 PERMANENT SURVEY STONE [BOOK "F", PAGE 157. SEE ALSO REPORTS IN VAULT PACKETS]

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 2,666.00' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 33-16-10

NORTHWEST CORNER SECTION 34-16-10