

NORTH 1/4 CORNER SECTION 35, TOWNSHIP 16 SOUTH, RANGE 10 EAST

- 1) ON PAGE 129 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 15" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-16-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.75 CHAINS WEST TO THE 20" X 16" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-16-10
 - 2) 39.75 CHAINS EAST TO THE 30" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-16-10

- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 165, AN AGREEMENT SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 135 DATED JULY 10-13, 1888 FOR LESTER NOPPER AND F. WILLIAMSON TO ESTABLISH THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4, THE CORNERS OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4, AND THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 , ALL IN SECTION 27, TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE IN THE GROUND IN GOOD CONDITION** AT THE NORTH 1/4 CORNER OF SECTION 35-16-10 ON THIS AGREEMENT SURVEY. THIS SURVEY WAS FILED IN VOLUME 41 ON PAGE 414 ON OCTOBER 18, 1888 IN THE REGISTER OF DEEDS OFFICE AND SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 16-10 IS A COPY OF THE RECORDED SURVEY.
HIS NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 7,887' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-16-10

NORTH QUARTER CORNER SECTION 35-16-10