

**NORTHWEST CORNER SECTION 35, TOWNSHIP 16 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 129 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 4"** FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-16-10.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.75 CHAINS EAST TO THE 18" X 15" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-16-10
- 2) 79.50 CHAINS EAST TO THE 30" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-16-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 75 DATED NOVEMBER 27, 1883 FOR A ROAD IN TOWNSHIP 16, RANGES 10, 11, 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 27-16-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR 1/4<sup>TH</sup> OF A MILE TO A STONE HE SET FOR A TURN TO THE WEST IN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 8 MILES TO THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE; THEN EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THENCE EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4-3/4 MILES TO THE SOUTHWEST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 248 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 TO 580 PETITION BY L. W. HUTCHASON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10, 16-11, 16-12 AND 16-13 [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED IN NOVEMBER 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, EXCEPT ON THE SOUTH LINE OF SECTION 28-16-12 ITS WIDTH IS TO BE 80 FEET FOR 8 RODS, ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 27-16-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND OR SET; THEN EXTENDS WEST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET A 1/4 OF A MILE NORTH OF THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN SOUTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN WEST ON THE SECTION LINES FOR 1-1/2 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 8 MILES TO THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE; THEN EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THENCE EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4-3/4 MILES TO

THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY.

- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 165, AN AGREEMENT SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 135 DATED JULY 10-13, 1888 FOR LESTER NOPPER AND F. WILLIAMSON TO ESTABLISH THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4, THE CORNERS OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4, AND THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4, ALL IN SECTION 27, TOWNSHIP 16, RANGE 10, SAID THAT HE DID **NOT** FIND THE STONE AT THE SOUTHEAST CORNER OF SECTION 27-16-10 ON THIS AGREEMENT SURVEY. THIS SURVEY WAS FILED IN VOLUME 41 ON PAGE 414 ON OCTOBER 18, 1888 IN THE REGISTER OF DEEDS OFFICE AND SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 16-10 IS A COPY OF THE RECORDED SURVEY. HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-16-10 SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-16-10 ON THE TOWNSHIP LINE, AND FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-16-10 TO THE STONE HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-16-10 ON THIS **PERMANENT SURVEY**.
- 5) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 663 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 82 FOR H. C. SILFIES, PRINCIPAL PETITIONER, FOR THE SURVEY OF A ROAD TO BE LOCATED ON THE SECTION LINE BETWEEN SECTIONS 27 & 34, AND 28 & 33 IN TOWNSHIP 16, RANGE 10, AND THE VACATION OF A PORTION OF THE ROAD IN SECTIONS 27 & 28 OF THE ABOVE TOWNSHIP AND RANGE AS VIEWED BY THE COUNTY COMMISSIONERS ACTING AS VIEWERS AND THE COUNTY SURVEYOR ON SEPTEMBER 2, 1909, SURVEYED ON MARCH 29 & 21, 1910 AND ENTERED IN THE PERMANENT SURVEY BOOK ON MARCH 31, 1910, SAID THAT THE CORNER STONE AT THE SOUTHEAST CORNER OF SECTION 27-16-10 WAS OUT. HE LOCATED THE SOUTHEAST CORNER OF SECTION 27-16-10 AND **HE PLANTED A ROAD STONE 8 X 12 X 15 INCHES MARKED "R" ON THE NORTH SIDE** FOR THE SOUTHEAST CORNER OF SECTION 27-16-10 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "E" ON PAGE 20.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) THIS FIRST ROAD EXTENDS WEST ON THE SECTION LINES FOR 1,317 FEET TO THE 2 X 14 X 12 INCH ROAD STONE HE PLANTED ON THIS ROAD SURVEY; THENCE N. 87°45' W. FOR 3,955 FEET TO THE 6 X 8 X 12 INCH ROAD STONE MARKED "R" ON THE NORTH SIDE HE PLANTED AT A POINT ON THE SECTION LINE RUNNING NORTH AND SOUTH BETWEEN SECTIONS 27-16-10 AND 28-16-10 AT 152 FEET NORTH OF THE EXISTING STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-16-10 AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY
- 6) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 663 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 20 PETITION BY H. C. SILFIES AND OTHERS FOR THE LOCATION AND VACATION OF A ROAD IN TOWNSHIP 16-10 [PACKET 909 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS ON SEPTEMBER 2, 1909, AND WAS GRANTED ON JANUARY 2, 1911, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 34-16-10 TO

BEGIN THIS ROAD SURVEY. HE SAID TO SEE SURVEYOR RECORD 1 ON PAGE 82 FOR DESCRIPTIONS OF THE MARKS AND A LARGE PLAT.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1,317 FEET TO THE 2" X 14" X 12" ROAD STONE HE PLANTED ON THIS ROAD SURVEY; THENCE N. 87°45' W. FOR 3,955 FEET TO THE 6" X 8" X 12" ROAD STONE MARKED "R" ON THE NORTH SIDE HE PLANTED AT 152 FEET NORTH OF THE EXISTING STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-16-10 TO END THE FIRST ROAD ON THIS ROAD SURVEY
  - 2) THE ROAD WAS 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS DESCRIBED
- 7) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 1  
ON AUGUST 2, 1909 A PETITION SIGNED BY H. C. SELFIES AND OTHERS FOR THE LOCATION AND VACATION OF CERTAIN ROADS IN TOWNSHIP 16-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROADS WERE VIEWED ON SEPTEMBER 2, 1909, AND THE FINAL ORDER FOR THE LOCATION OF THE FOLLOWING ROAD WAS ISSUED.
- 1) THE ROAD LOCATED BEGINS AT THE SOUTHWEST CORNER OF SECTION 26-16-10 AND EXTENDS WEST FOR 1-1/2 MILES TO END THIS ROAD THAT IS 40 FEET WIDE
- 8) REA BOOK 30 ON PAGE 14 AND DATED JUNE 1944 SAID THAT **THEY FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 35-16-10.
- 1) 25' SE TO A PIN ABOUT 18' EAST OF A FENCE POST
  - 2) 25' SW OF THE STONE IS A WITNESS PIN 8" OR 9" NORTH OF A POST

NORTHWEST CORNER SECTION 35-16-10