

WEST 1/4 CORNER SECTION 02, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 291 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 13" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 3-16-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 41.27 CHAINS NORTH TO THE 20" X 8" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-16-11 ON THE 3RD STANDARD PARALLEL
 - 2) 40.00 CHAINS SOUTH TO THE 21" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-16-11

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 139 & 140 DATED JANUARY 3-8, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 2, 3 & 4 IN TOWNSHIP 16, RANGE 11, SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 2-16-11 ON LINE BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 2-16-11 ON THE 3RD STANDARD PARALLEL AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 2-16-11 AT 40.00 CHAINS NORTH OF THE SOUTHWEST CORNER OF SECTION 2-16-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 2-16-11
 - 2) 40.91 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 2-16-11 ON THE 3RD STANDARD PARALLEL
 - 3) 19.90 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE NE1/4 OF SECTION 3-16-11
 - 4) 39.80 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 3-16-11

WEST QUARTER CORNER SECTION 02-16-11