

WEST 1/4 CORNER SECTION 03, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 295 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-16-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 41.54 CHAINS NORTH TO THE 30" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-16-11 ON THE 3RD STANDARD PARALLEL
 - 2) 40.00 CHAINS SOUTH TO THE 23" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-16-11

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 139 & 140 DATED JANUARY 3-8, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 2, 3 & 4 IN TOWNSHIP 16, RANGE 11, SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 3-16-11 ON LINE BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 3-16-11 ON THE 3RD STANDARD PARALLEL AND THE STONE THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 3-16-11 AT 40.00 CHAINS NORTH OF THE SOUTHWEST CORNER OF SECTION 3-16-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 3-16-11
 - 2) 20.00 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 3-16-11
 - 3) 41.05 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 3-16-11 ON THE 3RD STANDARD PARALLEL

WEST QUARTER CORNER SECTION 03-16-11